Precision Socket Strip Ultra Low Profile 2,54 mm

Series **008**

Product group **1**



Rated current	3,0 A
Rated voltage	150 VRMS / VDC
Withstand voltage	1000 VRMS for one minute
Material contact	Copper alloy
Material clip	BeCu
Material insulator	High temp. thermoplast UL94V-0
Operating temperature	-55°C to +125°C
Max. soldering temper.	260°C for 10 seconds

All dimensions in mm.

pitch **2,54**

termination

mating pin size **ø 0,40-0,56** **□ 0,25x0,45**

max. pincount **064**

Variation



1

Contact type

D2



Clip style:
S = 4 finger clip

Plating:
T = Sn
F = Au
H = Au 0,75 µ

Variation | No. of contacts (002,... - 064) | Contact type | Clip style | Plating contact | Plating clip (F,H)

www.mpe-connector.de

Order code: 008-1-???-D-D2STF-XS0

Mating series	034	038	035	037	367
see page	2-4	2-6	2-7	2-8	2-9

MPE-Garry GmbH • Schäfflerstraße 13 • 87629 Füssen • Germany • Phone: +49 (0) 83 62 / 91 56-0 • Fax: +49 (0) 83 62 / 91 56-500 • Email: vk@mpe-connector.de • www.mpe-connector.de