


3AG Fast-Acting Type



ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
100%	35	4 hours, Minimum
110%	4-30	4 hours, Minimum
135%	4-35	1 hour, Maximum
200%	4-30	10 seconds, Maximum
200%	35	20 seconds, Maximum

APPROVALS:[®] Listed by Underwriters Laboratories and Certified by CSA through 30 amperes.

DESIGN STANDARDS: U.L. Standard 275.



FUSE DIMENSIONS:

Diameter: $\frac{1}{4}$ "
Length: $1\frac{1}{4}$ "

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
311 004	4	32
311 005	5	32
311 006	6	32
311 007	7	32
311 07.5	7½	32
311 008	8	32
311 010	10	32
311 012	12	32
311 015	15	32
311 025	25	32
311 030	30	32
311 035	35	32

For 20-ampere rating use 307 020.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

[0311008.H](#) [0311025.M](#) [031103.2H](#) [0311005.TXN](#) [0311012.M](#) [0311015.TXN](#) [0311006.M](#) [0311004.M](#) [0311006.H](#)
[0311035.H](#) [0311035.M](#) [0311007.M](#) [0311035.TXN](#) [0311008.M](#) [0311005.M](#) [0311010.H](#) [0311015.H](#) [0311007.H](#)
[0311025.TXN](#) [0311005.H](#) [031103.2M](#) [0311012.H](#) [031107.5H](#) [0311030.TXN](#) [0311025.H](#) [031107.5M](#) [0311004.H](#)
[0311030.M](#) [0311015.M](#) [0311030.H](#) [0311010.TXN](#) [0311010.M](#) [0311015.XBP](#)