


SPRING-LOADED PINS

DISCRETE SPRING-LOADED CONTACTS • POWER SPRING PINS

0851

0851-0-15-20-82-14-11-0


Solder Mount in .090 min. mounting hole or Surface Mount, .087" Ø minimum pad



0853

0853-0-15-20-82-14-11-0


Solder Mount in .090 min. mounting hole or Surface Mount, .087" Ø minimum pad



0852

0852-0-15-20-83-14-11-0


Power spring pin
Solder Mount in .045 min. mounting hole



0854

0854-0-15-20-82-14-11-0


Power spring pin, Soldercup
Accepts wire sizes up to .057" Dia.



0855

0855-0-15-20-82-14-11-0


Power spring pin, Wire crimp termination for wire sizes 16 AWG Max. / 20 AWG Min.



0856

0856-0-15-20-82-14-11-0


Power spring pin
Solder Mount in .045 min. mounting hole



0859

0859-0-15-20-82-14-11-0


Power spring pin
Surface Mount, .100" Ø suggested pad size



0873

0873-0-15-20-82-14-11-0


Solder Mount in .090 min. mounting hole or Surface Mount, .087" Ø minimum pad



0850

0850-0-15-20-83-14-11-0


Power spring pin, Solder Mount in .090 min. mounting hole
Also available on 32mm wide carrier tape: 500 parts per 13" reel
Order as: 0850-0-57-20-83-14-11-0



0858

0858-0-15-20-82-14-11-0


Power spring pin
Solder Mount in .045 min. mounting hole



0878

0878-0-15-20-82-14-11-0

Power spring pin
Solder Mount in .045 min. mounting hole



Material Specifications:

Sleeve & Plunger Material: Copper Alloy
Spring Material: Stainless Steel 302
Sleeve & Plunger Finish: 20 µ" Gold over Nickel
Spring Finish: 10 µ" Gold over Nickel
Dimensions: Inches
Tolerances On: Lengths: ± .006
 Diameters: ± .002
 Angles: ± 2°



Mechanical & Electrical Specifications:

Durability: Up to 1,000,000 cycles
Rated Current (Free air):
 Continuous 9 amps @ 10° C temperature rise
Contact Resistance: 20 mΩ max.
Environmental Specifications:
Operating temperature range:
 -55/+125° C (discontinuous)
82, 83, Springs are not interchangeable

Order Code: 08XX - X - XX - 20 - 8X - 14 - 11 - 0

Spring Number

Spring Number	Mid. Stroke	Max. Stroke	Force @ Mid. Stroke	Initial Force (Pre-Load)
*82	.045	.090	120 g	25 g
83	.045	.090	120 g	25 g



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mill-Max:](#)

[0851-0-15-20-82-14-11-0](#) [0853-0-15-20-82-14-11-0](#) [0855-0-15-20-82-14-11-0](#) [0856-0-15-20-82-14-11-0](#) [0854-0-15-20-82-14-11-0](#) [0850-0-15-20-83-14-11-0](#) [0850-0-15-00-00-00-11-0](#) [0851-0-15-00-00-00-11-0](#) [0861-0-15-20-82-14-11-0](#)