

# 09 "Lineman's Pliers", High Leverage Combination Pliers

DIN ISO 5746



09 01 240



09 02 240



Powerful gripping zones for pulling, squeezing and leverage performance

- ▶ solid construction for heaviest impact; universally applicable
- ▶ high transmission ratio for easy cutting
- ▶ requires 40% less effort compared with conventional combination pliers thanks to optimised transmission ratio
- ▶ ergonomically optimised handle shape for firm contact to the hand and fatigue reducing operation
- ▶ particularly striking crosswise serrated gripping zone in the jaws - for strong gripping and pulling
- ▶ additional gripping zone below the articulated joint for powerful leverage and pressing performance
- ▶ with cutting edges for soft and hard wire
- ▶ cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- ▶ high grade special tool steel, oil-hardened and tempered



Crosswise serrated gripping zone for firm gripping and pulling on construction of railings



Gripping zone below the joint for powerful leverage



Long cutting edges for cutting flat cables

Article-No.	EAN-Code	Head	Handles	Cutting capacities		g
				●	●	
Length mm				ø mm	ø mm	
09 01 240	064992	polished	with non-slip plastic coating	4,6	3,0	465
09 02 240	065005	polished	with two-colour dual component handles	4,6	3,0	490