


Number of contacts

30, 20



Male connectors

Identification			Number of contacts	Contact arrangement	Part No.	Performance levels according to IEC 60603-2. Explanation chapter 00		
					3	2	1	
Male connector with solder pins 2.5 mm	30		Performance level 3 on request	Performance level 1 on request	09 29 130 6902			
with fixing flange	20				09 29 120 6902			
with fixing flange, SMC	30				09 29 130 6519 ^{d)}			
without fixing flange	30				09 29 130 6592			
without fixing flange, SMC	30				09 29 130 6569 ^{d)}			
Male connector with solder pins 4.0 mm	30				09 29 130 6903			
with fixing flange	20				09 29 120 6903			
with fixing flange, SMC	30				09 29 130 6520 ^{d)}			
without fixing flange	30				09 29 130 6593			
without fixing flange, SMC	30				09 29 130 6570 ^{d)}			
Male connector with solder pins 13 mm	30				09 29 130 6577			
with fixing flange	20				09 29 120 6577			
with fixing flange, SMC	30				09 29 130 6521 ^{d)}			
Male connector with wrap posts ¹⁾ 13 mm	30				09 29 130 6907			
Male connector with press-in pins 5.0 mm	30				09 29 130 6904			
with fixing flange	20				09 29 120 6904			
without fixing flange	30				09 29 130 6504			
Male connector with press-in pins 13 mm	30				09 29 130 6985 ^{w)} 09 29 130 6974 [•]			
with fixing flange	20				09 29 120 6974 [•]			
without fixing flange	30				09 29 130 6574 [•]			

* Wrap posts for interfacing selectively gold plated (performance level 3)

¹⁾ To be used only for wire wrap termination^{d)} CTI > 400^{w)} Wrap posts not for interfacing, no performance level