Our commitment. Your advantage.

Products

Documentation

Resources

Home > Products > By Type > Socket/Card Products > Product Feature Selector > Product Details

My Account

Customer Support

0000 404 Decelust Details

8060 - 1G4 Product Details



8060 -1G4 (1 - 1437504 - 7)

✓ Active_

Transistor Sockets and Adapters

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- ? Socket
- ? Terminal Style = Printed Circuit
- ? Terminal Type = Contact
- Lead Size Accepted = .41 mm
- Lead Length Accepted = 3.18 3.94

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>

Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

? None Available

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

? Product Line Information

Related Products:

? Tooling

Product Features

- Product Type Features:
 Product Type = Socket
 - ? Terminal Type = Contact
 - ? Product Series = 8060 Series
 - ? Sleeve Material = Brass
 - ? Profile = Low

Electrical Characteristics:

Lead Length Accepted (mm [in]) = 3.18 - 3.94
 [0.125 - 0.155]

(Please use the Product Drawing for all design activity)

? Pin Circle Diameter (mm [in]) = 2.54 [0.100]

Termination Related Features:

? Terminal Plating = Gold

Body Related Features:

- ? Terminal Style = Printed Circuit
- ? Number of Terminals = 4
- Post Diameter (mm [in]) = 0.51 [0.020]
- ? Socket Type = TO -5
- ? Terminal Material = Beryllium Copper
- ? Insulator Material = Teflon

Contact Related Features:

? Sleeve Plating = Gold

Configuration Related Features:

Lead Size Accepted (mm [in]) = 0.41 [0.016]

Industry Standards:

- Rohs/ELV Compliance = Rohs compliant, ELV compliant
- ¿ Lead Free Solder Processes = Wave solder capable to 240°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

? Operating Temperature (°C) = -55 - +125

Other:

? Brand = AMP