



1-1907118-3 Product Details


1-1907118-3

TE Internal Number: 1-1907118-3

Active

Fiber Optic Cable Assemblies

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Patch Cord
- Cable Assembly
- LC SECURE Fiber Optic Cable Connector Type, MT-RJ (No Pins) Fiber Optic Cable Connector Type
- Fiber Type = OM2 50/125 Micron
- Cable Assembly Type = LC Duplex SECURE to MT-RJ (No Pins)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information	
Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.	Related Products: <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Designation = Patch Cord • Product Type = Cable Assembly • Fiber Optic Cable Connector Type = LC SECURE, MT-RJ (No Pins) • Cable Assembly Type = LC Duplex SECURE to MT-RJ (No Pins) • Cable Type = Twin Zip <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Insertion Loss (dB) = 0.50 • Return Loss (dB) = 0 <p>Termination Features:</p> <ul style="list-style-type: none"> • Fiber Type (Micron) = OM2 50/125 <p>Dimensions:</p> <ul style="list-style-type: none"> • Cable Diameter (mm [in]) = 1.80 [.071] • Length (M [ft]) = 13.00 [42.65] <p>Body Features:</p> <ul style="list-style-type: none"> • Cable Color = Orange • Connector Color = Orange • Boot Body Style - Left = Standard • Boot Color - Left = Beige/Beige • Boot Body Style - Right = Standard • Boot Color - Right = Beige • Ferrule Material = Ceramic 	<p>Contact Features:</p> <ul style="list-style-type: none"> • Fibre Channel = No <p>Housing Features:</p> <ul style="list-style-type: none"> • Fiber Path Configuration = Pair Flipped <p>Configuration Features:</p> <ul style="list-style-type: none"> • Mode = Multimode • Number of Fibers = 2 • Cable Buffering = Tight Buffered • Connector(s) Exit Angle to Connector(s) Exit Angle = 180° to 180° <p>Industry Standards:</p> <ul style="list-style-type: none"> • Flammability Rating Type = OFNP (Plenum) Jacket • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Product Availability:</p> <ul style="list-style-type: none"> • Region = Asia, North America, Latin America <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity

Feedback

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



