



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

10 MODIV HSG DR MRKD .100CL

[AMPMODU](#) | [AMPMODU IV/V](#)

1-86148-2

TE Internal Number: 1-86148-2

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **10**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**

Color **Black**

Product Drawings

[ASSEMBLY, MOD IV, HOUSING WITH SPECIAL MARKING DOUBLE ROW, .100 X .100CL, CRIMP SNAP-IN](#)

PDF **(TIFF AVAILABLE)**
English

[ASSEMBLY, MOD IV, HOUSING WITH SPECIAL MARKING DOUBLE ROW, .100 X .100CL, CRIMP SNAP-IN](#)

PDF **(TIFF AVAILABLE)**
English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF
English

Application Specification

[AMPMODU MOD IV, IV1/2, And V Receptacles And Housings](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing	2.54 mm [.1 in]
Connector Style	Receptacle
Strain Relief	With
Connector Type	Housing
Product Type	Connector
Applies To	Wire/Cable

Configuration Features

Number of Positions	10
Number of Rows	2

Electrical Characteristics	Operating Voltage	250 VAC
Body Features	Color	Black
Contact Features	Contact Type	Socket
	Contact Base Material	Beryllium Copper
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Connector Lock	Without
	Mating Alignment	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Thermoplastic
	Housing Configuration	Both Ends Closed
	Housing Color	Black
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	250
	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	
