

Index

Series Swisstac

	Description	Page 583
	Product Assembly	Page 584
	Mounting Instruction	Page 585
	Product Range	
	- pushbuttons for standard mounting	Page 591
	- pushbuttons for flush mounting	Page 608
	- accessories / spare parts	Page 622
	Technical Data	Page 638
	Drawing / Dimension / Layouts	Page 642
	Circuit Drawing	Page 657
Marking	Page 667	

SWISSTAC - Three crucial advantages!

Easy storage in minimum space
Every SWISSTAC switch can be altered very simply any number of times, and afterwards added to, modified or adapted. This highly modular concept means that only a few subassemblies reducing storage costs.

All connections on one plane

All the terminals are arranged at the same level, are clearly laid out and fully accessible even when in close-packed arrays. Three colours provide optical help to make connections easier.

Ideal for switch interlock systems

SWISSTAC switches can be mechanically combined in many ways to form switch interlock systems and in fact in rows of up to 20 switches. This means that complicated protection and relay interlocks are unnecessary. Individual and irregular spacings between the switches of an array are no problem either.

CE

Our products are marked with the internationally approved CE low-voltage safety standard.

General information

Swisstac, a modularly constructed control switch system, offers the user a wide range of products: buzzers, illuminated pushbuttons and pushbuttons, indicators, emergency stop switches, push-pull illuminated switches, keylock switches and selector switches, as well as switch interlock systems in the front-facing protection classes IP 40 and IP 65.

The front dimensions of the switch units are: 18 mm dia., 18 x 18 mm, 24 mm dia., 24 x 24 mm. For flush mounting, dimensions 25 mm dia., 24 x 24 mm, 24 x 30 mm are also available.

Construction

SWISSTAC switches are of modular construction and are divided into the following three groups:

- Front section: Man/switch interface and status indicator two-part lens for engraving, film insert or printing
- Intermediate section: Latching/ pulse facility, lamp holder, latch function
- Intermediate section with switching mechanism and lamp holder, which is available in two versions: T: 5.5 max., 1.2 W and midjet grooved T 1 3/4 max.

1.2 W.

- Terminal block: up to a max. of five switching elements can be joined together in one switch terminal block. Are supplied mounted serially on intermediate sections.

Can be disassembled easily for wiring.

Marking

Engraved, printed film inlay see under 'Marking' page 667.

Illumination

Perfect illumination of the lenses supplied in various colours is guaranteed by the incandescent lamps midjet grooved T 1 3/4 and T 5.5 (6-60V9).

Where supply voltages are over 60 V, a voltage-reduction element (ext. protective series resistor or capacitor) must be used. Because of high surface temperature, the protective series resistor may not be soldered direct onto the connections of the pushbuttons.

Multi-LED midjet grooved T 1 3/4 and T 5.5 (6, 12, 24, 48 V) are available in the colours red, yellow and green.

Switch position indicator

When the pushbutton with latch function is operated, the lens latches in mechanically. The position of the lens makes the switch position evident at all the times.

Keylock switches

Standard lock

1 Standard number is B2 300. We supply B2 300 without specifications of the lock numbers. Four further standard locks are B2 301 - B2 304. This additional designation should be quoted when ordering. A further 95 locks are available in or without passepartout version on request. 2 keys are supplied per keylock switch.

Spare keys for a standard lock can be ordered under Type no. 240-2001-00 (please quote lock number). Example: 240-200-00 B2 300.

Emergency stop switch with key to unlock

Standard lock is B2 390. Four further standard locks are B2 391 - B2-394. When ordering this additional designation should be quoted. Spare keys for standard lock can be ordered under Type no. 240-3001-00 (please quote lock). Example: 240-3001-00 B2 390.

Two keys are supplied per emergency stop switch.

Emergency Stop Switch, foolproof with key to unlock


Kaba safety switch. Standard lock number is 1001. Spare keys can be ordered under Type no. 240.4001-00 1001.

2 keys are supplied per emergency stop switches.

All measurements in mm


Technical specifications subject to modification.

illuminated-/pushbutton



- 1 lens
- 2 front bezel
- 3 fixing nut
- 4 spring with pin for changing from maintained to momentary
- 5 intermediate section
- 6 holder for switching element
- 7 switching element block
- 8 switching element

pushbutton-/illuminated pushbutton for flush mounting




- 1 lens
- 2 front bezel
- 3 front bezel set f. fl. mounting
- 4 front panel
- 5 fixing nut
- 6 spring with pin f. changing from main to mom
- 7 intermediate section
- 8 holder f. switching element
- 9 switching element block
- 10 switching element

illuminated-/pushbutton 35mm

The switch is mounted in a fascia or control panel in three steps:

1. Detach terminal block as in drawing, remove fixing nut
2. Insert switch from the front in fascia/control panel
3. Reassemble the switch in the reverse order

To detach terminal block



Note: Type-identification on legs of actuator

illuminated-/pushbutton 55 - 70 mm


The switch is mounted in a fascia/control panel in two steps:

1. Insert switch from back side in fascia/control panel
2. Snap on bezel and tighten fixing nut

Lens


Bezel

Illuminated pushbutton



illuminated-/pushbutton 55 - 70 mm sealing gland and -ring

The first time the button is pressed, the gland is forced into its groove and becomes effective.



indicator 30 - 70 mm


The indicator is mounted in a fascia/control panel in two steps:

1. Insert indicator from back side in fascia/control panel
2. Snap on bezel and tighten fixing nut

Lens


Bezel

Indicator



indicator 30 - 70 mm sealing gland, -ring and press ring

The press ring is fitted between gland and lens. The seal is effective when the lens is snapped into place.



emergency stop switch turn to release 55 - 70 mm

The switch is mounted in a fascia or control panel in three steps:

1. Detach front section just in released position, as in drawing
2. Insert switch from back side in fascia/control panel
3. Snap on front section and tighten fixing nut

Important for IP 65


With models to IP 65, the sealing ring 1) is already fitted
This must be removed if the SWISSTAC emergency
Stop identity plate (IP 65 model) is used.

Sealing ring2) is fitted as standard
in models to IP 65.

Zero position

Identity plate

Wiring diagram



emergency stop switch with key release 55 - 70 mm

The switch is mounted in a fascia or control panel in three steps:

1. Detach front section, just in released position, as in drawing, remove fixing nut
2. Insert switch from back side in fascia/control panel
3. Snap on front section and tighten fixing nut

Important for IP 65


With models to IP 65, the sealing ring1) is already fitted
This must be removed if the SWISSTAC emergency
Stop identity plate (IP 65 model) is used.

Sealing ring2) is fitted as standard
in models to IP 65.

Zero position

Identity plate


Wiring diagram



emergency stop switch foolproof

Hint for mounting: the torque with which the fixing nut is tightened must not exceed 50 Ncm.

Hint for dismantling: dismantling of switching element just with dismantling tool.




keylock switch 45mm

The switch is mounted in a fascia or control panel in three steps:

1. Detach terminal block as in drawing, remove fixing nut
2. Insert switch from front side in fascia/control panel
3. Reassemble the switch in the reverse order

To detach terminal block




keylock switch 55 mm

The switch is mounted in a fascia/control panel in three steps:

1. Remove front section as in drawing
2. Insert switch from back side in fascia/control panel
3. Snap on front section (see Note) and tighten fixing nut

Zero position

Wiring diagram



To assemble, the key must be at the zero position, the symbol **0** is at the top, and on the terminal block the circuit diagram is uppermost.


keylock switch 70 mm

The switch is mounted in a fascia/control panel in three steps:

1. Remove front section as in drawing
2. Insert switch from back side in fascia/control panel
3. Snap on front section (see Note) and tighten fixing nut.

Zero position

Wiring diagram




To assemble, the key must be at the zero position, the symbol **0** is at the top, and on the terminal block the circuit diagram is uppermost.

selector switch 45 mm

The switch is mounted in a fascia or control panel in three steps:

1. Detach terminal block as in drawing, remove fixing nut
2. Insert switch from front side in fascia/control panel
3. Reassemble the switch in the reverse order

To detach terminal block




selector switch 55 mm

The switch is mounted in a fascia/control panel in three steps:

1. Remove front section as in drawing
2. Insert switch from back side in fascia/control panel
3. Snap on front section (see Note) and tighten fixing nut

Zero position

Wiring diagram



To assemble, the lever must be at the zero position, the symbol **0** is as the top, and on the terminal block the circuit diagram is uppermost.


selector switch 70 mm

The switch is mounted in a fascia/control panel in three steps:

1. Remove front section as in drawing
2. Insert switch from back side in fascia/control panel
3. Snap on front section (see Note) and tighten fixing nut

Zero position

Wiring diagram



To assemble, the lever must be at the zero position, the symbol **0** is at the top, and on the terminal block the circuit diagram is uppermost.


push pull illuminated switch

The switch is mounted in a fascia or control panel in three steps:

1. Detach terminal block as in drawing, remove fixing nut
2. Insert switch from back side in fascia/control panel
3. Reassemble the switch in the reverse order

Push-Pull knob

To detach terminal block



Push-pull knob can be mounted in only one position. Zero position Wiring diagram

buzzer 30 - 55 mm


The alarmbuzzer is mounted in a fascia/control panel in two steps:

1. Insert alarmbuzzer from backside in fascia/control panel
2. snap on bezel and tighten fixing nut

buzzerelement

bezel

buzzerhousing



indicator actuator 35 mm



- 🛒 lens for 35 mm page 622
- 🛒 lamp element block for 35 mm page 632
- 🛒 filament lamp MG T 1 3/4 page 634
- 🛒 LED MG T 1 3/4 page 634

	degree of protection	 18 x 24 mm Typ-Nr.	 18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	component layout	
indicator actuator 35 mm	IP 40	690-6000-00	690-4000-00	690-2000-00	1	1	1	1	0,004
lampholder MG T 1 3/4	IP 65	690-6000-W0	690-4000-W0	690-2000-W0	1	1	2	1	0,005

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

indicator 30 - 70 mm

protection degree IP 40/IP 65 is determined by front bezel and lens



- 🛒 lens page 623
- 🛒 front bezel for illuminated-/pushbutton 55 - 70 mm and indicator 30 - 70 mm page 627
- 🛒 pressure ring page 630
- 🛒 filament lamp MG T 1 3/4 page 634
- 🛒 LED MG T 1 3/4 page 634
- 🛒 filament lamp T 5.5 page 634
- 🛒 LED T 5.5 page 635

	mounting depth	connection method	lamp socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
indicator 30 - 70 mm	30 mm	-	MG T 1 3/4	990-.000-K0	1	2	3		0,004
	45 mm	-	T 5.5	890-.000-K0	1	3	3		0,006
	52 mm	P	MG T 1 3/4	990-.000-0P	1	4	3	1	0,007
	55 mm	-	MG T 1 3/4	990-.000-00	1	5	3		0,007
	67 mm	P	T 5.5	890-.000-0P	1	6	3	1	0,010
	70 mm	-	T 5.5	890-.000-00	1	7	3		0,010

connection method : soldering-/plug-in terminal = -, PCB terminal = P

The indicators 55 mm and 70 mm are as long as the corresponding illuminated pushbuttons and fit to the PCB plug-in base and multi-plug housing.
circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

pushbutton-/illuminated pushbutton actuator 35 mm



- 🛒 lens for 35 mm page 622
- 🛒 filament lamp MG T 1 3/4 page 634
- 🛒 LED MG T 1 3/4 page 634
- 🛒 snap-action switching element block for 35 mm page 631

	degree of pro- tection	switching action	 18 x 24 mm Typ-Nr.	 18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	component layout	
pushbutton-/illuminated pushbutton actuator 35 mm lampholder MG T 1 3/4	IP 40	M	680-6000-00	680-4000-00	680-2000-00	2	1	1	1	0,004
		MA	600-6000-00	600-4000-00	600-2000-00	3	1	1	1	0,004
	IP 65	M	680-6000-W0	680-4000-W0	680-2000-W0	2	1	2	1	0,005
		MA	600-6000-W0	600-4000-W0	600-2000-W0	3	1	2	1	0,005

switching action : momentary action = M, maintained action = MA (changeable to momentary action, reversible)
circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

illuminated-/pushbutton 55 - 70 mm

protection degree IP 40/IP 65 is determined by front bezel and lens



🔍 lens page 623

🔍 front bezel for illuminated-/pushbutton 55 - 70 mm and indicator 30 - 70 mm page 627

🔍 filament lamp MG T 1 3/4 page 634

🔍 filament lamp T 5.5 page 634

🔍 LED T 5.5 page 635

	mounting depth	contacts	switching action	connection method	lamp socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
illuminated-/pushbutton 55 - 70 mm	52 mm	1 NC + 1 NO	MA	P	MG T 1 3/4	901-.000-0P	4	8	3	1	0,013
		2 NC + 2 NO	MA	P	MG T 1 3/4	902-.000-0P	5	8	3	1	0,014
		3 NC + 3 NO	MA	P	MG T 1 3/4	903-.000-0P	6	8	3	1	0,014
		4 NC + 4 NO	MA	P	MG T 1 3/4	904-.000-0P	7	8	3	1	0,018
		5 NC + 5 NO	MA	P	MG T 1 3/4	905-.000-0P	8	8	3	1	0,021
	55 mm	1 NC + 1 NO	MA	-	MG T 1 3/4	901-.000-00	4	9	3		0,013
		2 NC + 2 NO	MA	-	MG T 1 3/4	902-.000-00	5	9	3		0,014
		3 NC + 3 NO	MA	-	MG T 1 3/4	903-.000-00	6	9	3		0,015
		4 NC + 4 NO	MA	-	MG T 1 3/4	904-.000-00	7	9	3		0,019
		5 NC + 5 NO	MA	-	MG T 1 3/4	905-.000-00	8	9	3		0,022
	67 mm	1 NC + 1 NO	MA	P	T 5.5	801-.000-0P	4	10	3	1	0,015
		2 NC + 2 NO	MA	P	T 5.5	802-.000-0P	5	10	3	1	0,016
		3 NC + 3 NO	MA	P	T 5.5	803-.000-0P	6	10	3	1	0,017
		4 NC + 4 NO	MA	P	T 5.5	804-.000-0P	7	10	3	1	0,020
		5 NC + 5 NO	MA	P	T 5.5	805-.000-0P	8	10	3	1	0,023
	70 mm	1 NC + 1 NO	MA	-	T 5.5	801-.000-00	4	11	3		0,015
		2 NC + 2 NO	MA	-	T 5.5	802-.000-00	5	11	3		0,016
		3 NC + 3 NO	MA	-	T 5.5	803-.000-00	6	11	3		0,017
		4 NC + 4 NO	MA	-	T 5.5	804-.000-00	7	11	3		0,021
		5 NC + 5 NO	MA	-	T 5.5	805-.000-00	8	11	3		0,024


contacts : normally closed = NC, normally open = NO

switching action : maintained action = MA (changeable to momentary action, reversible)

connection method : PCB terminal = P, soldering-/plug-in terminal = -

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

emergency stop switch 55 - 70 mm



🛒 label for emergency stop switch page 636

	unlocking	degree of protection	mounting depth	contacts	connection method	24 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	component layout	
emergency stop switch 55 - 70 mm according to VDE max. 2 NC are permitted	twist to release	IP 40	52 mm	1 NC	P	951+2000-0P	9	12	4	1	0,018
				2 NC	P	952+2000-0P	10	12	4	1	0,019
				3 NC	P	953+2000-0P	11	12	4	1	0,020
			55 mm	1 NC	-	951+2000-00	9	13	4		0,018
				2 NC	-	952+2000-00	10	13	4		0,019
				3 NC	-	953+2000-00	11	13	4		0,020
			67 mm	1 NC	P	851+2000-0P	9	14	4	1	0,021
				2 NC	P	852+2000-0P	10	14	4	1	0,022
				3 NC	P	853+2000-0P	11	14	4	1	0,023
			70 mm	1 NC	-	851+2000-00	9	15	4		0,021
				2 NC	-	852+2000-00	10	15	4		0,022
				3 NC	-	853+2000-00	11	15	4		0,023
		IP 65	52 mm	1 NC	P	951+2000-WP	9	12	5	1	0,018
				2 NC	P	952+2000-WP	10	12	5	1	0,019
				3 NC	P	953+2000-WP	11	12	5	1	0,020
			55 mm	1 NC	-	951+2000-W0	9	13	5		0,018
				2 NC	-	952+2000-W0	10	13	5		0,019
				3 NC	-	953+2000-W0	11	13	5		0,020
			67 mm	1 NC	P	851+2000-WP	9	14	5	1	0,021
				2 NC	P	852+2000-WP	10	14	5	1	0,022
				3 NC	P	853+2000-WP	11	14	5	1	0,023
			70 mm	1 NC	-	851+2000-W0	9	15	5		0,021
				2 NC	-	852+2000-W0	10	15	5		0,022
				3 NC	-	853+2000-W0	11	15	5		0,023

Continued on next page

	unlocking	degree of protection	mounting depth	contacts	connection method	24 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	component layout	
emergency stop switch 55 - 70 mm standard lock B2 390, other lock numbers on request according to VDE max. 2 NC are permitted	key to release	IP 40	52 mm	1 NC	P	961+2401-0P	9	12	4	1	0,030
				2 NC	P	962+2401-0P	10	12	4	1	0,031
				3 NC	P	963+2401-0P	11	12	4	1	0,032
			55 mm	1 NC	-	961+2401-00	9	13	4		0,030
				2 NC	-	962+2401-00	10	13	4		0,031
				3 NC	-	963+2401-00	11	13	4		0,032
			67 mm	1 NC	P	861+2401-0P	9	14	4	1	0,033
				2 NC	P	862+2401-0P	10	14	4	1	0,034
				3 NC	P	863+2401-0P	11	14	4	1	0,035
			70 mm	1 NC	-	861+2401-00	9	15	4		0,033
				2 NC	-	862+2401-00	10	15	4		0,034
				3 NC	-	863+2401-00	11	15	4		0,035
		IP 65	52 mm	1 NC	P	961+2401-WP	9	12	5	1	0,030
				2 NC	P	962+2401-WP	10	12	5	1	0,031
				3 NC	P	963+2401-WP	11	12	5	1	0,032
			55 mm	1 NC	-	961+2401-W0	9	13	5		0,030
				2 NC	-	962+2401-W0	10	13	5		0,031
				3 NC	-	963+2401-W0	11	13	5		0,032
			67 mm	1 NC	P	861+2401-WP	9	14	5	1	0,033
				2 NC	P	862+2401-WP	10	14	5	1	0,034
				3 NC	P	863+2401-WP	11	14	5	1	0,035
			70 mm	1 NC	-	861+2401-W0	9	15	5		0,033
				2 NC	-	862+2401-W0	10	15	5		0,034
				3 NC	-	863+2401-W0	11	15	5		0,035

contacts : 1 normally closed = 1 NC, normally closed = NC

connection method : PCB terminal = P, soldering-/plug-in terminal = -

hint:


- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

emergency stop switch foolproof 41 mm

according to EN 418



🛒 label for emergency stop switch page 636

	unlocking	degree of protection	mounting depth	contacts	connection method	27 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	
emergency stop switch foolproof 41 mm	twist to release	IP 65	41 mm	1 NC	-	551-8000-W0	12	16	6	0,025
				1 NC + 1 NO	-	553-8000-W0	13	16	6	0,025
				2 NC	-	552-8000-W0	14	16	6	0,025
standard lock 1001	key to release	IP 65	41 mm	1 NC	-	561-8101-W0	12	16	6	0,047
				1 NC + 1 NO	-	563-8101-W0	13	16	6	0,047
				2 NC	-	562-8101-W0	14	16	6	0,047

contacts : 1 normally closed = 1 NC, normally closed = NC, normally open = NO
connection method : soldering-/plug-in terminal = -
Mounting hint: starting torque for fixing nut max. 50 Ncm
circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652

pushbutton with mushroom-head cap 55 - 70 mm



mushroom-head cap page 625

front bezel for mushroom-head pushbutton 55 - 70 mm page 628

	degree of pro- tection	moun- ting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	(mm)
pushbutton with mushroom-head cap 55 - 70 mm	IP 40	52 mm	1 NC + 1 NO	maintained	P	901-.000-0P	15	17	7	1	0,013
			2 NC + 2 NO	maintained	P	902-.000-0P	16	17	7	1	0,014
			3 NC + 3 NO	maintained	P	903-.000-0P	17	17	7	1	0,014
			4 NC + 4 NO	maintained	P	904-.000-0P	18	17	7	1	0,018
			5 NC + 5 NO	maintained	P	905-.000-0P	19	17	7	1	0,021
		55 mm	1 NC + 1 NO	maintained	-	901-.000-00	15	18	7		0,013
			2 NC + 2 NO	maintained	-	902-.000-00	16	18	7		0,014
			3 NC + 3 NO	maintained	-	903-.000-00	17	18	7		0,015
			4 NC + 4 NO	maintained	-	904-.000-00	18	18	7		0,019
			5 NC + 5 NO	maintained	-	905-.000-00	19	18	7		0,022
		67 mm	1 NC + 1 NO	maintained	P	801-.000-0P	15	19	7	1	0,015
			2 NC + 2 NO	maintained	P	802-.000-0P	16	19	7	1	0,016
			3 NC + 3 NO	maintained	P	803-.000-0P	17	19	7	1	0,017
			4 NC + 4 NO	maintained	P	804-.000-0P	18	19	7	1	0,020
			5 NC + 5 NO	maintained	P	805-.000-0P	19	19	7	1	0,023
		70 mm	1 NC + 1 NO	maintained	-	801-.000-00	15	20	7		0,015
			2 NC + 2 NO	maintained	-	802-.000-00	16	20	7		0,016
			3 NC + 3 NO	maintained	-	803-.000-00	17	20	7		0,017
			4 NC + 4 NO	maintained	-	804-.000-00	18	20	7		0,021
			5 NC + 5 NO	maintained	-	805-.000-00	19	20	7		0,024

contacts : normally closed = NC, normally open = NO

switching action: maintained action = MA (changeable to momentary action, reversible)

connection method : PCB terminal = P, soldering-/plug-in terminal = -

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657


keylock switch 2 positions 45 - 70 mm



front cap for keylock-/selector switch 2 positions page 625

maint. 90° A C mom. 60° A C <tr><th></th><th>degree of protection</th><th>mounting depth</th><th>contacts</th><th>switching action</th><th>connection method</th><th>key removable in</th><th>part no.</th><th>circuit drawing</th><th>technical drawing</th><th>mounting dimensions</th><th>component layout</th><th></th></tr><tr><td rowspan="27">keylock switch 2 positions 45 - 70 mm standard lock B2 300, other lock numbers on request</td><td rowspan="27">IP 40</td><td rowspan="6">42 mm</td><td rowspan="3">1 NC + 1 NO</td><td>M</td><td>P</td><td>A</td><td>781-.401-0P</td><td>21</td><td>21</td><td>8</td><td>1</td><td>0,022</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>771-.401-0P</td><td>20</td><td>21</td><td>8</td><td>1</td><td>0,022</td></tr><tr><td></td><td></td><td>A+C</td><td>761-.401-0P</td><td>20</td><td>21</td><td>8</td><td>1</td><td>0,022</td></tr><tr><td rowspan="3">2 NC + 2 NO</td><td>M</td><td>P</td><td>A</td><td>782-.401-0P</td><td>23</td><td>21</td><td>8</td><td>1</td><td>0,023</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>772-.401-0P</td><td>22</td><td>21</td><td>8</td><td>1</td><td>0,023</td></tr><tr><td></td><td></td><td>A+C</td><td>762-.401-0P</td><td>22</td><td>21</td><td>8</td><td>1</td><td>0,023</td></tr><tr><td rowspan="6">45 mm</td><td rowspan="3">1 NC + 1 NO</td><td>M</td><td>-</td><td>A</td><td>781-.401-00</td><td>21</td><td>22</td><td>8</td><td></td><td>0,022</td></tr><tr><td>MA</td><td>-</td><td>A</td><td>771-.401-00</td><td>20</td><td>22</td><td>8</td><td></td><td>0,022</td></tr><tr><td></td><td></td><td>A+C</td><td>761-.401-00</td><td>20</td><td>22</td><td>8</td><td></td><td>0,022</td></tr><tr><td rowspan="3">2 NC + 2 NO</td><td>M</td><td>-</td><td>A</td><td>782-.401-00</td><td>23</td><td>22</td><td>8</td><td></td><td>0,023</td></tr><tr><td>MA</td><td>-</td><td>A</td><td>772-.401-00</td><td>22</td><td>22</td><td>8</td><td></td><td>0,023</td></tr><tr><td></td><td></td><td>A+C</td><td>762-.401-00</td><td>22</td><td>22</td><td>8</td><td></td><td>0,023</td></tr><tr><td rowspan="15">52 mm</td><td rowspan="3">1 NC + 1 NO</td><td>M</td><td>P</td><td>A</td><td>931-.401-0P</td><td>25</td><td>23</td><td>8</td><td>1</td><td>0,024</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>921-.401-0P</td><td>24</td><td>23</td><td>8</td><td>1</td><td>0,024</td></tr><tr><td></td><td></td><td>A+C</td><td>911-.401-0P</td><td>24</td><td>23</td><td>8</td><td>1</td><td>0,024</td></tr><tr><td rowspan="3">2 NC + 2 NO</td><td>M</td><td>P</td><td>A</td><td>932-.401-0P</td><td>23</td><td>23</td><td>8</td><td>1</td><td>0,025</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>922-.401-0P</td><td>22</td><td>23</td><td>8</td><td>1</td><td>0,025</td></tr><tr><td></td><td></td><td>A+C</td><td>912-.401-0P</td><td>22</td><td>23</td><td>8</td><td>1</td><td>0,025</td></tr><tr><td rowspan="3">3 NC + 3 NO</td><td>M</td><td>P</td><td>A</td><td>933-.401-0P</td><td>27</td><td>23</td><td>8</td><td>1</td><td>0,026</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>923-.401-0P</td><td>26</td><td>23</td><td>8</td><td>1</td><td>0,026</td></tr><tr><td></td><td></td><td>A+C</td><td>913-.401-0P</td><td>26</td><td>23</td><td>8</td><td>1</td><td>0,026</td></tr><tr><td rowspan="3">4 NC + 4 NO</td><td>M</td><td>P</td><td>A</td><td>934-.401-0P</td><td>29</td><td>23</td><td>8</td><td>1</td><td>0,029</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>924-.401-0P</td><td>28</td><td>23</td><td>8</td><td>1</td><td>0,029</td></tr><tr><td></td><td></td><td>A+C</td><td>914-.401-0P</td><td>28</td><td>23</td><td>8</td><td>1</td><td>0,029</td></tr><tr><td rowspan="3">5 NC + 5 NO</td><td>M</td><td>P</td><td>A</td><td>935-.401-0P</td><td>31</td><td>23</td><td>8</td><td>1</td><td>0,032</td></tr><tr><td>MA</td><td>P</td><td>A</td><td>925-.401-0P</td><td>30</td><td>23</td><td>8</td><td>1</td><td>0,032</td></tr><tr><td></td><td></td><td>A+C</td><td>915-.401-0P</td><td>30</td><td>23</td><td>8</td><td>1</td><td>0,032</td></tr>			degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout		keylock switch 2 positions 45 - 70 mm standard lock B2 300, other lock numbers on request	IP 40	42 mm	1 NC + 1 NO	M	P	A	781-.401-0P	21	21	8	1	0,022	MA	P	A	771-.401-0P	20	21	8	1	0,022			A+C	761-.401-0P	20	21	8	1	0,022	2 NC + 2 NO	M	P	A	782-.401-0P	23	21	8	1	0,023	MA	P	A	772-.401-0P	22	21	8	1	0,023			A+C	762-.401-0P	22	21	8	1	0,023	45 mm	1 NC + 1 NO	M	-	A	781-.401-00	21	22	8		0,022	MA	-	A	771-.401-00	20	22	8		0,022			A+C	761-.401-00	20	22	8		0,022	2 NC + 2 NO	M	-	A	782-.401-00	23	22	8		0,023	MA	-	A	772-.401-00	22	22	8		0,023			A+C	762-.401-00	22	22	8		0,023	52 mm	1 NC + 1 NO	M	P	A	931-.401-0P	25	23	8	1	0,024	MA	P	A	921-.401-0P	24	23	8	1	0,024			A+C	911-.401-0P	24	23	8	1	0,024	2 NC + 2 NO	M	P	A	932-.401-0P	23	23	8	1	0,025	MA	P	A	922-.401-0P	22	23	8	1	0,025			A+C	912-.401-0P	22	23	8	1	0,025	3 NC + 3 NO	M	P	A	933-.401-0P	27	23	8	1	0,026	MA	P	A	923-.401-0P	26	23	8	1	0,026			A+C	913-.401-0P	26	23	8	1	0,026	4 NC + 4 NO	M	P	A	934-.401-0P	29	23	8	1	0,029	MA	P	A	924-.401-0P	28	23	8	1	0,029			A+C	914-.401-0P	28	23	8	1	0,029	5 NC + 5 NO	M	P	A	935-.401-0P	31	23	8	1	0,032	MA	P	A	925-.401-0P	30	23	8	1	0,032			A+C	915-.401-0P	30	23	8	1	0,032
	degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout																																																																																																																																																																																																																																																																				
keylock switch 2 positions 45 - 70 mm standard lock B2 300, other lock numbers on request	IP 40	42 mm	1 NC + 1 NO	M	P	A	781-.401-0P	21	21	8	1	0,022																																																																																																																																																																																																																																																																			
				MA	P	A	771-.401-0P	20	21	8	1	0,022																																																																																																																																																																																																																																																																			
						A+C	761-.401-0P	20	21	8	1	0,022																																																																																																																																																																																																																																																																			
			2 NC + 2 NO	M	P	A	782-.401-0P	23	21	8	1	0,023																																																																																																																																																																																																																																																																			
				MA	P	A	772-.401-0P	22	21	8	1	0,023																																																																																																																																																																																																																																																																			
						A+C	762-.401-0P	22	21	8	1	0,023																																																																																																																																																																																																																																																																			
		45 mm	1 NC + 1 NO	M	-	A	781-.401-00	21	22	8		0,022																																																																																																																																																																																																																																																																			
				MA	-	A	771-.401-00	20	22	8		0,022																																																																																																																																																																																																																																																																			
						A+C	761-.401-00	20	22	8		0,022																																																																																																																																																																																																																																																																			
			2 NC + 2 NO	M	-	A	782-.401-00	23	22	8		0,023																																																																																																																																																																																																																																																																			
				MA	-	A	772-.401-00	22	22	8		0,023																																																																																																																																																																																																																																																																			
						A+C	762-.401-00	22	22	8		0,023																																																																																																																																																																																																																																																																			
		52 mm	1 NC + 1 NO	M	P	A	931-.401-0P	25	23	8	1	0,024																																																																																																																																																																																																																																																																			
				MA	P	A	921-.401-0P	24	23	8	1	0,024																																																																																																																																																																																																																																																																			
						A+C	911-.401-0P	24	23	8	1	0,024																																																																																																																																																																																																																																																																			
			2 NC + 2 NO	M	P	A	932-.401-0P	23	23	8	1	0,025																																																																																																																																																																																																																																																																			
				MA	P	A	922-.401-0P	22	23	8	1	0,025																																																																																																																																																																																																																																																																			
						A+C	912-.401-0P	22	23	8	1	0,025																																																																																																																																																																																																																																																																			
			3 NC + 3 NO	M	P	A	933-.401-0P	27	23	8	1	0,026																																																																																																																																																																																																																																																																			
				MA	P	A	923-.401-0P	26	23	8	1	0,026																																																																																																																																																																																																																																																																			
						A+C	913-.401-0P	26	23	8	1	0,026																																																																																																																																																																																																																																																																			
			4 NC + 4 NO	M	P	A	934-.401-0P	29	23	8	1	0,029																																																																																																																																																																																																																																																																			
				MA	P	A	924-.401-0P	28	23	8	1	0,029																																																																																																																																																																																																																																																																			
						A+C	914-.401-0P	28	23	8	1	0,029																																																																																																																																																																																																																																																																			
			5 NC + 5 NO	M	P	A	935-.401-0P	31	23	8	1	0,032																																																																																																																																																																																																																																																																			
				MA	P	A	925-.401-0P	30	23	8	1	0,032																																																																																																																																																																																																																																																																			
						A+C	915-.401-0P	30	23	8	1	0,032																																																																																																																																																																																																																																																																			

Continued on next page



keylock switch
2 positions 45 - 70 mm
 standard lock B2 300,
 other lock numbers on re-
 quest

degree of protec-
 tion

mounting
 depth

contacts

switching action

connection method

key
 removable
 in

part no.

circuit drawing

technical drawing


mounting dimensions

component layout




55 mm	1 NC + 1 NO	M	-	A	931-.401-00	25	24	8	0,024
		MA	-	A	921-.401-00	24	24	8	0,024
				A+C	911-.401-00	24	24	8	0,024
	2 NC + 2 NO	M	-	A	932-.401-00	23	24	8	0,025
		MA	-	A	922-.401-00	22	24	8	0,025
				A+C	912-.401-00	22	24	8	0,025
	3 NC + 3 NO	M	-	A	933-.401-00	27	24	8	0,027
		MA	-	A	923-.401-00	26	24	8	0,027
				A+C	913-.401-00	26	24	8	0,027
	4 NC + 4 NO	M	-	A	934-.401-00	29	24	8	0,030
		MA	-	A	924-.401-00	28	24	8	0,030
				A+C	914-.401-00	28	24	8	0,030
	5 NC + 5 NO	M	-	A	935-.401-00	31	24	8	0,033
		MA	-	A	925-.401-00	30	24	8	0,033
				A+C	915-.401-00	30	24	8	0,033
67 mm	1 NC + 1 NO	M	P	A	831-.401-0P	25	25	8	1 0,026
		MA	P	A	821-.401-0P	24	25	8	1 0,026
				A+C	811-.401-0P	24	25	8	1 0,026
	2 NC + 2 NO	M	P	A	832-.401-0P	23	25	8	1 0,027
		MA	P	A	822-.401-0P	22	25	8	1 0,027
				A+C	812-.401-0P	22	25	8	1 0,027
	3 NC + 3 NO	M	P	A	833-.401-0P	27	25	8	1 0,028
		MA	P	A	823-.401-0P	26	25	8	1 0,028
				A+C	813-.401-0P	26	25	8	1 0,028
	4 NC + 4 NO	M	P	A	834-.401-0P	29	25	8	1 0,031
		MA	P	A	824-.401-0P	28	25	8	1 0,031
				A+C	814-.401-0P	28	25	8	1 0,031
70 mm	1 NC + 1 NO	M	-	A	831-.401-00	25	26	8	0,026
		MA	-	A	821-.401-00	24	26	8	0,026
				A+C	811-.401-00	24	26	8	0,026
	2 NC + 2 NO	M	-	A	832-.401-00	23	26	8	0,027
		MA	-	A	822-.401-00	22	26	8	0,027
				A+C	812-.401-00	22	26	8	0,027
	3 NC + 3 NO	M	-	A	833-.401-00	27	26	8	0,029
		MA	-	A	823-.401-00	26	26	8	0,029
				A+C	813-.401-00	26	26	8	0,029
	4 NC + 4 NO	M	-	A	834-.401-00	29	26	8	0,032
		MA	-	A	824-.401-00	28	26	8	0,032
				A+C	814-.401-00	28	26	8	0,032
	5 NC + 5 NO	M	-	A	835-.401-00	31	26	8	0,035
		MA	-	A	825-.401-00	30	26	8	0,035
				A+C	815-.401-00	30	26	8	0,035

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
keylock switch 2 positions 45 - 70 mm standard lock B2 300, other lock numbers on request	IP 65	42 mm	1 NC + 1 NO	M	P	A	781-.401-WP	21	21	9	1	0,022
				MA	P	A	771-.401-WP	20	21	9	1	0,022
						A+C	761-.401-WP	20	21	9	1	0,022
			2 NC + 2 NO	M	P	A	782-.401-WP	23	21	9	1	0,023
				MA	P	A	772-.401-WP	22	21	9	1	0,023
						A+C	762-.401-WP	22	21	9	1	0,023
		45 mm	1 NC + 1 NO	M	-	A	781-.401-W0	21	22	9		0,022
				MA	-	A	771-.401-W0	20	22	9		0,022
						A+C	761-.401-W0	20	22	9		0,022
			2 NC + 2 NO	M	-	A	782-.401-W0	23	22	9		0,023
				MA	-	A	772-.401-W0	22	22	9		0,023
						A+C	762-.401-W0	22	22	9		0,023
		52 mm	1 NC + 1 NO	M	P	A	931-.401-WP	25	23	9	1	0,024
				MA	P	A	921-.401-WP	24	23	9	1	0,024
						A+C	911-.401-WP	24	23	9	1	0,024
			2 NC + 2 NO	M	P	A	932-.401-WP	23	23	9	1	0,025
				MA	P	A	922-.401-WP	22	23	9	1	0,025
						A+C	912-.401-WP	22	23	9	1	0,025
			3 NC + 3 NO	M	P	A	933-.401-WP	27	23	9	1	0,026
				MA	P	A	923-.401-WP	26	23	9	1	0,026
						A+C	913-.401-WP	26	23	9	1	0,026
			4 NC + 4 NO	M	P	A	934-.401-WP	29	23	9	1	0,029
				MA	P	A	924-.401-WP	28	23	9	1	0,029
						A+C	914-.401-WP	28	23	9	1	0,029
			5 NC + 5 NO	M	P	A	935-.401-WP	31	23	9	1	0,032
				MA	P	A	925-.401-WP	30	23	9	1	0,032
						A+C	915-.401-WP	30	23	9	1	0,032
		55 mm	1 NC + 1 NO	M	-	A	931-.401-W0	25	24	9		0,024
				MA	-	A	921-.401-W0	24	24	9		0,024
						A+C	911-.401-W0	24	24	9		0,024
			2 NC + 2 NO	M	-	A	932-.401-W0	23	24	9		0,025
				MA	-	A	922-.401-W0	22	24	9		0,025
						A+C	912-.401-W0	22	24	9		0,025
			3 NC + 3 NO	M	-	A	933-.401-W0	27	24	9		0,027
				MA	-	A	923-.401-W0	26	24	9		0,027
						A+C	913-.401-W0	26	24	9		0,027
			4 NC + 4 NO	M	-	A	934-.401-W0	29	24	9		0,030
				MA	-	A	924-.401-W0	28	24	9		0,030
						A+C	914-.401-W0	28	24	9		0,030
			5 NC + 5 NO	M	-	A	935-.401-W0	31	24	9		0,033
				MA	-	A	925-.401-W0	30	24	9		0,033
						A+C	915-.401-W0	30	24	9		0,033

Continued on next page



keylock switch
2 positions 45 - 70 mm
 standard lock B2 300,
 other lock numbers on re-
 quest

degree of protec-
 tion

mounting
 depth

contacts

switching action

connection method

key
 removable
 in

part no.

circuit drawing

technical drawing

mounting dimensions

component layout



67 mm	1 NC + 1 NO	M	P	A	831-.401-WP	25	25	9	1	0,026
		MA	P	A	821-.401-WP	24	25	9	1	0,026
				A+C	811-.401-WP	24	25	9	1	0,026
	2 NC + 2 NO	M	P	A	832-.401-WP	23	25	9	1	0,027
		MA	P	A	822-.401-WP	22	25	9	1	0,027
				A+C	812-.401-WP	22	25	9	1	0,027
	3 NC + 3 NO	M	P	A	833-.401-WP	27	25	9	1	0,028
		MA	P	A	823-.401-WP	26	25	9	1	0,028
				A+C	813-.401-WP	26	25	9	1	0,028
	4 NC + 4 NO	M	P	A	834-.401-WP	29	25	9	1	0,031
		MA	P	A	824-.401-WP	28	25	9	1	0,031
				A+C	814-.401-WP	28	25	9	1	0,031
	5 NC + 5 NO	M	P	A	835-.401-WP	31	25	9	1	0,034
		MA	P	A	825-.401-WP	30	25	9	1	0,034
				A+C	815-.401-WP	30	25	9	1	0,034
70 mm	1 NC + 1 NO	M	-	A	831-.401-W0	25	26	9		0,026
		MA	-	A	821-.401-W0	24	26	9		0,026
				A+C	811-.401-W0	24	26	9		0,026
	2 NC + 2 NO	M	-	A	832-.401-W0	23	26	9		0,027
		MA	-	A	822-.401-W0	22	26	9		0,027
				A+C	812-.401-W0	22	26	9		0,027
	3 NC + 3 NO	M	-	A	833-.401-W0	27	26	9		0,029
		MA	-	A	823-.401-W0	26	26	9		0,029
				A+C	813-.401-W0	26	26	9		0,029
	4 NC + 4 NO	M	-	A	834-.401-W0	29	26	9		0,032
		MA	-	A	824-.401-W0	28	26	9		0,032
				A+C	814-.401-W0	28	26	9		0,032
	5 NC + 5 NO	M	-	A	835-.401-W0	31	26	9		0,035
		MA	-	A	825-.401-W0	30	26	9		0,035
				A+C	815-.401-W0	30	26	9		0,035

contacts : normally closed = NC, normally open = NO

switching action : maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

other key removable combination on request

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.


- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

keylock switch 3 positions 45 mm



 front cap for keylock-/selector switch 3 positions page 626



maint. 90° A B C mom. 60° A B r r		degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
keylock switch 3 positions 45 mm standard lock B2 300, other lock numbers on request	IP 40	42 mm	2 NC + 2 NO	0 - MA - MA	P	B+A+C	722-.401-0P	32	21	8	1	0,023	
				M - 0 - M	P	A	732-.401-0P	33	21	8	1	0,023	
				M - 0 - MA	P	A+C	752-.401-0P	35	21	8	1	0,023	
				MA - 0 - M	P	B+A	742-.401-0P	34	21	8	1	0,023	
		45 mm	2 NC + 2 NO	MA - 0 - MA	P	B+A+C	712-.401-0P	32	21	8	1	0,023	
				0 - MA - MA	-	B+A+C	722-.401-00	32	22	8		0,023	
				M - 0 - M	-	A	732-.401-00	33	22	8		0,023	
				M - 0 - MA	-	A+C	752-.401-00	35	22	8		0,023	
	IP 65	42 mm	2 NC + 2 NO	MA - 0 - M	-	B+A	742-.401-00	34	22	8		0,023	
				MA - 0 - MA	-	B+A+C	712-.401-00	32	22	8		0,023	
				0 - MA - MA	P	B+A+C	722-.401-WP	32	21	9	1	0,023	
				M - 0 - M	P	A	732-.401-WP	33	21	9	1	0,023	
		45 mm	2 NC + 2 NO	M - 0 - MA	P	A+C	752-.401-WP	35	21	9	1	0,023	
				MA - 0 - M	P	B+A	742-.401-WP	34	21	9	1	0,023	
				MA - 0 - MA	P	B+A+C	712-.401-WP	32	21	9	1	0,023	
				0 - MA - MA	-	B+A+C	722-.401-W0	32	22	9		0,023	
	IP 65	42 mm	2 NC + 2 NO	M - 0 - M	-	A	732-.401-W0	33	22	9		0,023	
				M - 0 - MA	-	A+C	752-.401-W0	35	22	9		0,023	
				MA - 0 - M	-	B+A	742-.401-W0	34	22	9		0,023	
				MA - 0 - MA	-	B+A+C	712-.401-W0	32	22	9		0,023	

contacts : normally closed = NC, normally open = NO

switching action: maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

other key removable combination on request

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

selector switch 2 positions 45 - 70 mm




front cap for keylock-/selector switch 2 positions page 625

lever page 627


maint. 90° A C mom. 60° A C	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 2 positions 45 - 70 mm	IP 40	42 mm	1 NC + 1 NO	M	P	781-.700-0P	37	27	10	1	0,011
				MA	P	761-.700-0P	36	27	10	1	0,011
			2 NC + 2 NO	M	P	782-.700-0P	39	27	10	1	0,012
				MA	P	762-.700-0P	38	27	10	1	0,012
		45 mm	1 NC + 1 NO	M	-	781-.700-00	37	28	10		0,011
				MA	-	761-.700-00	36	28	10		0,011
			2 NC + 2 NO	M	-	782-.700-00	39	28	10		0,012
				MA	-	762-.700-00	38	28	10		0,012
		52 mm	1 NC + 1 NO	M	P	931-.700-0P	41	29	10	1	0,013
				MA	P	911-.700-0P	40	29	10	1	0,013
			2 NC + 2 NO	M	P	932-.700-0P	39	29	10	1	0,014
				MA	P	912-.700-0P	38	29	10	1	0,014
			3 NC + 3 NO	M	P	933-.700-0P	43	29	10	1	0,015
				MA	P	913-.700-0P	42	29	10	1	0,015
			4 NC + 4 NO	M	P	934-.700-0P	45	29	10	1	0,018
				MA	P	914-.700-0P	44	29	10	1	0,018
			5 NC + 5 NO	M	P	935-.700-0P	47	29	10	1	0,022
				MA	P	915-.700-0P	46	29	10	1	0,022
		55 mm	1 NC + 1 NO	M	-	931-.700-00	41	30	10		0,013
				MA	-	911-.700-00	40	30	10		0,013
			2 NC + 2 NO	M	-	932-.700-00	39	30	10		0,014
				MA	-	912-.700-00	38	30	10		0,014
			3 NC + 3 NO	M	-	933-.700-00	43	30	10		0,015
				MA	-	913-.700-00	42	30	10		0,015
			4 NC + 4 NO	M	-	934-.700-00	45	30	10		0,019
				MA	-	914-.700-00	44	30	10		0,019
			5 NC + 5 NO	M	-	935-.700-00	47	30	10		0,023
				MA	-	915-.700-00	46	30	10		0,023
		67 mm	1 NC + 1 NO	M	P	831-.700-0P	41	31	10	1	0,015
				MA	P	811-.700-0P	40	31	10	1	0,015
			2 NC + 2 NO	M	P	832-.700-0P	39	31	10	1	0,016
				MA	P	812-.700-0P	38	31	10	1	0,016
			3 NC + 3 NO	M	P	833-.700-0P	43	31	10	1	0,017
				MA	P	813-.700-0P	42	31	10	1	0,017
			4 NC + 4 NO	M	P	834-.700-0P	45	31	10	1	0,020
				MA	P	814-.700-0P	44	31	10	1	0,020
			5 NC + 5 NO	M	P	835-.700-0P	47	31	10	1	0,024
				MA	P	815-.700-0P	46	31	10	1	0,024

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 2 positions 45 - 70 mm	IP 40	70 mm	1 NC + 1 NO	M	-	831-.700-00	41	32	10		0,015
				MA	-	811-.700-00	40	32	10		0,015
			2 NC + 2 NO	M	-	832-.700-00	39	32	10		0,016
				MA	-	812-.700-00	38	32	10		0,016
			3 NC + 3 NO	M	-	833-.700-00	43	32	10		0,017
				MA	-	813-.700-00	42	32	10		0,017
			4 NC + 4 NO	M	-	834-.700-00	45	32	10		0,021
				MA	-	814-.700-00	44	32	10		0,021
			5 NC + 5 NO	M	-	835-.700-00	47	32	10		0,025
				MA	-	815-.700-00	46	32	10		0,025
	IP 65	42 mm	1 NC + 1 NO	M	P	781-.700-WP	37	27	11	1	0,011
				MA	P	761-.700-WP	36	27	11	1	0,011
			2 NC + 2 NO	M	P	782-.700-WP	39	27	11	1	0,012
				MA	P	762-.700-WP	38	27	11	1	0,012
		45 mm	1 NC + 1 NO	M	-	781-.700-W0	37	28	11		0,011
				MA	-	761-.700-W0	36	28	11		0,011
			2 NC + 2 NO	M	-	782-.700-W0	39	28	11		0,012
				MA	-	762-.700-W0	38	28	11		0,012
		52 mm	1 NC + 1 NO	M	P	931-.700-WP	41	29	11	1	0,013
				MA	P	911-.700-WP	40	29	11	1	0,013
			2 NC + 2 NO	M	P	932-.700-WP	39	29	11	1	0,014
				MA	P	912-.700-WP	38	29	11	1	0,014
			3 NC + 3 NO	M	P	933-.700-WP	43	29	11	1	0,015
				MA	P	913-.700-WP	42	29	11	1	0,015
			4 NC + 4 NO	M	P	934-.700-WP	45	29	11	1	0,018
				MA	P	914-.700-WP	44	29	11	1	0,018
			5 NC + 5 NO	M	P	935-.700-WP	47	29	11	1	0,022
				MA	P	915-.700-WP	46	29	11	1	0,022
		55 mm	1 NC + 1 NO	M	-	931-.700-W0	41	30	11		0,013
				MA	-	911-.700-W0	40	30	11		0,013
			2 NC + 2 NO	M	-	932-.700-W0	39	30	11		0,014
				MA	-	912-.700-W0	38	30	11		0,014
			3 NC + 3 NO	M	-	933-.700-W0	43	30	11		0,015
				MA	-	913-.700-W0	42	30	11		0,015
			4 NC + 4 NO	M	-	934-.700-W0	45	30	11		0,019
				MA	-	914-.700-W0	44	30	11		0,019
			5 NC + 5 NO	M	-	935-.700-W0	47	30	11		0,023
				MA	-	915-.700-W0	46	30	11		0,023
		67 mm	1 NC + 1 NO	M	P	831-.700-WP	41	31	11	1	0,015
				MA	P	811-.700-WP	40	31	11	1	0,015
			2 NC + 2 NO	M	P	832-.700-WP	39	31	11	1	0,016
				MA	P	812-.700-WP	38	31	11	1	0,016
			3 NC + 3 NO	M	P	833-.700-WP	43	31	11	1	0,017
				MA	P	813-.700-WP	42	31	11	1	0,017
			4 NC + 4 NO	M	P	834-.700-WP	45	31	11	1	0,020
				MA	P	814-.700-WP	44	31	11	1	0,020
			5 NC + 5 NO	M	P	835-.700-WP	47	31	11	1	0,024
				MA	P	815-.700-WP	46	31	11	1	0,024

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 2 positions 45 - 70 mm	IP 65	70 mm	1 NC + 1 NO	M	-	831-.700-W0	41	32	11		0,015
				MA	-	811-.700-W0	40	32	11		0,015
			2 NC + 2 NO	M	-	832-.700-W0	39	32	11		0,016
				MA	-	812-.700-W0	38	32	11		0,016
			3 NC + 3 NO	M	-	833-.700-W0	43	32	11		0,017
				MA	-	813-.700-W0	42	32	11		0,017
			4 NC + 4 NO	M	-	834-.700-W0	45	32	11		0,021
				MA	-	814-.700-W0	44	32	11		0,021
			5 NC + 5 NO	M	-	835-.700-W0	47	32	11		0,025
				MA	-	815-.700-W0	46	32	11		0,025

contacts : normally closed = NC, normally open = NO

switching action : maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.



circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

selector switch 3 positions 45 mm



front cap for keylock-/selector switch 3 positions page 626

lever page 627

maint. 90°  mom. 60° 		degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 3 positions 45 mm	IP 40	42 mm	2 NC + 2 NO	0 - MA - MA	P	722-.700-0P	48	27	10	1	0,012	
				M - 0 - M	P	732-.700-0P	49	27	10	1	0,012	
				M - 0 - MA	P	752-.700-0P	51	27	10	1	0,012	
				MA - 0 - M	P	742-.700-0P	50	27	10	1	0,012	
				MA - 0 - MA	P	712-.700-0P	48	27	10	1	0,012	
		45 mm	2 NC + 2 NO	0 - MA - MA	-	722-.700-00	48	28	10		0,012	
				M - 0 - M	-	732-.700-00	49	28	10		0,012	
				M - 0 - MA	-	752-.700-00	51	28	10		0,012	
				MA - 0 - M	-	742-.700-00	50	28	10		0,012	
				MA - 0 - MA	-	712-.700-00	48	28	10		0,012	
	IP 65	42 mm	2 NC + 2 NO	0 - MA - MA	P	722-.700-WP	48	27	11	1	0,012	
				M - 0 - M	P	732-.700-WP	49	27	11	1	0,012	
				M - 0 - MA	P	752-.700-WP	51	27	11	1	0,012	
				MA - 0 - M	P	742-.700-WP	50	27	11	1	0,012	
				MA - 0 - MA	P	712-.700-WP	48	27	11	1	0,012	
		45 mm	2 NC + 2 NO	0 - MA - MA	-	722-.700-W0	48	28	11		0,012	
				M - 0 - M	-	732-.700-W0	49	28	11		0,012	
				M - 0 - MA	-	752-.700-W0	51	28	11		0,012	
				MA - 0 - M	-	742-.700-W0	50	28	11		0,012	
				MA - 0 - MA	-	712-.700-W0	48	28	11		0,012	

contacts : normally closed = NC, normally open = NO

switching action: maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

buzzer 30 - 55 mm



buzzer element page 627

front bezel for buzzer 30 - 55 mm page 628

	degree of protection	mounting depth	connection method	buzzer socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
buzzer 30 - 55 mm	IP 40	30 mm	-	MG T 1 3/4	970-.000-K0	52	2	12		0,004
		52 mm	P	MG T 1 3/4	970-.000-0P	52	4	12	1	0,007
		55 mm	-	MG T 1 3/4	970-.000-00	52	5	12		0,007

connection method : soldering-/plug-in terminal = -, PCB terminal = P

the buzzer 55 mm is as long as the corresponding illuminated pushbutton and fits to the PCB plug-in base and multi plug housing

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

push-pull illuminated switch 45 mm



push-pull knob page 627

filament lamp MG T 1 3/4 page 634

LED MG T 1 3/4 page 634

	mounting depth	contacts	switching action	connection method	colour of front bezel	18 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	component layout	
push-pull illuminated switch 45 mm IP 40, lampholder MG T 1 3/4	42 mm	2 NC + 2 NO	M - 0 - M	P	grey	792-1000-0P	53	33	13	1	0,015
				P	black	792-2000-0P	53	33	13	1	0,015
	45 mm	2 NC + 2 NO	M - 0 - M	-	grey	792-1000-00	53	34	13		0,015
				-	black	792-2000-00	53	34	13		0,015

contacts : normally closed = NC, normally open = NO

switching action: maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

indicator actuator 41-44 mm for flush mounting



- 🛒 lens for 35 mm page 622
- 🛒 front bezel-set for flush mounting page 628
- 🛒 filament lamp MG T 1 3/4 page 634
- 🛒 LED MG T 1 3/4 page 634
- 🛒 lamp element block for 35 mm page 632

	degree of protection	a 24 x 30 mm part no.	b 24 x 24 mm part no.	25 mm dia. part no.	circuit drawing	technical drawing	mounting dimension	components layout	
indicator actuator 41-44 mm for flush mounting lamp socket MG T 1 3/4	IP 40	690-6000-00	690-4000-00	690-2000-00	1	35	14	-	0,004
	IP 65	690-6000-W0	690-4000-W0	690-2000-W0	1	35	14	-	0,005

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652

indicator for flush mounting 39 - 79 mm

protection degree IP 40



- lens page 623
- front bezel for indicator 39 - 79 mm page 627
- front bezel-set for flush mounting page 628
- filament lamp MG T 1 3/4 page 634
- LED MG T 1 3/4 page 634
- filament lamp T 5.5 page 634
- LED T 5.5 page 635

	mounting depth	connection method	lamp socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
indicator for flush mounting 39 - 79 mm	39 mm	-	MG T 1 3/4	990-.000-K0	1	36	14		0,004
	54 mm	-	T 5.5	890-.000-K0	1	37	14		0,006
	61 mm	P	MG T 1 3/4	990-.000-0P	1	38	14	1	0,007
	64 mm	-	MG T 1 3/4	990-.000-00	1	39	14		0,007
	76 mm	P	T 5.5	890-.000-0P	1	40	14	1	0,010
	79 mm	-	T 5.5	890-.000-00	1	41	14		0,010

connection method : soldering-/plug-in terminal = -, PCB terminal = P

The indicators 55 mm and 70 mm are as long as the corresponding illuminated pushbuttons and fit to the PCB plug-in base and multi-plug housing.
circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

illuminated-/pushbutton actuator 41-44 mm for flush mounting



- 🛒 lens page 623
- 🛒 filament lamp MG T 1 3/4 page 634
- 🛒 LED MG T 1 3/4 page 634
- 🛒 snap-action switching element block for 35 mm page 631

	degree of protection	switching action	component layout 24 x 30 mm Typ-Nr.	24 x 24 mm Typ-Nr.	25 mm dia. Typ-Nr.	circuit drawing	technical drawing	mounting dimensions	
illuminated-/pushbutton actuator 41-44 mm for flush mounting	IP 40	M			680-2000-00	54	35	14	0,004
				680-4000-00		54	35	14	0,004
			680-6000-00			54	35	14	0,004
		MA (M)			600-2000-00	55	35	14	0,004
				600-4000-00		55	35	14	0,004
			600-6000-00			55	35	14	0,004
	IP 65	M			680-2000-W0	54	35	14	0,005
				680-4000-W0		54	35	14	0,005
			680-6000-W0			54	35	14	0,005
		MA (M)			600-2000-W0	55	35	14	0,005
				600-4000-W0		55	35	14	0,005
			600-6000-W0			55	35	14	0,005

switching action : momentary action = M, maintained action = MA
circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652

pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm

protection degree IP 40



lens page 623

front bezel for illuminated-/pushbutton 61 - 79 mm page 627

front bezel-set for flush mounting page 628

filament lamp MG T 1 3/4 page 634

LED MG T 1 3/4 page 634

filament lamp T 5.5 page 634

LED T 5.5 page 635

	mounting depth	contacts	switching action	connection method	lamp socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm	61 mm	1 NC + 1 NO	maintained	P	MG T 1 3/4	901-.000-0P	4	42	14	1	0,013
		2 NC + 2 NO	maintained	P	MG T 1 3/4	902-.000-0P	5	42	14	1	0,014
		3 NC + 3 NO	maintained	P	MG T 1 3/4	903-.000-0P	6	42	14	1	0,014
		4 NC + 4 NO	maintained	P	MG T 1 3/4	904-.000-0P	7	42	14	1	0,018
		5 NC + 5 NO	maintained	P	MG T 1 3/4	905-.000-0P	8	42	14	1	0,021
	64 mm	1 NC + 1 NO	maintained	-	MG T 1 3/4	901-.000-00	4	43	14		0,013
		2 NC + 2 NO	maintained	-	MG T 1 3/4	902-.000-00	5	43	14		0,014
		3 NC + 3 NO	maintained	-	MG T 1 3/4	903-.000-00	6	43	14		0,015
		4 NC + 4 NO	maintained	-	MG T 1 3/4	904-.000-00	7	43	14		0,019
		5 NC + 5 NO	maintained	-	MG T 1 3/4	905-.000-00	8	43	14		0,022
	76 mm	1 NC + 1 NO	maintained	P	T 5.5	801-.000-0P	4	44	14	1	0,015
		2 NC + 2 NO	maintained	P	T 5.5	802-.000-0P	5	44	14	1	0,016
		3 NC + 3 NO	maintained	P	T 5.5	803-.000-0P	6	44	14	1	0,014
		4 NC + 4 NO	maintained	P	T 5.5	804-.000-0P	7	44	14	1	0,020
		5 NC + 5 NO	maintained	P	T 5.5	805-.000-0P	8	44	14	1	0,023
	79 mm	1 NC + 1 NO	maintained	-	T 5.5	801-.000-00	4	45	14		0,015
		2 NC + 2 NO	maintained	-	T 5.5	802-.000-00	5	45	14		0,016
		3 NC + 3 NO	maintained	-	T 5.5	803-.000-00	6	45	14		0,017
		4 NC + 4 NO	maintained	-	T 5.5	804-.000-00	7	45	14		0,021
		5 NC + 5 NO	maintained	-	T 5.5	805-.000-00	8	45	14		0,024


contacts : normally closed = NC, normally open = NO

switching action: (changeable to momentary, reversible)

connection method : PCB terminal = P, soldering-/plug-in terminal = -

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

keylock switch 2 positions for flush mounting 51 - 79 mm




front cap for keylock-/selector switch 2 positions page 625

front bezel-set for flush mounting page 628


maint. 90° A C mom. 60° A ↻	degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	kg
keylock switch 2 positions for flush mounting 51 - 79 mm	IP 40	51 mm	1 NC + 1 NO	M	P	A	781-.401-0P	21	46	14	1	0,022
				MA	P	A	771-.401-0P	20	46	14	1	0,022
						A+C	761-.401-0P	20	46	14	1	0,022
			2 NC + 2 NO	M	P	A	782-.401-0P	23	46	14	1	0,023
				MA	P	A	772-.401-0P	22	46	14	1	0,023
						A+C	762-.401-0P	22	46	14	1	0,023
		54 mm	1 NC + 1 NO	M	-	A	781-.401-00	21	47	14		0,022
				MA	-	A	771-.401-00	20	47	14		0,022
						A+C	761-.401-00	20	47	14		0,022
			2 NC + 2 NO	M	-	A	782-.401-00	23	47	14		0,023
				MA	-	A	772-.401-00	22	47	14		0,023
						A+C	762-.401-00	22	47	14		0,023
		61 mm	1 NC + 1 NO	M	P	A	931-.401-0P	25	48	14	1	0,024
				MA	P	A	921-.401-0P	24	48	14	1	0,024
						A+C	911-.401-0P	24	48	14	1	0,024
			2 NC + 2 NO	M	P	A	932-.401-0P	23	48	14	1	0,025
				MA	P	A	922-.401-0P	22	48	14	1	0,025
						A+C	912-.401-0P	22	48	14	1	0,025
			3 NC + 3 NO	M	P	A	933-.401-0P	27	48	14	1	0,026
				MA	P	A	923-.401-0P	26	48	14	1	0,026
						A+C	913-.401-0P	26	48	14	1	0,026
			4 NC + 4 NO	M	P	A	934-.401-0P	29	48	14	1	0,029
				MA	P	A	924-.401-0P	28	48	14	1	0,029
						A+C	914-.401-0P	28	48	14	1	0,029
			5 NC + 5 NO	M	P	A	935-.401-0P	31	48	14	1	0,032
				MA	P	A	925-.401-0P	30	48	14	1	0,032
						A+C	915-.401-0P	30	48	14	1	0,032

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	key removable in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
keylock switch 2 positions for flush mounting 51 - 79 mm	IP 40	64 mm	1 NC + 1 NO	M	-	A	931-.401-00	25	49	14		0,024
				MA	-	A	921-.401-00	24	49	14		0,024
						A+C	911-.401-00	24	49	14		0,024
			2 NC + 2 NO	M	-	A	932-.401-00	23	49	14		0,025
				MA	-	A	922-.401-00	22	49	14		0,025
						A+C	912-.401-00	22	49	14		0,025
			3 NC + 3 NO	M	-	A	933-.401-00	27	49	14		0,027
				MA	-	A	923-.401-00	26	49	14		0,027
						A+C	913-.401-00	26	49	14		0,027
			4 NC + 4 NO	M	-	A	934-.401-00	29	49	14		0,030
				MA	-	A	924-.401-00	28	49	14		0,030
						A+C	914-.401-00	28	49	14		0,030
			5 NC + 5 NO	M	-	A	935-.401-00	31	49	14		0,033
				MA	-	A	925-.401-00	30	49	14		0,033
						A+C	915-.401-00	30	49	14		0,033
		76 mm	1 NC + 1 NO	M	P	A	831-.401-0P	25	50	14	1	0,026
				MA	P	A	821-.401-0P	24	50	14	1	0,026
						A+C	811-.401-0P	24	50	14	1	0,026
			2 NC + 2 NO	M	P	A	832-.401-0P	23	50	14	1	0,027
				MA	P	A	822-.401-0P	22	50	14	1	0,027
						A+C	812-.401-0P	22	50	14	1	0,027
			3 NC + 3 NO	M	P	A	833-.401-0P	27	50	14	1	0,028
				MA	P	A	823-.401-0P	26	50	14	1	0,028
						A+C	813-.401-0P	26	50	14	1	0,028
			4 NC + 4 NO	M	P	A	834-.401-0P	29	50	14	1	0,031
				MA	P	A	824-.401-0P	28	50	14	1	0,031
						A+C	814-.401-0P	28	50	14	1	0,031
			5 NC + 5 NO	M	P	A	835-.401-0P	31	50	14	1	0,034
				MA	P	A	825-.401-0P	30	50	14	1	0,034
						A+C	815-.401-0P	30	50	14	1	0,034
		79 mm	1 NC + 1 NO	M	-	A	831-.401-00	25	51	14		0,026
				MA	-	A	821-.401-00	24	51	14		0,026
						A+C	811-.401-00	24	51	14		0,026
			2 NC + 2 NO	M	-	A	832-.401-00	23	51	14		0,027
				MA	-	A	822-.401-00	22	51	14		0,027
						A+C	812-.401-00	22	51	14		0,027
			3 NC + 3 NO	M	-	A	833-.401-00	27	51	14		0,029
				MA	-	A	823-.401-00	26	51	14		0,029
						A+C	813-.401-00	26	51	14		0,029
			4 NC + 4 NO	M	-	A	834-.401-00	29	51	14		0,032
				MA	-	A	824-.401-00	28	51	14		0,032
						A+C	814-.401-00	28	51	14		0,032
			5 NC + 5 NO	M	-	A	835-.401-00	31	51	14		0,035
				MA	-	A	825-.401-00	30	51	14		0,035
						A+C	815-.401-00	30	51	14		0,035
	IP 65	51 mm	1 NC + 1 NO	M	P	A	781-.401-WP	21	46	14	1	0,022
				MA	P	A	771-.401-WP	20	46	14	1	0,022
						A+C	761-.401-WP	20	46	14	1	0,022
			2 NC + 2 NO	M	P	A	782-.401-WP	23	46	14	1	0,023
				MA	P	A	772-.401-WP	22	46	14	1	0,023
						A+C	762-.401-WP	22	46	14	1	0,023

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	key remova-ble in	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
keylock switch 2 positions for flush mounting 51 - 79 mm	IP 65	54 mm	1 NC + 1 NO	M	-	A	781-.401-W0	21	47	14		0,022
				MA	-	A	771-.401-W0	20	47	14		0,022
						A+C	761-.401-W0	20	47	14		0,022
			2 NC + 2 NO	M	-	A	782-.401-W0	23	47	14		0,023
				MA	-	A	772-.401-W0	22	47	14		0,023
						A+C	762-.401-W0	22	47	14		0,023
		61 mm	1 NC + 1 NO	M	P	A	931-.401-WP	25	48	14	1	0,024
				MA	P	A	921-.401-WP	24	48	14	1	0,024
						A+C	911-.401-WP	24	48	14	1	0,024
			2 NC + 2 NO	M	P	A	932-.401-WP	23	48	14	1	0,025
				MA	P	A	922-.401-WP	22	48	14	1	0,025
						A+C	912-.401-WP	22	48	14	1	0,025
			3 NC + 3 NO	M	P	A	933-.401-WP	27	48	14	1	0,026
				MA	P	A	923-.401-WP	26	48	14	1	0,026
						A+C	913-.401-WP	26	48	14	1	0,026
			4 NC + 4 NO	M	P	A	934-.401-WP	29	48	14	1	0,029
				MA	P	A	924-.401-WP	28	48	14	1	0,029
						A+C	914-.401-WP	28	48	14	1	0,029
		64 mm	1 NC + 1 NO	M	P	A	935-.401-WP	31	48	14	1	0,032
				MA	P	A	925-.401-WP	30	48	14	1	0,032
						A+C	915-.401-WP	30	48	14	1	0,032
			2 NC + 2 NO	M	-	A	931-.401-W0	25	49	14		0,024
				MA	-	A	921-.401-W0	24	49	14		0,024
						A+C	911-.401-W0	24	49	14		0,024
			3 NC + 3 NO	M	-	A	932-.401-W0	23	49	14		0,025
				MA	-	A	922-.401-W0	22	49	14		0,025
						A+C	912-.401-W0	22	49	14		0,025
			4 NC + 4 NO	M	-	A	933-.401-W0	27	49	14		0,027
				MA	-	A	923-.401-W0	26	49	14		0,027
						A+C	913-.401-W0	26	49	14		0,027
		76 mm	1 NC + 1 NO	M	-	A	934-.401-W0	29	49	14		0,030
				MA	-	A	924-.401-W0	28	49	14		0,030
						A+C	914-.401-W0	28	49	14		0,030
			2 NC + 2 NO	M	-	A	935-.401-W0	31	49	14		0,033
				MA	-	A	925-.401-W0	30	49	14		0,033
						A+C	915-.401-W0	30	49	14		0,033
			3 NC + 3 NO	M	P	A	831-.401-WP	25	50	14	1	0,026
				MA	P	A	821-.401-WP	24	50	14	1	0,026
						A+C	811-.401-WP	24	50	14	1	0,026
			4 NC + 4 NO	M	P	A	832-.401-WP	23	50	14	1	0,027
				MA	P	A	822-.401-WP	22	50	14	1	0,027
						A+C	812-.401-WP	22	50	14	1	0,027
		76 mm	1 NC + 1 NO	M	P	A	833-.401-WP	27	50	14	1	0,028
				MA	P	A	823-.401-WP	26	50	14	1	0,028
						A+C	813-.401-WP	26	50	14	1	0,028
			2 NC + 2 NO	M	P	A	834-.401-WP	29	50	14	1	0,031
				MA	P	A	824-.401-WP	28	50	14	1	0,031
						A+C	814-.401-WP	28	50	14	1	0,031
			3 NC + 3 NO	M	P	A	835-.401-WP	31	50	14	1	0,034
				MA	P	A	825-.401-WP	30	50	14	1	0,034
						A+C	815-.401-WP	30	50	14	1	0,034

Continued on next page

keylock switch with 3 positions for flush mounting 51 - 54 mm



front cap for keylock-/selector switch 3 positions 626

front bezel-set for flush mounting page 628

maint. 90° A B C mom. 60° A B C degree of protection mounting depth contacts switching action connection method key remo- vable in part no. circuit drawing technical drawing mounting dimensions component layout												
keylock switch with 3 positions for flush moun- ting 51 - 54 mm	IP 40	51 mm	2 NC + 2 NO	0 - MA - MA	P	B+A+C	722-.401-0P	32	46	14	1	0,023
				M - 0 - M	P	A	732-.401-0P	33	46	14	1	0,023
				M - 0 - MA	P	A+C	752-.401-0P	35	46	14	1	0,023
				MA - 0 - M	P	B+A	742-.401-0P	34	46	14	1	0,023
				MA - 0 - MA	P	B+A+C	712-.401-0P	32	46	14	1	0,023
		54 mm	2 NC + 2 NO	0 - MA - MA	-	B+A+C	722-.401-00	32	47	14		0,023
				M - 0 - M	-	A	732-.401-00	33	47	14		0,023
				M - 0 - MA	-	A+C	752-.401-00	35	47	14		0,023
				MA - 0 - M	-	B+A	742-.401-00	34	47	14		0,023
				MA - 0 - MA	-	B+A+C	712-.401-00	32	47	14		0,023
	IP 65	51 mm	2 NC + 2 NO	0 - MA - MA	P	B+A+C	722-.401-WP	32	46	14	1	0,023
				M - 0 - M	P	A	732-.401-WP	33	46	14	1	0,023
				M - 0 - MA	P	A+C	752-.401-WP	35	46	14	1	0,023
				MA - 0 - M	P	B+A	742-.401-WP	34	46	14	1	0,023
				MA - 0 - MA	P	B+A+C	712-.401-WP	32	46	14	1	0,023
		54 mm	2 NC + 2 NO	0 - MA - MA	-	B+A+C	722-.401-W0	32	47	14		0,023
				M - 0 - M	-	A	732-.401-W0	33	47	14		0,023
				M - 0 - MA	-	A+C	752-.401-W0	35	47	14		0,023
				MA - 0 - M	-	B+A	742-.401-W0	34	47	14		0,023
				MA - 0 - MA	-	B+A+C	712-.401-W0	32	47	14		0,023

contacts : normally closed = NC, normally open = NO

switching action : maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

other key removable combination on request


hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

selector switch 2 positions for flush mounting 51 - 79 mm




front cap for keylock-/selector switch 2 positions page 625

lever page 627

front bezel-set for flush mounting page 628

maint. 90° A C mom. 60° A C	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 2 positions for flush mounting 51 - 79 mm	IP 40	51 mm	1 NC + 1 NO	M	P	781-.700-0P	37	52	15	1	0,011
				MA	P	761-.700-0P	36	52	15	1	0,011
			2 NC + 2 NO	M	P	782-.700-0P	39	52	15	1	0,012
				MA	P	762-.700-0P	38	52	15	1	0,012
		54 mm	1 NC + 1 NO	M	-	781-.700-00	37	53	15		0,011
				MA	-	761-.700-00	36	53	15		0,011
			2 NC + 2 NO	M	-	782-.700-00	39	53	15		0,012
				MA	-	762-.700-00	38	53	15		0,012
		61 mm	1 NC + 1 NO	M	P	931-.700-0P	41	54	15	1	0,013
				MA	P	911-.700-0P	40	54	15	1	0,013
			2 NC + 2 NO	M	P	932-.700-0P	39	54	15	1	0,014
				MA	P	912-.700-0P	38	54	15	1	0,014
			3 NC + 3 NO	M	P	933-.700-0P	43	54	15	1	0,015
				MA	P	913-.700-0P	42	54	15	1	0,015
			4 NC + 4 NO	M	P	934-.700-0P	45	54	15	1	0,018
				MA	P	914-.700-0P	44	54	15	1	0,018
			5 NC + 5 NO	M	P	935-.700-0P	47	54	15	1	0,022
				MA	P	915-.700-0P	46	54	15	1	0,022
		64 mm	1 NC + 1 NO	M	-	931-.700-00	41	55	15		0,013
				MA	-	911-.700-00	40	55	15		0,013
			2 NC + 2 NO	M	-	932-.700-00	39	55	15		0,014
				MA	-	912-.700-00	38	55	15		0,014
			3 NC + 3 NO	M	-	933-.700-00	43	55	15		0,015
				MA	-	913-.700-00	42	55	15		0,015
			4 NC + 4 NO	M	-	934-.700-00	45	55	15		0,019
				MA	-	914-.700-00	44	55	15		0,019
			5 NC + 5 NO	M	-	935-.700-00	47	55	15		0,023
				MA	-	915-.700-00	46	55	15		0,023


Continued on next page



selector switch 2 positions
for flush mounting 51 - 79 mm

degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
IP 65	76 mm	1 NC + 1 NO	M	P	831-.700-0P	41	56	15	1	0,015
			MA	P	811-.700-0P	40	56	15	1	0,015
		2 NC + 2 NO	M	P	832-.700-0P	39	56	15	1	0,016
			MA	P	812-.700-0P	38	56	15	1	0,016
		3 NC + 3 NO	M	P	833-.700-0P	43	56	15	1	0,017
			MA	P	813-.700-0P	42	56	15	1	0,017
		4 NC + 4 NO	M	P	834-.700-0P	45	56	15	1	0,020
			MA	P	814-.700-0P	44	56	15	1	0,020
		5 NC + 5 NO	M	P	835-.700-0P	47	56	15	1	0,024
			MA	P	815-.700-0P	46	56	15	1	0,024
	79 mm	1 NC + 1 NO	M	-	831-.700-00	41	57	15		0,015
			MA	-	811-.700-00	40	57	15		0,015
		2 NC + 2 NO	M	-	832-.700-00	39	57	15		0,016
			MA	-	812-.700-00	38	57	15		0,016
		3 NC + 3 NO	M	-	833-.700-00	43	57	15		0,017
			MA	-	813-.700-00	42	57	15		0,017
		4 NC + 4 NO	M	-	834-.700-00	45	57	15		0,021
			MA	-	814-.700-00	44	57	15		0,021
		5 NC + 5 NO	M	-	835-.700-00	47	57	15		0,025
			MA	-	815-.700-00	46	57	15		0,025
	51 mm	1 NC + 1 NO	M	P	781-.700-WP	37	52	15	1	0,011
			MA	P	761-.700-WP	36	52	15	1	0,011
		2 NC + 2 NO	M	P	782-.700-WP	39	52	15	1	0,012
			MA	P	762-.700-WP	38	52	15	1	0,012
	54 mm	1 NC + 1 NO	M	-	781-.700-W0	37	53	15		0,011
			MA	-	761-.700-W0	36	53	15		0,011
		2 NC + 2 NO	M	-	782-.700-W0	39	53	15		0,012
			MA	-	762-.700-W0	38	53	15		0,012
	61 mm	1 NC + 1 NO	M	P	931-.700-WP	41	54	15	1	0,013
			MA	P	911-.700-WP	40	54	15	1	0,013
		2 NC + 2 NO	M	P	932-.700-WP	39	54	15	1	0,014
			MA	P	912-.700-WP	38	54	15	1	0,014
		3 NC + 3 NO	M	P	933-.700-WP	43	54	15	1	0,015
			MA	P	913-.700-WP	42	54	15	1	0,015
		4 NC + 4 NO	M	P	934-.700-WP	45	54	15	1	0,018
			MA	P	914-.700-WP	44	54	15	1	0,018
		5 NC + 5 NO	M	P	935-.700-WP	47	54	15	1	0,022
			MA	P	915-.700-WP	46	54	15	1	0,022
	64 mm	1 NC + 1 NO	M	-	931-.700-W0	41	55	15		0,013
			MA	-	911-.700-W0	40	55	15		0,013
		2 NC + 2 NO	M	-	932-.700-W0	39	55	15		0,014
			MA	-	912-.700-W0	38	55	15		0,014
		3 NC + 3 NO	M	-	933-.700-W0	43	55	15		0,015
			MA	-	913-.700-W0	42	55	15		0,015
		4 NC + 4 NO	M	-	934-.700-W0	45	55	15		0,019
			MA	-	914-.700-W0	44	55	15		0,019
		5 NC + 5 NO	M	-	935-.700-W0	47	55	15		0,023
			MA	-	915-.700-W0	46	55	15		0,023

Continued on next page



	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 2 positions for flush mounting 51 - 79 mm	IP 65	76 mm	1 NC + 1 NO	M	P	831-.700-WP	41	56	15	1	0,015
				MA	P	811-.700-WP	40	56	15	1	0,015
			2 NC + 2 NO	M	P	832-.700-WP	39	56	15	1	0,016
				MA	P	812-.700-WP	38	56	15	1	0,016
			3 NC + 3 NO	M	P	833-.700-WP	43	56	15	1	0,017
				MA	P	813-.700-WP	42	56	15	1	0,017
			4 NC + 4 NO	M	P	834-.700-WP	45	56	15	1	0,020
				MA	P	814-.700-WP	44	56	15	1	0,020
			5 NC + 5 NO	M	P	835-.700-WP	47	56	15	1	0,024
				MA	P	815-.700-WP	46	56	15	1	0,024
		79 mm	1 NC + 1 NO	M	-	831-.700-W0	41	57	15		0,015
				MA	-	811-.700-W0	40	57	15		0,015
			2 NC + 2 NO	M	-	832-.700-W0	39	57	15		0,016
				MA	-	812-.700-W0	38	57	15		0,016
			3 NC + 3 NO	M	-	833-.700-W0	43	57	15		0,017
				MA	-	813-.700-W0	42	57	15		0,017
			4 NC + 4 NO	M	-	834-.700-W0	45	57	15		0,021
				MA	-	814-.700-W0	44	57	15		0,021
			5 NC + 5 NO	M	-	835-.700-W0	47	57	15		0,025
				MA	-	815-.700-W0	46	57	15		0,025

contacts : normally closed = NC, normally open = NO

switching action : maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657


selector switch 3 positions for flush mounting 51 - 54 mm





 front cap for keylock-/selector switch 3 positions page 626

 lever page 627

 front bezel-set for flush mounting page 628



maint. 90°  mom. 60°  <th>degree of protection</th> <th>mounting depth</th> <th>contacts</th> <th>switching action</th> <th>connection method</th> <th>part no.</th> <th>circuit drawing</th> <th>technical drawing</th> <th>mounting dimensions</th> <th>component layout</th> <th></th>	degree of protection	mounting depth	contacts	switching action	connection method	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
selector switch 3 positions for flush mounting 51 - 54 mm	IP 40	51 mm	2 NC + 2 NO	0 - MA - MA	P	722-.700-0P	48	52	15	1	0,012
				M - 0 - M	P	732-.700-0P	49	52	15	1	0,012
				M - 0 - MA	P	752-.700-0P	51	52	15	1	0,012
				MA - 0 - M	P	742-.700-0P	50	52	15	1	0,012
				MA - 0 - MA	P	712-.700-0P	48	52	15	1	0,012
		54 mm	2 NC + 2 NO	0 - MA - MA	-	722-.700-00	48	53	15		0,012
				M - 0 - M	-	732-.700-00	49	53	15		0,012
				M - 0 - MA	-	752-.700-00	51	53	15		0,012
				MA - 0 - M	-	742-.700-00	50	53	15		0,012
				MA - 0 - MA	-	712-.700-00	48	53	15		0,012
	IP 65	51 mm	2 NC + 2 NO	0 - MA - MA	P	722-.700-WP	48	52	15	1	0,012
				M - 0 - M	P	732-.700-WP	49	52	15	1	0,012
				M - 0 - MA	P	752-.700-WP	51	52	15	1	0,012
				MA - 0 - M	P	742-.700-WP	50	52	15	1	0,012
				MA - 0 - MA	P	712-.700-WP	48	52	15	1	0,012
		54 mm	2 NC + 2 NO	0 - MA - MA	-	722-.700-W0	48	53	15		0,012
				M - 0 - M	-	732-.700-W0	49	53	15		0,012
				M - 0 - MA	-	752-.700-W0	51	53	15		0,012
				MA - 0 - M	-	742-.700-W0	50	53	15		0,012
				MA - 0 - MA	-	712-.700-W0	48	53	15		0,012

contacts : normally closed = NC, normally open = NO

switching action: maintained action = MA, momentary action = M

connection method : PCB terminal = P, soldering-/plug-in terminal = -

hint:

- we recommend to use location strip no. 260-0020-00 for anti-twisting of the front bezel.

- at momentary position the overturning force is max. 60 Ncm.

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

buzzer for flush mounting 39 - 64 mm



🛒 buzzer element page 627

🛒 front bezel for buzzer 30 - 55 mm page 628

🛒 front bezel set for flush mounting for buzzer page 628

	degree of protection	mounting depth	connection method	buzzer socket	part no.	circuit drawing	technical drawing	mounting dimensions	component layout	
buzzer for flush mounting 39 - 64 mm	IP 40	39 mm	-	MG T 1 3/4	970-.000-K0	52	36	16		0,004
		61 mm	P	MG T 1 3/4	970-.000-0P	52	38	16	1	0,007
		64 mm	-	MG T 1 3/4	970-.000-00	52	39	16		0,007

connection method : soldering-/plug-in terminal = -, PCB terminal = P

the buzzer 55 mm is as long as the corresponding illuminated pushbutton and fits to the PCB plug-in base and multi plug housing

circuit drawings from page 657, technical drawings from page 642, mounting dimensions from page 652, component layouts from page 657

at front

lens for 35 mm

for pushbuttons 35 mm

	shape	lens/support	colour	18 x 24 mm Typ-Nr.	18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	
lens for 35 mm of plastic	flat	transparent/translucent	blue	600-5150-00	600-3150-00	600-1150-00	0,001
			yellow	600-5170-00	600-3170-00	600-1170-00	0,001
			green	600-5140-00	600-3140-00	600-1140-00	0,001
			orange	600-5110-00	600-3110-00	600-1110-00	0,001
			red	600-5120-00	600-3120-00	600-1120-00	0,001
			white	600-5160-00	600-3160-00	600-1160-00	0,001
of plastic (not recommended for film insert)	flat	transparent/transparent	blue	600-5250-00	600-3250-00	600-1250-00	0,001
			yellow	600-5270-00	600-3270-00	600-1270-00	0,001
			green	600-5240-00	600-3240-00	600-1240-00	0,001
			orange	600-5210-00	600-3210-00	600-1210-00	0,001
			red	600-5220-00	600-3220-00	600-1220-00	0,001
			white	600-5260-00	600-3260-00	600-1260-00	0,001
of plastic (not for film insert and illumination)	flat	opaque/translucent	grey	600-5180-00	600-3180-00	600-1180-00	0,001
			black	600-5190-00	600-3190-00	600-1190-00	0,001



lens

	degree of protection	front dimension pushbutton	shape	lens/support	colour	part no.	
lens of plastic	IP 40	18 x 18 mm	flat	transparent/translucent	blue	200-3150-00	0,001
					yellow	200-3170-00	0,001
					green	200-3140-00	0,001
					orange	200-3110-00	0,001
					red	200-3120-00	0,001
					white	200-3160-00	0,001
		18 x 24 mm	flat	transparent/translucent	blue	200-5150-00	0,001
					yellow	200-5170-00	0,001
					green	200-5140-00	0,001
					orange	200-5110-00	0,001
					red	200-5120-00	0,001
					white	200-5160-00	0,001
		24 x 24 mm	flat	transparent/translucent	blue	200-9150-00	0,001
					yellow	200-9170-00	0,001
					green	200-9140-00	0,001
					orange	200-9110-00	0,001
					red	200-9120-00	0,001
					white	200-9160-00	0,001
		18 mm dia.	flat	transparent/translucent	blue	200-1150-00	0,001
					yellow	200-1170-00	0,001
					green	200-1140-00	0,001
					orange	200-1110-00	0,001
					red	200-1120-00	0,001
					white	200-1160-00	0,001
		24 mm dia.	flat	transparent/translucent	blue	200-7150-00	0,001
					yellow	200-7170-00	0,001
					green	200-7140-00	0,001
					orange	200-7110-00	0,001
					red	200-7120-00	0,001
					white	200-7160-00	0,001
	IP 65	24 x 24 mm	flat	transparent/translucent	blue	200-9150-W0	0,002
					yellow	200-9170-W0	0,002
					green	200-9140-W0	0,002
					orange	200-9110-W0	0,002
					red	200-9120-W0	0,002
					white	200-9160-W0	0,002
		24 mm dia.	flat	transparent/translucent	blue	200-7150-W0	0,002
					yellow	200-7170-W0	0,002
					green	200-7140-W0	0,002
					orange	200-7110-W0	0,002
					red	200-7120-W0	0,002
					white	200-7160-W0	0,002



Continued on next page

lens of plastic (not recommended for film insert)	IP 40	18 x 18 mm	flat	transparent/ transparent	blue	200-3250-00	0,001
					yellow	200-3270-00	0,001
					green	200-3240-00	0,001
					orange	200-3210-00	0,001
					red	200-3220-00	0,001
					white	200-3260-00	0,001
		18 x 24 mm	flat	transparent/ transparent	blue	200-5250-00	0,001
					yellow	200-5270-00	0,001
					green	200-5240-00	0,001
					orange	200-5210-00	0,001
					red	200-5220-00	0,001
					white	200-5260-00	0,001
		24 x 24 mm	flat	transparent/ transparent	blue	200-9250-00	0,001
					yellow	200-9270-00	0,001
					green	200-9240-00	0,001
					orange	200-9210-00	0,001
					red	200-9220-00	0,001
					white	200-9260-00	0,001
		18 mm dia.	flat	transparent/ transparent	blue	200-1250-00	0,001
					yellow	200-1270-00	0,001
					green	200-1240-00	0,001
					orange	200-1210-00	0,001
					red	200-1220-00	0,001
					white	200-1260-00	0,001
		24 mm dia.	flat	transparent/ transparent	blue	200-7250-00	0,001
					yellow	200-7270-00	0,001
					green	200-7240-00	0,001
					orange	200-7210-00	0,001
					red	200-7220-00	0,001
					white	200-7260-00	0,001
	IP 65	24 x 24 mm	flat	transparent/ transparent	blue	200-9250-W0	0,002
					yellow	200-9270-W0	0,002
					green	200-9240-W0	0,002
					orange	200-9210-W0	0,002
					red	200-9220-W0	0,002
					white	200-9260-W0	0,002
		24 mm dia.	flat	transparent/ transparent	blue	200-7250-W0	0,002
					yellow	200-7270-W0	0,002
					green	200-7240-W0	0,002
					orange	200-7210-W0	0,002
					red	200-7220-W0	0,002
					white	200-7260-W0	0,002
of plastic (not for film insert and illumination)	IP 40	18 x 18 mm	flat	opaque/translucent	grey	200-3180-00	0,001
					black	200-3190-00	0,001
		18 x 24 mm	flat	opaque/translucent	grey	200-5180-00	0,001
					black	200-5190-00	0,001
		24 x 24 mm	flat	opaque/translucent	grey	200-9180-00	0,001
					black	200-9190-00	0,001
		18 mm dia.	flat	opaque/translucent	grey	200-1180-00	0,001
					black	200-1190-00	0,001
		24 mm dia.	flat	opaque/translucent	grey	200-7180-00	0,001
					black	200-7190-00	0,001
	IP 65	24 x 24 mm	flat	opaque/translucent	grey	200-9180-W0	0,002
					black	200-9190-W0	0,002
		24 mm dia.	flat	opaque/translucent	grey	200-7180-W0	0,002
					black	200-7190-W0	0,002

mushroom-head cap

can only be used with front bezel 18 mm dia.

	degree of protection	mushroom	colour	18 x 24 mm Typ-Nr.	24 x 24 mm Typ-Nr.	24 mm dia. Typ-Nr.	 (kg)
mushroom-head cap	IP 40	opaque	yellow	200-5370-00	200-9370-00	200-7370-00	0,005
			green	200-5340-00	200-9340-00	200-7340-00	0,005
			red	200-5320-00	200-9320-00	200-7320-00	0,005
			black	200-5390-00	200-9390-00	200-7390-00	0,005

**front cap for keylock-/selector switch 2 positions**

for IP 40/IP 65, will be delivered assembled

	front dimension pushbutton	for switching action	marking	colour	part no.	 (kg)
front cap for keylock-/selector switch 2 positions plastic, for types 761-... - 772-..., 911-... - 925-..., 811-... - 825-...	18 x 18 mm	0 - MA	0 - I (90°)	grey	200-3001-00	0,002
	18 x 24 mm	0 - MA	0 - I (90°)	black	200-4001-00	0,002
				grey	200-5001-00	0,002
	24 x 24 mm	0 - MA	0 - I (90°)	black	200-6001-00	0,002
				grey	200-9001-00	0,002
	18 mm dia.	0 - MA	0 - I (90°)	black	200-0001-00	0,002
				grey	200-1001-00	0,002
	24 mm dia.	0 - MA	0 - I (90°)	black	200-2001-00	0,002
				grey	200-7001-00	0,002
	24 mm dia.	0 - M	0 - I (60°)	black	200-8001-00	0,002
plastic, for types 781-... - 782-..., 931-... - 935-..., 831-... - 835-...	18 x 18 mm	0 - M	0 - I (60°)	grey	200-3001-01	0,002
	18 x 24 mm	0 - M	0 - I (60°)	black	200-4001-01	0,002
				grey	200-5001-01	0,002
	24 x 24 mm	0 - M	0 - I (60°)	black	200-6001-01	0,002
				grey	200-9001-01	0,002
	18 mm dia.	0 - M	0 - I (60°)	black	200-0001-01	0,002
				grey	200-1001-01	0,002
	24 mm dia.	0 - M	0 - I (60°)	black	200-2001-01	0,002
				grey	200-7001-01	0,002
	24 mm dia.	0 - M	0 - I (60°)	black	200-8001-01	0,002
of plastic, fits for all types	18 x 18 mm	M- or MA action	without marking	grey	200-3004-00	0,002
	18 x 24 mm	M- or MA action	without marking	black	200-4004-00	0,002
				grey	200-5004-00	0,002
	24 x 24 mm	M- or MA action	without marking	black	200-6004-00	0,002
				grey	200-9004-00	0,002
	18 mm dia.	M- or MA action	without marking	black	200-0004-00	0,002
				grey	200-1004-00	0,002
	24 mm dia.	M- or MA action	without marking	black	200-2004-00	0,002
				grey	200-7004-00	0,002
	24 mm dia.	M- or MA action	without marking	black	200-8004-00	0,002



front cap for keylock-/selector switch 3 positions

for IP 40/IP 65, will be delivered assembled

	front dimension	for switching action	marking	colour	part no.	000000
front cap for keylock-/selector switch 3 positions plastic, for type 712-...	18 x 18 mm	M - 0 - M	I (90°) - 0 - II (90°)	grey	200-3002-00	0,002
				black	200-4002-00	0,002
	18 x 24 mm	M - 0 - M	I (90°) - 0 - II (90°)	grey	200-5002-00	0,002
				black	200-6002-00	0,002
	24 x 24 mm	M - 0 - M	I (90°) - 0 - II (90°)	grey	200-9002-00	0,002
				black	200-0002-00	0,002
	18 mm dia.	M - 0 - M	I (90°) - 0 - II (90°)	grey	200-1002-00	0,002
				black	200-2002-00	0,002
	24 mm dia.	M - 0 - M	I (90°) - 0 - II (90°)	grey	200-7002-00	0,002
				black	200-8002-00	0,002
	18 x 18 mm	O - M - M	O (90°) - I - II (90°)	grey	200-3003-01	0,002
				black	200-4003-01	0,002
plastic, for type 722-...	18 x 24 mm	O - M - M	O (90°) - I - II (90°)	grey	200-5003-01	0,002
				black	200-6003-01	0,002
	24 x 24 mm	O - M - M	O (90°) - I - II (90°)	grey	200-9003-01	0,002
				black	200-0003-01	0,002
	18 mm dia.	O - M - M	O (90°) - I - II (90°)	grey	200-1003-01	0,002
				black	200-2003-01	0,002
plastic, for type 732-...	24 mm dia.	O - M - M	O (90°) - I - II (90°)	grey	200-7003-01	0,002
				black	200-8003-01	0,002
	18 x 18 mm	M - 0 - M	I (60°) - 0 - II (60°)	grey	200-3002-02	0,002
				black	200-4002-02	0,002
	18 x 24 mm	M - 0 - M	I (60°) - 0 - II (60°)	grey	200-5002-02	0,002
				black	200-6002-02	0,002
	24 x 24 mm	M - 0 - M	I (60°) - 0 - II (60°)	grey	200-9002-02	0,002
				black	200-0002-02	0,002
	18 mm dia.	M - 0 - M	I (60°) - 0 - II (60°)	grey	200-1002-02	0,002
				black	200-2002-02	0,002
	24 mm dia.	M - 0 - M	I (60°) - 0 - II (60°)	grey	200-7002-02	0,002
				black	200-8002-02	0,002
plastic, for type 742-...	18 x 18 mm	MA - 0 - M	I (90°) - 0 - II (60°)	grey	200-3002-03	0,002
				black	200-4002-03	0,002
	18 x 24 mm	MA - 0 - M	I (90°) - 0 - II (60°)	grey	200-5002-03	0,002
				black	200-6002-03	0,002
	24 x 24 mm	MA - 0 - M	I (90°) - 0 - II (60°)	grey	200-9002-03	0,002
				black	200-0002-03	0,002
	18 mm dia.	MA - 0 - M	I (90°) - 0 - II (60°)	grey	200-1002-03	0,002
				black	200-2002-03	0,002
	24 mm dia.	MA - 0 - M	I (90°) - 0 - II (60°)	grey	200-7002-03	0,002
				black	200-8002-03	0,002
	18 x 18 mm	M - 0 - MA	I (60°) - 0 - II (90°)	grey	200-3002-04	0,002
				black	200-4002-04	0,002
plastic, for type 752-...	18 x 24 mm	M - 0 - MA	I (60°) - 0 - II (90°)	grey	200-5002-04	0,002
				black	200-6002-04	0,002
	24 x 24 mm	M - 0 - MA	I (60°) - 0 - II (90°)	grey	200-9002-04	0,002
				black	200-0002-04	0,002
	18 mm dia.	M - 0 - MA	I (60°) - 0 - II (90°)	grey	200-1002-04	0,002
				black	200-2002-04	0,002
	24 mm dia.	M - 0 - MA	I (60°) - 0 - II (90°)	grey	200-7002-04	0,002
				black	200-8002-04	0,002



Continued on next page

front cap for keylock-/selector switch 3 positions of plastic, fits for all types	18 x 18 mm	M- or MA action	without marking	grey	200-3004-00	0,002
				black	200-4004-00	0,002
	18 x 24 mm	M- or MA action	without marking	grey	200-5004-00	0,002
				black	200-6004-00	0,002
	24 x 24 mm	M- or MA action	without marking	grey	200-9004-00	0,002
				black	200-0004-00	0,002
	18 mm dia.	M- or MA action	without marking	grey	200-1004-00	0,002
				black	200-2004-00	0,002
	24 mm dia.	M- or MA action	without marking	grey	200-7004-00	0,002
				black	200-8004-00	0,002

lever

will be delivered assembled

	construction	colour	part no.	
lever	short	black	200-.704-00	0,001
		chromium-plated	200-.604-00	0,001
	long	black	200-.904-00	0,001
		chromium-plated	200-.804-00	0,001



buzzer element

	voltage	colour	 18 x 24 mm Typ-Nr.	 24 x 24 mm Typ-Nr.	
buzzer element	6 V AC/DC	grey	970-5006-00	970-9006-00	0,004
		black	970-6006-00	970-0006-00	0,004
	12 V AC/DC	grey	970-5012-00	970-9012-00	0,004
		black	970-6012-00	970-0012-00	0,004
	24 V AC/DC	grey	970-5024-00	970-9024-00	0,004
		black	970-6024-00	970-0024-00	0,004



push-pull knob

	knob	colour	part no.	
push-pull knob	transparent	blue	200-.255-00	0,003
		yellow	200-.275-00	0,003
		green	200-.245-00	0,003
		red	200-.225-00	0,003
		white	200-.265-00	0,003



front bezel for illuminated-/pushbutton 55 - 70 mm and indicator 30 - 70 mm

	degree of protection	front dimension	material	colour	part no.	
front bezel for illuminated-/pushbutton 55 - 70 mm and indicator 30 - 70 mm	IP 40	18 x 18 mm	plastic	grey	200-3000-00	0,002
				black	200-4000-00	0,002
		18 x 24 mm	plastic	grey	200-5000-00	0,002
				black	200-6000-00	0,002
		24 x 24 mm	plastic	grey	200-9000-00	0,002
				black	200-0000-00	0,002
		18 mm dia.	plastic	grey	200-1000-00	0,002
				black	200-2000-00	0,002
	IP 65	24 mm dia.	plastic	grey	200-7000-00	0,002
				black	200-8000-00	0,002
		24 x 24 mm	plastic	grey	200-9000-W0	0,002
				black	200-0000-W0	0,002
		24 mm dia.	plastic	grey	200-7000-W0	0,002
				black	200-8000-W0	0,002



front bezel for mushroom-head pushbutton 55 - 70 mm

	degree of protection	material	colour	18 mm dia. Typ-Nr.	
front bezel for mushroom-head pushbutton 55 - 70 mm	IP 40	plastic	grey	200-1000-00	0,002
			black	200-2000-00	0,002



front bezel for buzzer 30 - 55 mm


	degree of protection	material	colour	 18 x 24 mm Typ-Nr.	 24 x 24 mm Typ-Nr.	
front bezel for buzzer 30 - 55 mm	IP 40	plastic	grey	200-5000-00	200-9000-00	0,002
			black	200-6000-00	200-0000-00	0,002



front bezel-set for flush mounting

to us as IP 40: cut off (with knife) the anti-twisting at the front bezel/actuator


	degree of protection	material	colour	 18 x 24 mm Typ-Nr.	 18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	
front bezel-set for flush mounting 24 x 24 mm	IP 40/IP 65	plastic	black		200-4400-V0		0,007
24 x 30 mm	IP 40/IP 65	plastic	black	200-6400-V0			0,008
25 mm dia.	IP 40/IP 65	plastic	black			200-8400-V0	0,006



front bezel set for flush mounting for buzzer

to us as IP 40: cut off (with knife) the anti-twisting at the front bezel/actuator

	degree of protection	material	colour	 18 x 24 mm Typ-Nr.	
front bezel set for flush mounting for buzzer 24 x 30 mm	IP 40	plastic	black	200-6400-V0	0,008



protective cover for 35 mm

for pushbuttons 35 mm

	degree of protection	 18 x 24 mm Typ-Nr.	 18 x 18 mm Typ-Nr.	technical drawing	
protective cover for 35 mm hinged, transparent, with means for sealing	IP 40	200-6008-00	200-4008-00	58	0,002
	IP 65	200-6008-W0	200-4008-W0	58	0,002



technical drawings from page 642

protective cover for illuminated-/pushbutton 55 - 70 mm

		⌀ 18 x 24 mm Typ-Nr.	⌀ 18 x 18 mm Typ-Nr.	⌀ 24 x 24 mm Typ-Nr.	technical drawing	
protective cover for illuminated-/pushbutton 55 - 70 mm hinged, transparent, not with means for sealing, for use as IP 40: cut off (with knife) the anti-twisting at the front bezel/actuator	degree of protection IP 40/IP 65			200-0008-W0	58	0,006
hinged, transparent, with means for sealing	IP 40	200-6008-00	200-4008-00		58	0,005




technical drawings from page 642

protective cover for flush mounting


to us as IP 40: cut off (with knife) the anti-twisting at the front bezel/actuator

	degree of protection	use	material	colour	⌀ 18 x 24 mm Typ-Nr.	⌀ 18 x 18 mm Typ-Nr.	
protective cover for flush mounting 24x24 mm, hinged, transparent, with means for sealing	IP 40/IP65	for illuminated pushbutton/keylock switch	plastic	black		200-4408-V0	0,006
24x30 mm, hinged, transparent, with means for sealing	IP 40/IP65	for illuminated pushbutton/keylock switch	plastic	black	200-6408-V0		0,006



sprayproof cover

	material	⌀ 18 x 24 mm Typ-Nr.	⌀ 18 x 18 mm Typ-Nr.	
sprayproof cover 24x24 mm, two-part, protection IP 65, illumination exchangeable from the front	PVC		200-3009-W0	0,003
24x30 mm, two-part, protection IP 65, illumination exchangeable from the front	silicone	200-5009-W0		0,003



protective guard for illuminated-/pushbutton

for mounting depth 55/70 mm

	⌀ 18 x 24 mm Typ-Nr.	⌀ 18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	
protective guard for illuminated-/pushbutton aluminium anodized colourless, 18x20 mm		200-3007-00		0,002
aluminium anodized colourless, 20x24 mm	200-5007-00			0,002
aluminium anodized colourless, 20 mm dia.			200-1007-00	0,002



pressure ring

for indicator IP 65, mounting depth 30/45 mm, obligatory

	part no.	
pressure ring plastic suitable for 24 dia. mm and 24 x 24 mm	200-8009-W0	0,001



sealing ring

for front bezel IP 65, 24 dia. mm and 24 x 24 mm

	degree of protection	material	part no.	
sealing ring	IP 65	silicone	200-9009-W0	0,001



sealing bulb

for lens IP65, 24 dia. mm and 24 x 24 mm

	degree of protection	material	part no.	
sealing bulb	IP 65	silicone	200-7009-W0	0,001



blind plug

for lenses and pushbuttons 30/45/55/70 mm

	degree of protection	colour	18 x 24 mm Typ-Nr.	18 x 18 mm Typ-Nr.	18 mm dia. Typ-Nr.	24 x 24 mm Typ-Nr.	kg
blind plug for mounting hole 16.2 mm dia.	IP 40	grey	200-5006-00	200-3006-00	200-1006-00		0,003
		black	200-6006-00	200-4006-00	200-2006-00		0,003
	IP 65	black	200-6006-W0	200-4006-W0	200-2006-W0	200-0006-W0	0,003



spare key

add to the part no., the engraved lock no.

	use	part no.	kg
spare key for standard lock 1001	for emergency stop switch foolproof with key to release	240-4001-00	0,005
for standard lock B2 300, other lock numbers on request	for keylock switch	240-2001-00	0,005
for standard lock B2 390, other lock numbers on request	for emergency stop switch with key to release	240-3001-00	0,005



At ordering indicate marked lock no.

at back

snap-action switching element block for 35 mm

for pushbuttons 35 mm

	contacts	connection method	part no.	circuit drawing	component layout	kg
snap-action switching element block for 35 mm	1 NC + 1 NO	-	601-0000-00	56		0,006
		P	601-0000-0P	56	1	0,006
	1 NC + 1 NO + 1	-	608-0000-00	58		0,006
		P	608-0000-0P	58	1	0,006
	1 NC + 1 NO + 2	-	609-0000-00	59		0,006
		P	609-0000-0P	59	1	0,006
	2 NC + 2 NO	-	602-0000-00	57		0,006
		P	602-0000-0P	57	1	0,006



circuit drawings from page 657, component layouts from page 657

lamp element block for 35 mm

for indicator 35 mm

	diodes	connection method	part no.	circuit drawing	component layout	
lamp element block for 35 mm	0	-	600-0000-00	1		0,005
		P	600-0000-0P	1	1	0,005
	1	-	606-0000-00	60		0,006
		P	606-0000-0P	60	1	0,006
	2	-	607-0000-00	61		0,006
		P	607-0000-0P	61	1	0,006



circuit drawings from page 657, component layouts from page 657

blind element

	part no.	
blind element white	202-0600-00	0,002



lamp terminal

	use	part no.	
lamp terminal	for soldering-/plug-in terminal	270-0000-00	0,001
	for PCB terminal	270-0000-0P	0,001



intermediate section

	use	part no.	
intermediate section incl. fixing nut	for illuminated pushbutton 55 mm MG T 1 3/4	260-9000-00	0,005
	for illuminated pushbutton 70 mm T 5.5	260-8000-00	0,008



snap-action switching element

	contacts	colour	connection method	material of contacts	part no.	technical drawing	
snap-action switching element	1 NC + 1 NO	blue	-	gold plated	201-0500-00	59	0,003
		grey	-	gold plated	201-0800-00	59	0,003
			P	gold plated	221-0800-0P	59	0,003
		green	-	gold plated	201-0400-00	59	0,003



technical drawings from page 642

holder for 2 switching elements

	use	material	part no.	
holder for 2 switching elements	push-pull illuminated switch	plastic	270-2000-00	0,001
	for pushbutton 35 mm, keylock-/selector switch 45 mm	plastic	270-3000-00	0,001



holder for 3 switching elements

	use	material	part no.	
holder for 3 switching elements	for illuminated-/pushbuttons 55-70 mm	stainless steel	270-1000-00	0,001



spring with pin


for maintained version at the intermediate section

	use	part no.	
spring with pin	for illuminated pushbutton 55/70 mm	260-0010-00	0,001



PCB plug-in base

	for	pin orientation	part no.	
PCB plug-in base lamp terminal 0.5 mikron Au	indicator 35/55/70 mm	angled	280-0200-00	0,006
		straight	280-0100-00	0,005
incl. lamp terminal 0.5 mikron Au	1NC + 1NO for 35/45 mm	angled	280-1210-00	0,006
		straight	280-1110-00	0,005
	1NC + 1NO for 55/70 mm	angled	280-1200-00	0,006
		straight	280-1100-00	0,005
	2NC + 2NO for 35/45/55/70 mm	angled	280-2200-00	0,006
		straight	280-2100-00	0,005
	3NC + 3NO for 55/70 mm	angled	280-3200-00	0,006
		straight	280-3100-00	0,005



multi-plug housing

	part no.	
multi-plug housing for flat connector with locating tongue with 14 terminal possibilities, 10 terminals plugable max.	280-0000-00	0,002



cable shoe

	use	locating tongue	wire cross-section of terminal	connection method	part no.	
cable shoe	for multi-plug housing (280-0000-00)	with	0.1 - 0.25 mm²	- 2.8 x 0.5 mm	280-0001-00	0,001
			0.5 - 1.00 mm²	- 2.8 x 0.5 mm	280-0002-00	0,001
as per VDE 0630 use with insulation socket (280-0010-00)	for insulation socket (280-0010-00)	without	0.2 - 0.75 mm²	- 2.8 x 0.5 mm	280-0003-00	0,001



connector with two outputs

	use	connection method	part no.	
connector with two outputs	for cable shoe (280-0003-00)	- 2.8 x 0.5 mm	280-0004-00	0,001



insulation socket

	part no.	
insulation socket for connector without locating tongue (280-0003-00)	280-0010-00	0,001



for illumination

filament lamp MG T 1 3/4

	voltage/current	part no.	
filament lamp MG T 1 3/4	14 V / 80 mA	10-1310.1319	0,001
	28 V / 40 mA	10-1313.1249	0,001
	36 V / 30 mA	10-1316.1209	0,001
	48 V / 25 mA	10-1319.1199	0,001
	6.3 V / 200 mA	10-1307.1369	0,001
	60 V / 20 mA	10-1320.1179	0,001



filament lamp T 5.5

	voltage/current	part no.	
filament lamp T 5.5	6 V / 200 mA	10-1106.1369	0,001
	12 V / 100 mA	10-1109.1329	0,001
	24 V / 50 mA	10-1112.1279	0,001
	36 V / 35 mA	10-1116.1229	0,001
	48 V / 25 mA	10-1119.1199	0,001



LED MG T 1 3/4

	number of chips	voltage/current	colour	part no.	
LED MG T 1 3/4 with built-in protective diode Note: For optimal illumination we strongly recommend using our new single-chip LEDs. For new designs, only the new single-chip LEDs should be chosen. They can be found on page 669.	6	6 VDC / 45 mA	yellow	10-5306.3254	0,001
			green	10-5306.3255	0,001
			red	10-5306.3252	0,001
		12 VDC / 25 mA	yellow	10-5309.3204	0,001
			green	10-5309.3205	0,001
			red	10-5309.3202	0,001
		24 VDC / 12.5 mA	yellow	10-5312.3134	0,001
			green	10-5312.3135	0,001
			red	10-5312.3132	0,001
		48 VDC / 12.5 mA	yellow	10-5319.3104	0,001
			green	10-5319.3105	0,001
			red	10-5319.3102	0,001



LED T 5.5

	number of chips	voltage/current	colour	part no.	
LED T 5.5 with built-in protective diode Note: For optimal illumination we strongly recommend using our new single-chip LEDs. For new designs, only the new single-chip LEDs should be chosen. They can be found on page 669.	6	6 VDC / 45 mA	yellow	10-5106.3254	0,001
			green	10-5106.3255	0,001
			red	10-5106.3252	0,001
		12 VDC / 25 mA	yellow	10-5109.3204	0,001
			green	10-5109.3205	0,001
			red	10-5109.3202	0,001
		24 VDC / 12.5 mA	yellow	10-5112.3144	0,001
			green	10-5112.3145	0,001
			red	10-5112.3142	0,001
		48 VDC / 12.5 mA	yellow	10-5119.3134	0,001
			green	10-5119.3135	0,001
			red	10-5119.3132	0,001



diode element

	diodes	colour	connection method	part no.	
diode element diode 1N/4007	1	red	-	212-0100-00	0,003
			P	222-0100-0P	0,003
	2	red	-	213-0100-00	0,003
			P	214-0100-0P	0,003



capacitor

for lamp voltage reduction

	value	part no.	
capacitor use with 60 V/20 mA, 50 Hz lamp voltage	220 V/0.27 μ F	300-0090-00	0,004



Please keep to the country specific security rules.

series resistor

for lamp voltage reduction

	value	part no.	
series resistor use with 60 V / 20 mA lamp rating	100 V / 2.7 k Ω	300-0010-00	0,003
	125 V / 3.3 k Ω	300-0020-00	0,003
	145 V / 4.7 k Ω	300-0030-00	0,003
	230 V / 8.2 k Ω	300-0040-00	0,003
	240 V / 10 k Ω	300-0050-00	0,003



Please keep to the country specific security rules.

terminal plate empty

for fitting with series resistors and capacitors

	no. of spaces	part no.	
terminal plate empty 125 x 60 x 15 mm	10 spaces	300-0110-00	0,045
187.5 x 60 x 15 mm	15 spaces	300-0115-00	0,090
250 x 60 x 15 mm	20 spaces	300-0120-00	0,095
62.5 x 60 x 15 mm	5 spaces	300-0105-00	0,025



for emergency stop switch

label for emergency stop switch

	degree of protection	marking	43 mm dia. Typ-Nr.	
label for emergency stop switch yellow, other constructions on request	IP 40	in German	200-1300-02	0,002
		in English	200-1300-03	0,002
		in French	200-1300-04	0,002
		without	200-1300-01	0,002
	IP 65	in German	200-1300-W2	0,002
		in English	200-1300-W3	0,002
		in French	200-1300-W4	0,002
		without	200-1300-W1	0,002



slow-make switching element for emergency stop switch

	contacts	colour	connection method	material of contacts	part no.	technical drawing	
slow-make switching element for emergency stop switch	1 NC	grey	-	gold plated	211+0800-00	60	0,003
			P	gold plated	231+0800-0P	60	0,003



technical drawings from page 642

dismantling tool for emergency stop switch foolproof

	part no.	
dismantling tool for emergency stop switch foolproof	300-0017-00	0,004



assembling

fixing nut

for standard mounting

	use	panel thickness	colour	part no.	
fixing nut plastic	for mounting depth 30-70 mm	1-3 mm	grey	260-0001-00	0,001
		3-5 mm	grey	260-0002-00	0,001
		5-7 mm	grey	260-0005-00	0,001
	for mounting depth 35 mm	1-3 mm	black	260-0003-00	0,001



fixing nut for flush mounting

	use	panel thickness	colour	part no.	
fixing nut for flush mounting plastic	for mounting depth 41/44 mm	1-3 mm	black	260-0003-00	0,001
	for mounting depth 39-79 mm	3-5 mm	grey	260-0002-00	0,001



location strip

for indicators, illuminated/push buttons, push-pull illuminated button, buzzer, mushroom-head cap, key and selector switches and emergency button 55-70 mm IP 40 / IP 65 designs

	use	part no.	
location strip anti-twisting, in-line arrays or single switches	graduation 18 mm	260-0020-00	0,001
	graduation 24 mm	260-0021-00	0,001



lens remover

	part no.	
lens remover	300-0001-00	0,012



lamp/LED remover

	part no.	
lamp/LED remover	300-0002-00	0,003

Warning:
when replacing lamps/LED a switching process can be triggered!



mounting tool


	part no.	
mounting tool for tightening (or loosening) fixing nuts (at dismantled element block)	300-0003-00	0,007



contact element pliers

for block mounting

	part no.	
contact element pliers for dismantling the switching elements off the holder for 3 switching elements	300-0005-00	0,013



jaw spanner

	part no.	
jaw spanner for tightening (or loosening) fixing nuts and dismantling of the element blocks (mounting depth 35-70 mm)	300-0004-00	0,003



cable shoe remover

	part no.	
cable shoe remover for removing the connector from the multi-plug housing (280-0000-00)	300-0006-00	0,001



Switching system

Self-cleaning, double-break slow-make element with four-path contacts (contact opening width 2 x 1.5 mm). The slow-make elements are constructed as per DIN EN 60947-5-1.

Materials

Mushroom-head cap

Polyamide PA

Actuator housing

Polyetherimide PEI, self-extinguishing

Switching element

Polyamide PA

Polysulfone PSU

Contact material

Silver

Connections

Solder/plug-in terminal

max. wire diameter: 2 wires of 1 mm

max. wire cross-section: 1 strand at 0.75 mm²

Connection

2.8 x 0.5 mm

Mechanical characteristic values

Actuating travel

EMERGENCY button 10 mm

Actuating force

max. 65 N (measured on mushroom-head cap of emergency button)

Self-aligning torque

15 Ncm

Shock resistance

(single impact, half-sinusoidal)

50 g, 11 ms as per IEC 512-4

Resistance to vibration

(sinusoidal)

10 g, at 10- 2000- 10- Hz

Amplitude 0.75 mm as per IEC 512-4

Rebound time

<= 2 ms

Degree of pollution

3

Protection class

Front side IP 65

Switching element IP 40

Ambient temperature

-25°C as per DIN EN 60068-2-1

+55°C as per DIN EN 60068-2-2

Storage temperature

-40°C to +85°C

Mechanical service life

EMERGENCY button 50,000 operations

Electrical characteristic values

Switch rating

Silver contact

(Solder/plug-inmin. 20 VAC, 10 mA

connection)max. 250 VAC, 5 A

Service category

Rated serviceRated service

voltagecurrent (inductive)

	AC 13	AC 14
250 VAC	3 A	2 A
120 VAC	5 A	3 A
60 VAC	6 A	4 A
24 VAC	6 A	5 A

Service category

Rated serviceRated service

voltagecurrent

	resistive	DC 13
240 VDC	0.5 A	0.2 A
110 VDC	0.7 A	0.4 A
60 VDC	2.0 A	1.0 A
24 VDC	6.0 A	2.0 A

Volume resistivity

New value for:

Silver contact

<= 50 m Ω

as per IEC 512-2 Test 5

Rated insulation voltage Ui

300 VAC

Electric strength

as per VDE 0660 (IEC 512-2-11)

4000 VAC, 50 Hz, 1 min between connections and earth

Overvoltage category

III

Thermal steady current

I_{th2} solder/plug-in connection 5 A

Max. permissible current for continuous operation and ambient temperature which does not exceed the specified max. values

Max. permissible rated current

for series-connected blow-out fuse
10 A gL

Electrical service life

Slow-make element 6050 operations

Approvals

- CE (declaration of conformity)
- CSA
- UR
- VDE
- ENEC

Right reserved to change all technical specifications.

EMERGENCY slow-make element

General

Is equipped with rigid contact link. The slow-make element opens positively and simply consists of a double-break NC. The multilayer contacts are designed for universal use and are gilded with a 2 µm gold coating. The EMERGENCY slow-make element is designed according to DIN EN 60947-5-1.

Material

Housing

Duroplast (DAP)
with fireproofing as per UL 94 V0

Contact

AgNi, 2 µm gilded

Contact carrier

Brass or CuBe

Connection

Brass gilded
2.8 x 0.5 mm solder/plug-in or PCB connection
1 mm² max. connection cross-section

Mechanical characteristic values

Ambient temperature

-25°C as per DIN EN 60068-2-1
+55°C as per DIN EN 60068-2-2

Storage temperature

-40°C to +85°C

Mechanical service life

8000 switching cycles

Contact opening width

> 2 x 1.5 mm

EMERGENCY switching element

Electrical characteristic values

Rated voltage

250 V / 50 Hz

Service category

AC 15: 250 V / 1 A

Rated insulation voltage U_i

250 V

Series-connected blow-out fuse

5 A gL

Conventional thermal current I_{th}

5 A

Electrical service life

8000 switching cycles AC 15: 250 V / 1 A

Diode element

General

Has no switching function. The diodes are soldered into the switching element housing between the contact connections.

Material

Housing

Thermoplast (PETP)
with fireproofing as per UL 94 V0

Connection

Brass gilded
2.8 x 0.5 mm solder/plug-in or PCB connection
1 mm² max. connection cross-section

Electrical characteristic values

Diode

1 N / 4007, $I_{max.} = 1 A$, $U_{block} = 1000 V$

Dummy element

General

Is inserted in empty places in the switching element block. The dummy element has no metal parts and no electrical function.

Material

Housing

Thermoplast (PET)
with fireproofing as per UL 94 V0

Alarm buzzer

Operating voltage

Current consumption

approx. 13 mA

Reverse-connect protection

yes

Acoustics

approx. 84 dB at 0.1 m

Frequency

approx. 2.3 kHz

Unit

General

In accordance with the low-voltage directive, our products are labelled with the CE mark.
SWISSTAC switches are modularly designed and are divided into the following three groups:

1. Front

Man-switch interface and state detector

2. Intermediate piece

Set and reset device, bulb holder, latching function

3. Switching element block

Up to five switching elements can be integrated in a switching element block.

Each switch is tested fully mounted. Electrical output and service life are determined by the switching element. Front and intermediate piece are designed for maximum service life of the switching element. They determine in what way the switches are protected against external influences. The type approvals relate to the complete switches. The approval regulations are UL 1054, VDE 0630 (EMERGENCY button VDE 0660), CSA 22.2.

Mechanical characteristic values

Resistance to vibration

tested as per DIN EN 60068-2-6 (10 g to 2000 Hz)

Shock resistance

tested as per DIN EN 60068-2-27 (semi-sinusoidal, 50 g during 11 ms) (single impacts, semi-sinusoidal)
15 g during 11 ms as per DIN EN 60068-2-29

Approvals

- CE (declaration of conformity)
- CSA
- UR
- VDE
- ENEC

Front

General

The front notifies the switching status, serves for activation of the switch and determines its type of protection. The form and colours of the front also characterise the appearance of the entire switching system. With the exception of the front γ 18 mm of the illuminated pushbuttons 55 and 70 mm, all front frame elements have activation protection.

Material

Lens

Thermoplast (PC)

Front bezel

Thermoplast with fireproofing (PBT)

Actuator 35 mm

Thermoplast with fireproofing (PBT)

Lock housing

Thermoplast with fireproofing (PBT)

Lock cylinder

Rynite reinforced with carbon fibre (PBT + CF)
Seal bellows (IP 65)
Silicon

Mechanical characteristic values

Protection class

as per IEC 529 (front side)

IP 40

IP 65

IP 67

protection against water

0 = without protection

5 = spray water

7 = watertight up to 1 m WS

protection against solid matter of varying size

4 = protection against solid matter $> \gamma$ 1 mm

6 = dust-tight

see "Intermediate piece" for other properties

Intermediate piece

General

The intermediate piece serves for several properties such as the setting and resetting functions, and the latching device. In addition, all parts necessary for a complete switch are fastened to the intermediate piece. These include the front parts, switching element block and lamps.

Material

Housing

Thermoplast with fireproofing (PC)

Lamp connection

Nickel silver 2.8 x 0.5 mm

Electrical characteristic values

Electric strength

3750 V AC, 1 min. as per DIN EN 61058-1

Insulation resistance

$> 10^{12} \Omega$ as per IEC 512-2-10

Illumination

Lamp voltage

6 V to 125 V as per CSA

6 V to 60 V as per VDE, UL, DEMKO

Lamp output

max. 1.2 W

Mechanical characteristic values

Ambient temperature

-25°C as per DIN EN 60068-2-1

+55°C as per DIN EN 60068-2-2

Storage temperature

-40°C to +85°C

Service life

> 2 x 10⁶ activations of the illuminated pushbuttons

> 5 x 10⁴ activations of the key and selector switches

> 8 x 10³ activations of the emergency button

> 2.5 x 10⁵ activations of the push-pull illuminated button

Switching element block

General

Up to five independent switching elements can be integrated in the switching element block as a switching unit. There are four different types of switching element available.

1. Snap-action switching element
2. Emergency button switching element
3. Diode element
4. Dummy element

Material

Bracket for three switching elements

rust-free chromium steel

Bracket for two switching elements

Thermoplast with fireproofing (PA6)

Lamp connection

CuBe, 2 µm Optalloy 2.8 x 0.5 mm solder/plug-in connection

Electrical characteristic values

Electric strength

2000 V AC, 50 Hz 1 min. (functional isolation)

Insulation resistance

> 10¹² W

In accordance with the VDE 0630 regulation, blade receptacles must be used with the insulation socket 280-0010-00.

Snap-action switching element

General

Is equipped with double-break jump contacts. Owing to the large cleaning path, outstanding self-cleaning is possible. The multilayer contacts are designed for universal use. They are gilded with a 2 µm gold coating. Each snap-action switching element comprises an NC (normally closed contact) and an NO (normally open contact)

Material

Housing

Thermoplast (PETP)

with fireproofing as per UL 94 V0

Contact

AgNi, 2 µm gilded

Contact carrier

Brass or CuBe

Connection

Brass gilded

2.8 x 0.5 mm solder/plug-in or PCB connection

1 mm² max. connection cross-section

Mechanical characteristic values

Ambient temperature

-25°C to +55°C

-25°C as per DIN EN 60068-2-1

+55°C as per DIN EN 60068-2-2

Storage temperature

-40°C to +85°C as per DIN EN 60068

Mechanical service life

2 x 10⁵ switching cycles

Contact opening width

2 x 0.65 mm

Contact cleaning path

2 x 0.6 mm

Rebound time

typically 0.5 ms

Activation force

approx. 2 N for each snap-action switching element

Electrical characteristic values

Thermal steady current Ith. max.

6 A, up to 3-pole switching element block

4 A, for 4- and 5-pole switching element blocks

Limited on thermal grounds to I_{max.} = 4 A

Volume resistivity

< = 50 m Ω typically, new statically

Electrical load as per DIN EN 61058-1

5(1.5) A 250 V up to 3 switching elements

4(1) A 250 V for 4 or 5 switching elements,

min. AC / DC: 5 V / 1 mA

Electrical service life

> 10⁴ switching operations

DIN EN 61058-1250 V, (1.5) A

DIN EN 60947-5-1 AC 12:250 V / 0.5 A

110 V / 2 A

75 V / 5 A

60 V / 6 A

48 V / 6 A

24 V / 6 A


Snap-action switching element

Out 4.7


In 3.6

technical drawings


1 indicator actuator 35 mm, pushbutton-/illuminated pushbutton actuator 35 mm
page 591, 592




2 indicator 30 - 70 mm, buzzer 30 - 55 mm
page 591, 607




3 indicator 30 - 70 mm
page 591




4 indicator 30 - 70 mm, buzzer 30 - 55 mm
page 591, 607



5 indicator 30 - 70 mm, buzzer 30 - 55 mm
page 591, 607




6 indicator 30 - 70 mm
page 591




7 indicator 30 - 70 mm

page 591




8 illuminated-/pushbutton 55 - 70 mm

page 593




9 illuminated-/pushbutton 55 - 70 mm

page 593




10 illuminated-/pushbutton 55 - 70 mm

page 593




11 illuminated-/pushbutton 55 - 70 mm

page 593




12 emergency stop switch 55 - 70 mm

page 594




13 emergency stop switch 55 - 70 mm

page 594




14 emergency stop switch 55 - 70 mm

page 594




15 emergency stop switch 55 - 70 mm

page 594




16 emergency stop switch foolproof 41 mm

page 596




17 pushbutton with mushroom-head cap 55 - 70 mm

page 597




18 pushbutton with mushroom-head cap 55 - 70 mm

page 597




19 pushbutton with mushroom-head cap 55 - 70 mm

page 597




20 pushbutton with mushroom-head cap 55 - 70 mm

page 597




21 keylock switch 2 positions 45 - 70 mm, keylock switch 3 positions 45 mm

page 598, 602




22 keylock switch 2 positions 45 - 70 mm, keylock switch 3 positions 45 mm

page 598, 602




23 keylock switch 2 positions 45 - 70 mm


page 598




24 keylock switch 2 positions 45 - 70 mm
page 598




25 keylock switch 2 positions 45 - 70 mm
page 598




26 keylock switch 2 positions 45 - 70 mm
page 598




27 selector switch 2 positions 45 - 70 mm, selector switch 3 positions 45 mm
page 603, 606




28 selector switch 2 positions 45 - 70 mm, selector switch 3 positions 45 mm
page 603, 606




29 selector switch 2 positions 45 - 70 mm
page 603




30 selector switch 2 positions 45 - 70 mm
page 603




31 selector switch 2 positions 45 - 70 mm
page 603




32 selector switch 2 positions 45 - 70 mm
page 603




33 push-pull illuminated switch 45 mm
page 607




34 push-pull illuminated switch 45 mm
page 607




35 indicator actuator 41-44 mm for flush mounting, illuminated-/pushbutton actuator 41-44 mm for flush mounting
page 608, 610




36 indicator for flush mounting 39 - 79 mm, buzzer for flush mounting 39 - 64 mm
page 609, 621




37 indicator for flush mounting 39 - 79 mm
page 609




38 indicator for flush mounting 39 - 79 mm, buzzer for flush mounting 39 - 64 mm
page 609, 621




39 indicator for flush mounting 39 - 79 mm, buzzer for flush mounting 39 - 64 mm
page 609, 621



40 indicator for flush mounting 39 - 79 mm
page 609




41 indicator for flush mounting 39 - 79 mm
page 609




42 pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm

page 611




43 pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm

page 611




44 pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm

page 611




45 pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm

page 611




46 keylock switch 2 positions for flush mounting 51 - 79 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm

page 612, 616




47 keylock switch 2 positions for flush mounting 51 - 79 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm

page 612, 616




48 keylock switch 2 positions for flush mounting 51 - 79 mm

page 612




49 keylock switch 2 positions for flush mounting 51 - 79 mm

page 612




50 keylock switch 2 positions for flush mounting 51 - 79 mm

page 612




51 keylock switch 2 positions for flush mounting 51 - 79 mm

page 612




52 selector switch 2 positions for flush mounting 51 - 79 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 617, 620




53 selector switch 2 positions for flush mounting 51 - 79 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 617, 620




54 selector switch 2 positions for flush mounting 51 - 79 mm

page 617




55 selector switch 2 positions for flush mounting 51 - 79 mm

page 617




56 selector switch 2 positions for flush mounting 51 - 79 mm

page 617




57 selector switch 2 positions for flush mounting 51 - 79 mm

page 617





58 protective cover for 35 mm, protective cover for illuminated-/pushbutton 55 - 70 mm


page 628, 629




page 632




page 591, 592




page 591, 592




3 indicator 30 - 70 mm, illuminated-/pushbutton 55 - 70 mm
page 591, 593,




4 emergency stop switch 55 - 70 mm
page 594




5 emergency stop switch 55 - 70 mm
page 594






6 emergency stop switch foolproof 41 mm
page 596






7 pushbutton with mushroom-head cap 55 - 70 mm page 597




8 keylock switch 2 positions 45 - 70 mm, keylock switch 3 positions 45 mm 598, 602,




9 keylock switch 2 positions 45 - 70 mm, keylock switch 3 positions 45 mm page 598, 602



10 selector switch 2 positions 45 - 70 mm, selector switch 3 positions 45 mm page 603, 606




for lever long




for lever short

11 selector switch 2 positions 45 - 70 mm, selector switch 3 positions 45 mm page 603, 606




for lever long



for lever short


12 buzzer 30 - 55 mm

page 607



13 push-pull illuminated switch 45 mm

page 607




14 indicator actuator 41-44 mm for flush mounting, indicator for flush mounting 39 - 79 mm, illuminated-/pushbutton actuator 41-44 mm for flush mounting, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm, keylock switch 2 positions for flush mounting 51 - 79 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm
page 608, 609, 610, 611, 612, 616


Ø25mm

24 x 30mm


24 x 24mm



15 selector switch 2 positions for flush mounting 51 - 79 mm, selector switch 3 positions for flush mounting 51 - 54 mm
page 617, 620




16 buzzer for flush mounting 39 - 64 mm
page 621



component layouts

1 indicator actuator 35 mm, indicator 30 - 70 mm, pushbutton-/illuminated pushbutton actuator 35 mm, illuminated-/pushbutton 55 - 70 mm, emergency stop switch 55 - 70 mm, pushbutton with mushroom-head cap 55 - 70 mm, keylock switch 2 positions 45 - 70 mm, keylock switch 3 positions 45 mm, selector switch 2 positions 45 - 70 mm, selector switch 3 positions 45 mm, buzzer 30 - 55 mm, push-pull illuminated switch 45 mm, indicator for flush mounting 39 - 79 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm, keylock switch 2 positions for flush mounting 51 - 79 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm, selector switch 2 positions for flush mounting 51 - 79 mm, selector switch 3 positions for flush mounting 51 - 54 mm, buzzer for flush mounting 39 - 64 mm, snap-action switching element block for 35 mm, lamp element block for 35 mm

page 591, 591, 592, 593, 594, 597, 598, 602, 603, 606, 607, 607, 609, 611, 612, 616, 617, 620, 621, 631, 632



circuit drawings

1 indicator actuator 35 mm, indicator 30 - 70 mm, indicator actuator 41-44 mm for flush mounting, indicator for flush mounting 39 - 79 mm, lamp element block for 35 mm

page 591, 591, 608, 609, 632


x1+



x2-


2 pushbutton-/illuminated pushbutton actuator 35 mm

page 592




3 pushbutton-/illuminated pushbutton actuator 35 mm


page 59




4 illuminated-/pushbutton 55 - 70 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm
593, 611,




5 illuminated-/pushbutton 55 - 70 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm
page 593, 611




6 illuminated-/pushbutton 55 - 70 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm
page 593, 611




7 illuminated-/pushbutton 55 - 70 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm
page 593, 611




8 illuminated-/pushbutton 55 - 70 mm, pushbutton-/illuminated pushbutton for flush mounting 61 - 79 mm
page 593, 611



9 emergency stop switch 55 - 70 mm
page 594




10 emergency stop switch 55 - 70 mm
page 594




11 emergency stop switch 55 - 70 mm

page 594




12 emergency stop switch foolproof 41 mm

page 596




13 emergency stop switch foolproof 41 mm

page 596




14 emergency stop switch foolproof 41 mm

page 596




15 pushbutton with mushroom-head cap 55 - 70 mm

page 597




16 pushbutton with mushroom-head cap 55 - 70 mm

page 597




17 pushbutton with mushroom-head cap 55 - 70 mm

page 597




18 pushbutton with mushroom-head cap 55 - 70 mm

page 597




19 pushbutton with mushroom-head cap 55 - 70 mm

page 597




20 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm

page 598, 612




21 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm

page 598, 612




22 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm

page 598, 612




23 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm

page 598, 612




24 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm


page 598, 612




25 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




26 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




27 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




28 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




29 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




30 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




31 keylock switch 2 positions 45 - 70 mm, keylock switch 2 positions for flush mounting 51 - 79 mm
page 598, 612




32 keylock switch 3 positions 45 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm
page 602, 616




33 keylock switch 3 positions 45 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm
page 602, 616




34 keylock switch 3 positions 45 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm
page 602, 616




35 keylock switch 3 positions 45 mm, keylock switch with 3 positions for flush mounting 51 - 54 mm
page 602, 616




36 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




37 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




38 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




39 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




40 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




41 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




42 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




43 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617



44 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




45 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm
page 603, 617




46 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm

page 603, 617




47 selector switch 2 positions 45 - 70 mm, selector switch 2 positions for flush mounting 51 - 79 mm

page 603, 617




48 selector switch 3 positions 45 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 606, 620




49 selector switch 3 positions 45 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 606, 620




50 selector switch 3 positions 45 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 606, 620




51 selector switch 3 positions 45 mm, selector switch 3 positions for flush mounting 51 - 54 mm

page 606, 620




52 buzzer 30 - 55 mm, buzzer for flush mounting 39 - 64 mm

page 607, 621




53 push-pull illuminated switch 45 mm

page 607




54 illuminated-/pushbutton actuator 41-44 mm for flush mounting

page 610




55 illuminated-/pushbutton actuator 41-44 mm for flush mounting

page 610




56 snap-action switching element block for 35 mm

page 631




57 snap-action switching element block for 35 mm

page 631




58 snap-action switching element block for 35 mm

page 631




59 snap-action switching element block for 35 mm


page 631



60 lamp element block for 35 mm
page 632



61 lamp element block for 35 mm
page 632



1. Engraving

The lens top or the lens holder can be engraved in any of the usual languages.
Typefaces: compressed typeface to DIN 1451. Other faces on request.

Colour of lettering

White for lens tops red, blue, green and black
Black for lens tops orange, yellow, grey and white
Black for lens holders translucent and transparent

Important!

With engraving, the position of the lens must agree with the position of the push-button or indicator.
However, the lens can be mounted turned through 180°.

2. Hot stamping

For lettering any sizeable quantity we recommend pad printing on the lens holder.

Important!

With pad printing, the position of the lens must agree with the position of the push-button or indicator.
However, the lens can be mounted turned through 180°.

3. Film insert


Instead of engraving, a transparent foil can be laid in the lens tops, except with the colours grey and black.

Foil thickness

0.1 mm max

Ø 18 mm	Ø 12,7 mm
18 x 18 mm	12,7 x 12,7 mm
18 x 24 mm	12,7 x 18,9 mm
Ø 24 mm	Ø 18,3 mm
24 x 24 mm	18,3 x 18,3 mm

Filmdickemax. 0,1mm



Important!

When a foil is used, the position of the lens must agree with the position of the push-button or indicator.
However, the lens can be mounted turned through 180°.

Height of letters	'round' 18		18 x 18		18 x 24		24 x 18		'round' 24		24 x 24	
	Number of lines	- Number of letters per line	Number of lines	- Number of letters per line	Number of lines	- Number of letters per line	Number of lines	- Number of letters per line	Number of lines	- Number of letters per line	Number of lines	- Number of letters per line
h												
2,5 mm	2	5	3	5	3	8	5	5	4	7	5	8
3 mm	2	5	3	5	3	8	4	5	3	7	4	8
4 mm	1	3	2	3	2	5	3	3	3	4	3	6
5 mm	1	2	1	3	1	5	2	3	2	3	2	5