

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0010891341](#)  
**Status:** **Obsolete**  
**Description:** 2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 34 Circuits, 6.10mm (.240") Mating Pin Length, 0.38µm (15µ") Gold (Au) Selective Plating

**Documents:**  
[Drawing \(PDF\)](#)

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                               |                                       |
|-------------------------------|---------------------------------------|
| Product Family                | PCB Headers                           |
| Series                        | <a href="#">8624</a>                  |
| Application                   | Board-to-Board, Signal, Wire-to-Board |
| Application Tooling Part Link | 011201230                             |
| Product Name                  | C-Grid®                               |

**Physical**

|                                |                        |
|--------------------------------|------------------------|
| Breakaway                      | Yes                    |
| Circuits (Loaded)              | 34                     |
| Circuits (maximum)             | 34                     |
| Durability (mating cycles max) | 50                     |
| Flammability                   | 94V-0                  |
| Glow-Wire Compliant            | No                     |
| Lock to Mating Part            | None                   |
| Material - Metal               | Brass, Phosphor Bronze |
| Material - Plating Mating      | Gold                   |
| Material - Plating Termination | Tin                    |
| Number of Rows                 | 2                      |
| Orientation                    | Vertical               |
| PC Tail Length                 | 2.79mm (.110")         |
| PCB Locator                    | No                     |
| PCB Retention                  | None                   |
| Packaging Type                 | Bag                    |
| Pitch - Mating Interface       | 2.54mm (.100")         |
| Plating min - Mating           | 0.381µm (15µ")         |
| Plating min - Termination      | 1.905µm (75µ")         |
| Polarized to Mating Part       | Yes                    |
| Polarized to PCB               | No                     |
| Shrouded                       | Fully                  |
| Stackable                      | Yes                    |
| Temperature Range - Operating  | -40°C to +105°C        |
| Termination Interface: Style   | Through Hole           |


**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 3A   |
| Voltage - Maximum             | 250V |

**Solder Process Data**

|                                                |                        |
|------------------------------------------------|------------------------|
| Duration at Max. Process Temperature (seconds) | 40                     |
| Lead-free Process Capability                   | Wave Capable (TH only) |
| Max. Cycles at Max. Process Temperature        | 3                      |
| Process Temperature max. C                     | 245                    |

**Material Info**



Series  
image - Reference only

**EU RoHS**

**ELV and RoHS  
Compliant**  
**REACH SVHC**  
**Contains SVHC: No**  
**Low-Halogen Status**  
**Not Low-Halogen**

**China RoHS**



**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of  
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any  
non-product compliance questions.

**Search Parts in this Series**  
[8624Series](#)

| | Old Part Number

86240057

**onlinecomponents.com**  
THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

This document was generated on 05/10/2011

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

onlinecomponents.com