





3

10057443-

STYLE : MECHAMICAL KEYING

I: I.8 VOLT. W/TYPE "C" 2 : 2,5 VOLT, W/TYPE "L"

3 : X.X VOLT. W/TYPE "R"

METAL CLIP:

(WITH NI 1.27 um MIN, PLATING)

I: WITH METAL CLIP + DIM. "D"=3.05 2 : WITH METAL CLIP + DIM, "D"=3,56 3 : WITH METAL CLIP + DIM, "D"=3,43

TAIL LENGTH

CODE	DIM. "B"	PCB THICKNESS
0	2.54	I.47 mm (0.058")
ı	2.67	1.60 mm (0.063")
2	3.18	2.36 mm (0.093")
3	4.00	3.18 mm (0.125")

— PLATING

CODE	CONTACT	SOLDERTAIL	UNDERPLATE
2	15 u"(0.38um) MIN, GOLD		FA #/ 1 07 )
3	30u"(0.76um) MIN. GOLD	100u"(2.54um) MIN. TIN/LEAD	50u"(I,27um) MIN, NICKEL OVERALL
4	3u"(0.076um) MIN. GOLD		
7LF	15u"(0,38um) MIN, GOLD	100u"(2.54um) MIN. 100% TIN	50u"(I.27um) MIN. NICKEL OVERALL
8LF	30u"(0.76um) MIN. GOLD		
9LF	3u"(0,076um) MIN, GOLD		
2 N	15 u"(0.38um) MIN. GOLD		90u"(2.29um) MIN. NICKEL OVERALL
3 N	30 u"(0.76um) MIN, GOLD	100u"(2,54um)   MIN, TIN/LEAD	
4 N	3 u"(0,076um) MIN. GOLD		
7 N L F	15 u"(0.38um) MIN. GOLD	100u"(2.54um) MIN. 100% TIN	90u"(2.29um) MIN. NICKEL OVERALL
8NLF	30 u"(0,76um) MIN, GOLD		
9 N L F	3 u"(0.076um) MIN. GOLD		

COLOR OF HOUSING AND EJECTOR

0 : BLACK HOUSING + IVORY EJECTOR I : BLUE HOUSING + IVORY EJECTOR 2 : BLACK HOUSING + BLACK EJECTOR

I. MATERIAL:

NOTE:

HOUSING: HIGH PERFORMANCE RESINS, GLASS FILLED UL94V-0 RATED. EJECTOR: HIGH PERFORMANCE RESINS, GLASS FILLED UL 94V-0 RATED.

TERMINAL : COPPER ALLOY. METAL CLIP: COPPER ALLOY.

2. PRODUCT SPECIFICATION: GS-12-300.

⚠ DIMENSIONS APPLICABLE WHEN COMPONENTS MOUNTED ON ONE OR BOTH SIDES.

AL CARD THICKNESS APPLIES ACROSS TABS AND INCLUDES PLATING AND/OR)

MEALIZATION STRAIGHTNESS CALLOUT APPLIES TO ZONE DEFINED BY THE 4.00 CONTACT AREA DIMENSION FOR THE ENTIRE LENGTH OF 133.35.

⚠ BOARD OF COMPONENT AREA.

LATCH DESIGN INCLUDES COMPLEMENTARY FEATURE TO ACCOMMODATE MODULE END NOTCHES AS DEFIND IN DETAIL A OF P.2 AND AS SPECIFIED IN MO-256.

7. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS

AS DESCRIBED IN GS-22-008. 8. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMP. FOR 10 SECONDS IN A WAVE SOLDER APPLICATION

9. IOO57443-XXXXXX(X)LF SERIES ARE FOR LEAD-FREE OPTIONS.

IO. DATE CODE: XXXXXXX MEANS MONTH/DAY/YEAR.

"\*" MEANS PRODUCTION LINE CODE.

FÇj

DDRII 240P FBDIMM SMALL HEAD SOCKET

10057443

Rev

В

Pro/E file catalog PDM: Rev:C

STATUS Released

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

FCI / Amphenol:

10057443-11109LF 10057443-11119LF 10057443-12207LF