

## 100LVELT22

### 3.3V Dual LVTT/LVCMOS to Differential LVPECL Translator

#### General Description

The 100LVELT22 is a LVTT/LVCMOS to differential LVPECL translator operating from a single +3.3V supply.

Both outputs of a differential pair should be terminated in  $50\Omega$  to  $V_{CC}$  - 2.0V even if only one output is being used. If an output pair is unused both outputs can be left open (un-terminated).

The 100 series is temperature compensated.

#### Features


- Typical propagation delay of 350 ps
- $<100$  ps skew between outputs
- Max  $I_{CC}$  of 28 mA at  $25^\circ C$
- When TTL input is left Open Q output defaults HIGH
- Fairchild MSOP-8 package is a drop-in replacement to ON TSSOP-8
- Flow through pinout
- Meets or exceeds JEDEC specification EIA/JESD78 IC latch-up test
- Moisture Sensitivity Level 1
- ESD Performance:  
Human Body Model > 2000V  
Machine Model > 200V

#### Ordering Code:


Order Number	Package Number	Product Code Top Mark	Package Description
100LVELT22M	M08A	KVT22	8-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow
100LVELT22M8 (Preliminary)	MA08D	KR22	8-Lead Molded Small Outline Package (MSOP), JEDEC MO-187, 3.0mm Wide

Devices also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code.

#### Connection Diagram



#### Logic Diagram



#### Pin Descriptions

Pin Name	Description
$Q_n, \bar{Q}_n$	LVPECL Differential Outputs
$D_0, D_1$	LVTT/LVCMOS Inputs
$V_{CC}$	Positive Supply
GND	Ground

**Absolute Maximum Ratings**(Note 1)

Supply Voltage ( $V_{CC}$ )	0.0V to +7.0V
Input Voltage ( $V_I$ ) $V_I \leq V_{CC}$	0.0V to +7.0V
DC Output Current ( $I_{OUT}$ )	
Continuous	50 mA
Surge	100 mA
Storage Temperature ( $T_{STG}$ )	-65°C to +150°C

**Recommended Operating Conditions**

Power Supply Operating	$V_{CC} = 3.0V$ to 3.8V
LVTT/LVCMS Input Voltage	0.0V to $V_{CC}$
Free Air Operating Temperature ( $T_A$ )	-40°C to +85°C

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum rating. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

**LVPECL DC Electrical Characteristics**  $V_{CC} = 3.3V$ ; GND = 0.0V (Note 2)

Symbol	Parameter	-40°C			25°C			85°C			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$I_{CC}$	Power Supply Current		28			28			29		mA
$V_{OH}$	Output HIGH Voltage (Note 3)	2215	2420	2275	2420	2275	2420	2275	2420	2420	mV
$V_{OL}$	Output LOW Voltage (Note 3)	1470	1745	1490	1680	1490	1680	1490	1680	1680	mV

**Note 2:** Output parameters vary 1 to 1 with  $V_{CC}$ .  $V_{CC}$  can vary  $\pm 0.15V$ .

**Note 3:** Outputs are terminated through a  $50\Omega$  resistor to  $V_{CC} - 2.0V$ .

**Note:** Devices are designed to meet the DC specifications after thermal equilibrium has been established. Circuit is tested with air flow greater than 500LFPM maintained.

**LVTT/LVCMS DC Electrical Characteristics**  $V_{CC} = 3.3V$ ; GND = 0.0V (Note 4)

Symbol	Parameter	$T_A = -40^{\circ}C$ to $85^{\circ}C$			Units	Condition	
		Min	Typ	Max			
$I_{IH}$	Input HIGH Current		20		$\mu A$	$V_{IN} = 2.7V$	
			100			$V_{IN} = V_{CC}$	
$I_{IL}$	Input LOW Current		-200		$\mu A$	$V_{IN} = 0.5V$	
$V_{IK}$	Clamp Diode Voltage		-1.2		V	$I_{IN} = -18 mA$	
$V_{IH}$	Input HIGH Voltage	2.0			V		
$V_{IL}$	Input LOW Voltage		0.8		V		

**Note 4:**  $V_{CC}$  can vary  $\pm 0.15V$ .

**Note:** Devices are designed to meet the DC specifications after thermal equilibrium has been established. Circuit is tested with air flow greater than 500LFPM maintained.

**AC Electrical Characteristics**  $V_{CC} = 3.3V$ ; GND = 0.0V (Note 5)

Symbol	Parameter	-40°C			25°C			85°C			Units	Figure Number
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max		
$f_{MAX}$	Maximum Toggle Frequency		TBD			TBD			TBD		MHz	
$t_{JITTER}$	Cycle-to-Cycle Jitter		TBD			TBD			TBD		ps	
$t_{PLH} / t_{PHL}$	Propagation Delay (Note 6)	200	350	600	200	350	600	200	350	600	ps	Figure 1
$t_{SKEW}$	Skew Output-to-Output Part-to-Part		30	100		30	100		30	100	ps	
$t_r, t_f$	Output Rise Time Q (20% to 80%)	200	550	200	500	200	500	200	500	500	ns	Figure 2

**Note 5:**  $V_{CC}$  can vary  $\pm 0.15V$ .

**Note 6:** Specifications for standard LVTT input signal (see Figure 1).

## Switching Waveforms




FIGURE 1. LVTTL to Differential LVPECL Propagation Delay






FIGURE 2. Differential Output Edge Rates

**Physical Dimensions** inches (millimeters) unless otherwise noted

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



8-Lead Molded Small Outline Package (MSOP), JEDEC MO-187, 3.0mm Wide  
Package Number MA08D

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)