



# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

## TE CONNECTIVITY (TE) 20 MODII HDR DRRA SHRD .100CL

AMPMODU | AMPMODU Headers

103167-7

TE Internal Number: 103167-7

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **20**

Header Type **Shrouded**

### Product Drawings

[HDR ASSY, MOD II, SHROUDED, 4 SIDES, DBL ROW, .100X.100 RIGHT ANGLE, W/ .025 SQ POSTS](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To

**Printed Circuit Board**

Connector Style

**Plug**

PCB Mounting Orientation

**Right Angle**

Connector Type

**Header**

Row-to-Row Spacing

**2.54 mm [ .1 in ]**

Stabilizers

**Without**

Strain Relief

**Without**

	Strain Relief	<b>Without</b>
	Board Standoff Profile	<b>With Standard</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
<hr/>		
Configuration Features	Number of Positions	<b>20</b>
	Number of Rows	<b>2</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	<b>750 Vrms</b>
<hr/>		
Body Features	Header Type	<b>Shrouded</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
<hr/>		
Contact Features	Contact Protection	<b>With</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Protection Type	<b>Shrouded</b>
Contact Current Rating (A)	<b>3</b>	
<hr/>		
Termination Features	Termination Post Length	<b>3.43 mm [ .135 in ]</b>
	Termination End Plating Thickness (µin)	<b>100 – 200</b>
	Termination End Plating Material	<b>Tin-Lead Over Nickel</b>
	Termination Method to PC Board	<b>Through Hole</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>
	Mating Connector Lock Type	<b>Detent Windows</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>With</b>
	Mating Connector Lock	<b>With</b>

	Mating Alignment Type	Polarization
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
	Housing Style	<b>4-Sided</b>
Dimensions	Shrouded End Dimension	<b>3.81 mm [ .15 in ]</b>
	PCB Thickness (Recommended)	<b>1.397 mm [ .055 in ]</b>
	Mating Post Length	<b>8.08 mm [ .318 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>No</b>
Operation/Application	High Speed Serial Data Connector	<b>No</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Quantity	<b>144</b>
	Packaging Method	<b>Tray</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	PCB D-SUB CONNECTORS	STANDARD POWER RELAYS	IDC D-SUB CONNECTORS
 <p><b>10 MODII HDR DRRA SHRD .100CL</b> 102570-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>09 MSFL RCPT RA 318 (IN, FM, BL)</b> 747844-4</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>R10E1Y1-JJ10.0K=R10 R10E1Y1-JJ10.0K</b></p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>25 POS HDF RCPT, AP</b> 1658609-2</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>

