



DESIGNED FOR USE WITH RG 178/U & 196	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.036
FERRULE	.099
CONTACT	.025

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	K.L. 8-27-96	<i>[Signature]</i>

HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204
COMPONENT	MATERIAL	FINISH

.XXX = in
XX.X = mm (REF)

NOTES:
1. CAPTURED CENTER CONTACT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY K.L.	DATE 8-2-96	AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599									
	CHECKED BY RP	8-2-96										
FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°	USE ASSY PROCEDURE	TITLE OSSM RIGHT ANGLE CABLE PLUG-CRIMP ATTACHMENT								
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			NO. A.P. 408-04783 (10-019)	<table border="1"> <tr> <td>SIZE B</td> <td>CODE IDENT NO. 26805</td> <td>1037-7196-02</td> <td>REV 01₀</td> </tr> <tr> <td colspan="2">SCALE 4:1</td> <td colspan="2">SHEET 1 OF 1</td> </tr> </table>	SIZE B	CODE IDENT NO. 26805	1037-7196-02	REV 01 ₀	SCALE 4:1		SHEET 1 OF 1	
SIZE B	CODE IDENT NO. 26805	1037-7196-02	REV 01 ₀									
SCALE 4:1		SHEET 1 OF 1										

COPY IN PUERTO RICO

CUSTOMER DRAWING

AMP PART # 1044569-1
SHEET 1 OF 1 REV A