




FEATURES:

- Banana plug spring material is gold plated beryllium copper for low contact resistance and long insertion life.
- For test versatility, the banana plugs are designed with vertical stacking.
- The wire features a high strand count for excellent wire flexibility.
- The banana plugs are molded directly to the wire for added pull strength.

MATERIALS:

Plug Body – Brass, Gold Plated

Spring - Beryllium Copper, Gold Plated

Insulation – Polypropylene, Color Matches Wire

Wire - 20 AWG, Stranding 41 x 36 t.c., PVC Insulated. .087" (2,21mm) O.D., Color per Part Number.

RATINGS:

Operating Temperature: +55° C. (+131° F.) Max.

Operating Voltage: 3000 VRMS/DC (Remove power before handling)

Current: 5 Amperes

ORDERING INFORMATION: Model 1081-XX-*

Other wire lengths can be quoted upon request.

*= Color, Standard Colors: -0 Black, -2 Red

XX = Wire Length in Inches, Standard Lengths: 4" (10,16cm) , 8" (20,32) 12" (30,48cm), 18" (45,72), 24" (60,96cm), 36" (91,44cm), 48" (121,92cm) & 60" (152,4cm).

Other wire lengths can be quoted upon request.

*= Color, Standard Colors: -0 Black, -2 Red

Ordering Example: 1081-12-2 Wire length is 12" (30,48cm) and the Color is Red.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[1081-8-2](#) [1081-8-0](#) [1081-4-2](#) [1081-4-0](#) [1081-48-2](#) [1081-48-0](#) [1081-18-0](#) [1081-18-2](#) [1081-36-0](#) [1081-36-2](#) [1081-24-2](#) [1081-12-2](#) [1081-12-0](#) [1081-24-0](#) [1081-60-0](#) [1081-60-2](#) [1081-60-4](#) [1081-60-6](#)