

Technical drawing of a reel-to-reel tape, showing two views: a top view (reel) and a side view (tape).

Top View (Reel):

- REEL DIA. REF. (Reference diameter of the reel)
- FEED DIRECTION (Arrow pointing right)
- .500 [12.7] DIA. HOLE THRU (Diameter of the central hole)

Side View (Tape):

- WIDTH (Overall width of the tape)
- FEED DIRECTION (Arrow pointing right)
- PITCH (Distance between adjacent tape frames)
- .005 [0.15] (Tape thickness)
- .157 [4.0] (Distance between adjacent tape frames)
- .059 [1.5] DIA. HOLE (TYP.) (Typical diameter of the hole in the tape)
- .079 [2.0] (Distance between adjacent tape frames)
- .787 [20.0] (Overall length of the tape)
- .413 [10.5] REF. (Reference length of the tape)
- .016 [0.4] REF. (Reference length of the tape)

TAPE AND REEL SPECIFICATIONS:

- MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
1.732 [44.0] WIDE; 1.260 [32.0] PITCH

- 13.0 [330.2] DIA. 200 PIECES OF
PART NO. 1082 PER REEL.

KEYSTONE ELECTRONICS CORP. www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME 20mm SM COIN CELL HOLDER ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 3.19.09
		APP'D LN	SCALE X
TOLERANCES INCH [MM] DECIMAL ±.015 [± 0.38] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED		CODE C/M	DWG NO. 1082TR

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[1082TR](#)