


1090QA Series Non-Relampable Incandescent Indicator Lights

Description and Features



Mounting: Will snap-fit into Ø.500/.505 hole in panels
.020/.100 thick. Push-on speednut SN0461
also available. Mounting hole pattern on page SP2.

Terminals: Quick-connect, tinned brass

Lens: Polycarbonate

Bezel: Polished stainless steel. For black finish add "X"
after the series letter(s).

Housing: White Nylon

Lens Color	Incandescent	
	Model No. (12V)	Model No. (28V)
Red		
Amber		
White		
Green	1090QA1-12V	1090QA1-28V
Blue	1090QA3-12V	1090QA3-28V
	1090QA4-12V	1090QA4-28V
	1090QA5-12V	1090QA5-28V
	1090QA6-12V	1090QA6-28V
Lamp used	#2162	#2187

Underwriters Laboratories (UL) File No. E20325
Canadian Standards Association (CSA) File No. LR13346

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Chicago Miniature:

[1090QA3-12V](#) [1090QA4-12V](#) [1090QA6-12V](#) [1090QAX1-12V](#) [1090QAX1-28V](#) [1090QAX3-12V](#) [1090QAX3-28V](#)
[1090QAX4-12V](#) [1090QAX4-28V](#) [1090QAX5-12V](#) [1090QAX5-28V](#) [1090QAX6-12V](#) [1090QAX6-28V](#)