

The Automotive-Grade Device Handbook



Contents

- 1 Overview..... 4**
 - 1.1 Intel Automotive-Grade Devices..... 4
 - 1.2 Intel Automotive Qualifications..... 4
 - 1.3 Supported Device Families..... 4
- 2 Supported Automotive-Grade Devices.....6**
 - 2.1 Intel Cyclone 10 Devices..... 6
 - 2.1.1 Supported Automotive-Grade Devices.....6
 - 2.1.2 Package Options and Maximum User I/Os..... 7
 - 2.1.3 Device Ordering Codes..... 7
 - 2.2 Intel Arria 10 Devices.....7
 - 2.2.1 Supported Automotive-Grade Devices.....7
 - 2.2.2 Package Options and Maximum User I/Os..... 8
 - 2.2.3 Device Ordering Codes..... 9
 - 2.3 Enpirion Devices.....9
 - 2.3.1 Supported Automotive-Grade Devices.....9
 - 2.4 Intel MAX 10 Devices..... 10
 - 2.4.1 Supported Automotive-Grade Devices.....10
 - 2.4.2 Package Options and Maximum User I/Os..... 11
 - 2.4.3 Device Ordering Codes..... 13
 - 2.5 Cyclone V SoC Devices..... 13
 - 2.5.1 Supported Automotive-Grade Devices.....13
 - 2.5.2 Package Options and Maximum User I/Os..... 14
 - 2.5.3 Device Ordering Codes..... 15
 - 2.6 Cyclone V Devices.....16
 - 2.6.1 Supported Automotive-Grade Devices.....16
 - 2.6.2 Package Options and Maximum User I/Os..... 16
 - 2.6.3 Device Ordering Codes..... 18
 - 2.7 Cyclone IV Devices.....19
 - 2.7.1 Supported Automotive-Grade Devices.....19
 - 2.7.2 Package Options and Maximum User I/Os..... 20
 - 2.7.3 Device Ordering Codes..... 21
 - 2.8 MAX V Devices..... 22
 - 2.8.1 Supported Automotive-Grade Devices.....22
 - 2.8.2 Package Options and Maximum User I/Os..... 22
 - 2.8.3 Device Ordering Codes..... 23
 - 2.9 MAX II Devices..... 23
 - 2.9.1 Supported Automotive-Grade Devices.....23
 - 2.9.2 Device Ordering Codes..... 24
 - 2.10 Cyclone III Devices (Legacy Support)..... 24
 - 2.10.1 Supported Automotive-Grade Devices..... 24
 - 2.10.2 Device Ordering Codes.....25
 - 2.11 Cyclone II Devices (Legacy Support).....25
 - 2.11.1 Supported Automotive-Grade Devices..... 25
 - 2.11.2 Device Ordering Codes.....26
 - 2.12 Cyclone Devices (Legacy Support).....26
 - 2.12.1 Supported Automotive-Grade Devices..... 26



| | |
|--|-----------|
| 2.12.2 Device Ordering Codes..... | 26 |
| 2.13 MAX 7000A Devices (Legacy Support)..... | 27 |
| 2.13.1 Supported Automotive-Grade Devices..... | 27 |
| 2.13.2 Device Ordering Codes..... | 27 |
| 3 Intel Quartus Prime Software Support..... | 28 |
| 4 Power Analysis and Estimation..... | 29 |
| 4.1 Early Power Estimator..... | 29 |
| 4.2 Power Analyzer..... | 29 |
| 5 DC and Timing Specifications..... | 31 |
| 6 Pin-Out Information..... | 32 |
| 7 Package and Board Layout Information..... | 33 |
| A Document Revision History for the Automotive-Grade Device Handbook..... | 34 |



1 Overview

1.1 Intel Automotive-Grade Devices

Intel automotive-grade devices are available in CPLD, FPGA, system on a chip (SoC), and Enpirion PowerSoC's. You can use these devices for high-temperature environments, such as automotive driver assist, infotainment, and e-vehicle.

Related Links

[Automotive page, Intel® website](#)

Provides more information about Intel automotive solutions.

1.2 Intel Automotive Qualifications

Intel automotive-grade devices comply to the following qualifications:

- ISO-26262
- IEC-61508
- AEC-Q100
- ISO-9001
- TS-16949
- Electronic Industries Alliance (EIA)
- Joint Electron Device Engineering Council (JEDEC)

Related Links

[Automotive Quality and Reliability page, Intel website](#)

Provides more information about automotive quality.

1.3 Supported Device Families

Table 1. Intel Automotive-Grade Device Families

| Category | Product Family | Quartus Software Support ⁽¹⁾ | Description |
|---------------------|-------------------|---|---|
| IC, FPGA | Intel Cyclone® 10 | Version 17.1 and later | Low-cost, low-power, feature-rich FPGAs |
| IC, FPGA | Intel Arria® 10 | Version 14.0.2 and later | High-performance, low-power 20 nm FPGAs with hard floating-point digital signal processing (DSP) blocks |
| <i>continued...</i> | | | |

⁽¹⁾ Starting from version 15.1, the Quartus II software is known as the Intel Quartus® Prime software.



| Category | Product Family | Quartus Software Support ⁽¹⁾ | Description |
|-----------|---------------------------|---|---|
| IC, power | Enpirion | — | Integrated inductor, combination of small footprint, low noise performance, and high efficiency |
| IC, FPGA | Intel MAX [®] 10 | Version 14.0.2 and later | Low-cost, instant-on, small form factor programmable logic device |
| IC, SoC | Cyclone V SoC | Version 12.1 and later | Low-cost, low-power, user-customizable ARM-based SoC devices |
| IC, FPGA | Cyclone V | Version 11.1 and later | Low-cost, low-power, feature-rich 28 nm FPGAs |
| IC, FPGA | Cyclone IV | Version 9.1 SP2 and later | Low-cost, low-power, feature-rich 60 nm FPGAs (1.2 V) |
| IC, CPLD | MAX V | Version 11.0 and later | High-density, low-power glue logic CPLDs (1.8 V) |
| IC, CPLD | MAX II | Version 7.2 SP1 and later | High-density, low-power glue logic CPLDs (3.3 V, 2.5 V) |

| Volume Production Support for Legacy Device Families | | | |
|--|----------------|---|---|
| Category | Product Family | Quartus Software Support ⁽²⁾ | Description |
| IC, FPGA | Cyclone III | Version 8.0 to 13.1 | Low-cost, feature-rich 65 nm FPGAs |
| IC, FPGA | Cyclone II | Version 7.2 SP1 to 13.0 | Low-cost, feature-rich 90 nm FPGAs |
| IC, FPGA | Cyclone | Version 7.2 SP1 to 13.0 | Low-cost, glue logic 130 nm FPGAs |
| IC, CPLD | MAX 7000AE | Version 7.2 SP1 to 13.0 | High-performance, glue logic CPLDs (5-V I/O compatible) |

-
- (1) Starting from version 15.1, the Quartus II software is known as the Intel Quartus[®] Prime software.
- (2) The legacy devices are only supported in the Quartus II software.



2 Supported Automotive-Grade Devices

2.1 Intel Cyclone 10 Devices

2.1.1 Supported Automotive-Grade Devices

Table 2. Automotive-Grade in Intel Cyclone 10 Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| 10CL006YE144A7G | 10CL006 | 144-pin EQFP | -40°C to 125°C | -7 |
| 10CL006YU256A7G | 10CL006 | 256-pin UBGA | -40°C to 125°C | -7 |
| 10CL010YE144A7G | 10CL010 | 144-pin EQFP | -40°C to 125°C | -7 |
| 10CL010YM164A7G | 10CL010 | 164-pin MBGA | -40°C to 125°C | -7 |
| 10CL010YU256A7G | 10CL010 | 256-pin UBGA | -40°C to 125°C | -7 |
| 10CL016YE144A7G | 10CL016 | 144-pin EQFP | -40°C to 125°C | -7 |
| 10CL016YM164A7G | 10CL016 | 164-pin MBGA | -40°C to 125°C | -7 |
| 10CL016YU256A7G | 10CL016 | 256-pin UBGA | -40°C to 125°C | -7 |
| 10CL025YE144A7G | 10CL025 | 144-pin EQFP | -40°C to 125°C | -7 |
| 10CL025YU256A7G | 10CL025 | 256-pin UBGA | -40°C to 125°C | -7 |
| 10CL025YU484A7G | 10CL025 | 484-pin UBGA | -40°C to 125°C | -7 |
| 10CL040YU484A7G | 10CL040 | 484-pin UBGA | -40°C to 125°C | -7 |
| 10CL055YU484A7G | 10CL055 | 484-pin UBGA | -40°C to 125°C | -7 |
| 10CL080YU484A7G | 10CL080 | 484-pin UBGA | -40°C to 125°C | -7 |

Intel Corporation. All rights reserved. Intel, the Intel logo, Altera, Arria, Cyclone, Enpirion, MAX, Nios, Quartus and Stratix words and logos are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Intel warrants performance of its FPGA and semiconductor products to current specifications in accordance with Intel's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Intel assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Intel. Intel customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services.

*Other names and brands may be claimed as the property of others.

ISO
9001:2008
Registered




2.1.2 Package Options and Maximum User I/Os

Table 3. Package Options and Maximum User I/Os in Intel Cyclone 10 LP Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | | |
|-------------------------|-------------------|-----------------|--------------|-----------|-----------|-----------|-----------|-----------|-----------|---|
| | | | 10CL006 | 10CL010 | 10CL016 | 10CL025 | 10CL040 | 10CL055 | 10CL080 | |
| | | | (6K LEs) | (10K LEs) | (16K LEs) | (25K LEs) | (40K LEs) | (55K LEs) | (80K LEs) | |
| GPIO / LVDS | | | | | | | | | | |
| MBGA-164 | 0.5 | 8 × 8 | — | 71 / 22 | 71 / 22 | — | — | — | — | — |
| UBGA-256 | 0.8 | 14 × 14 | 176 / 65 | 176 / 65 | 162 / 53 | 150 / 52 | — | — | — | — |
| UBGA-484 | 0.8 | 19 × 19 | — | — | — | 325 / 124 | 325 / 124 | 321 / 132 | 289 / 110 | — |
| EQFP-144 | 0.5 | 22 × 22 | 88 / 22 | 88 / 22 | 78 / 19 | 76 / 18 | — | — | — | — |

2.1.3 Device Ordering Codes

Figure 1. Automotive-Grade Ordering Information for Intel Cyclone 10 LP Devices



2.2 Intel Arria 10 Devices

2.2.1 Supported Automotive-Grade Devices

Table 4. Automotive-Grade in Intel Arria 10 Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Ambient Temperature Range | Speed Grade |
|----------------------|---------|--------------|---------------------------|-------------|
| 10AX016C4U19A3SG | 10AX016 | 484-pin UBGA | -40°C to 125°C | -3 |
| 10AX022C4U19A3SG | 10AX022 | 484-pin UBGA | -40°C to 125°C | -3 |
| <i>continued...</i> | | | | |



| Device Ordering Code | Device | Package | Ambient Temperature Range | Speed Grade |
|----------------------|---------|---------------|---------------------------|-------------|
| 10AX016E4F29A3SG | 10AX016 | 780-pin FBGA | -40°C to 125°C | -3 |
| 10AX022E4F29A3SG | 10AX022 | 780-pin FBGA | -40°C to 125°C | -3 |
| 10AX027E4F29A3SG | 10AX027 | 780-pin FBGA | -40°C to 125°C | -3 |
| 10AX032E4F29A3SG | 10AX032 | 780-pin FBGA | -40°C to 125°C | -3 |
| 10AX048E4F29A3SG | 10AX048 | 780-pin FBGA | -40°C to 125°C | -3 |
| 10AX027H4F34A3SG | 10AX027 | 1152-pin FBGA | -40°C to 125°C | -3 |
| 10AX032H4F34A3SG | 10AX032 | 1152-pin FBGA | -40°C to 125°C | -3 |
| 10AX048H4F34A3SG | 10AX048 | 1152-pin FBGA | -40°C to 125°C | -3 |
| 10AX057H4F34A3SG | 10AX057 | 1152-pin FBGA | -40°C to 125°C | -3 |
| 10AX066H4F34A3SG | 10AX066 | 1152-pin FBGA | -40°C to 125°C | -3 |

2.2.2 Package Options and Maximum User I/Os


Table 5. Package Options and Maximum User I/Os in Intel Arria 10 GX Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | | |
|---------------------------|-------------------|-----------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | | | 10AX016 | 10AX022 | 10AX027 | 10AX032 | 10AX048 | 10AX057 | 10AX066 | |
| | | | (160K LEs) | (220K LEs) | (270K LEs) | (320K LEs) | (480K LEs) | (570K LEs) | (660K LEs) | |
| 3 V I/O / LVDS I/O / XCVR | | | | | | | | | | |
| UBGA-484 | 0.8 | 19 × 19 | 48 / 192 / 6 | 48 / 192 / 6 | — | — | — | — | — | — |
| FBGA-780 | 1 | 29 × 29 | 48 / 240 / 12 | 48 / 240 / 12 | 48 / 312 / 12 | 48 / 312 / 12 | 48 / 312 / 12 | — | — | — |
| FBGA-1152 | 1 | 35 × 35 | — | — | 48 / 336 / 24 | 48 / 336 / 24 | 48 / 444 / 24 | 48 / 444 / 24 | 48 / 444 / 24 | 48 / 444 / 24 |



2.2.3 Device Ordering Codes

Figure 2. Automotive-Grade Ordering Information for Intel Arria 10 GX Devices



2.3 Enpirion Devices

2.3.1 Supported Automotive-Grade Devices

Table 6. Automotive-Grade in Enpirion Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Ambient Temperature Range |
|----------------------|-----------|------------|---------------------------|
| EP5358HUA | EP5358HUA | 16-pin QFN | -40°C to 105°C |
| EP5358LUA | EP5358LUA | 16-pin QFN | -40°C to 105°C |
| EN6310QA | EN6310QA | 30-pin QFN | -40°C to 105°C |
| EP53A8HQA | EP53A8HQA | 16-pin QFN | -40°C to 105°C |
| EP53A8LQA | EP53A8LQA | 16-pin QFN | -40°C to 105°C |
| EN6337QA | EN6337QA | 38-pin QFN | -40°C to 105°C |
| EN6347QA | EN6347QA | 38-pin QFN | -40°C to 105°C |
| EN6360QA | EN6360QA | 68-pin QFN | -40°C to 105°C |
| EN63A0QA | EN63A0QA | 76-pin QFN | -40°C to 105°C |



2.4 Intel MAX 10 Devices

2.4.1 Supported Automotive-Grade Devices

Table 7. Automotive-Grade in Intel MAX 10 Devices

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|-------------------------------|---------|--------------|----------------------------|-------------|
| 10M02SCE144A7G | 10M02SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M02SCM153A7G ⁽³⁾ | 10M02SC | 153-pin MBGA | -40°C to 125°C | -7 |
| 10M02SCU169A7G | 10M02SC | 169-pin UBGA | -40°C to 125°C | -7 |
| 10M02DCU324A7G | 10M02DC | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M02DCV36A7G ⁽³⁾ | 10M02DC | 36-pin WLCSP | -40°C to 125°C | -7 |
| 10M04SCE144A7G | 10M04SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M04SCM153A7G ⁽³⁾ | 10M04SC | 153-pin MBGA | -40°C to 125°C | -7 |
| 10M04SCU169A7G | 10M04SC | 169-pin UBGA | -40°C to 125°C | -7 |
| 10M04DCF256A7G | 10M04DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M04DAF256A7G ⁽³⁾ | 10M04DA | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M04DCU324A7G | 10M04DC | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M04DAU324A7G ⁽³⁾ | 10M04DA | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M08DCV81A7G ⁽³⁾ | 10M08DC | 81-pin WLCSP | -40°C to 125°C | -7 |
| 10M08DFV81A7G ⁽³⁾ | 10M08DF | 81-pin WLCSP | -40°C to 125°C | -7 |
| 10M08SAU169A7G ⁽³⁾ | 10M08SA | 169-pin UBGA | -40°C to 125°C | -7 |
| 10M08SCE144A7G | 10M08SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M08SCM153A7G ⁽³⁾ | 10M08SC | 153-pin MBGA | -40°C to 125°C | -7 |
| 10M08SCU169A7G | 10M08SC | 169-pin UBGA | -40°C to 125°C | -7 |
| 10M08DCF256A7G | 10M08DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M08DAF256A7G ⁽³⁾ | 10M08DA | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M08DCU324A7G | 10M08DC | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M08DAU324A7G ⁽³⁾ | 10M08DA | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M08DCF484A7G ⁽³⁾ | 10M08DC | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M08DAF484A7G ⁽³⁾ | 10M08DA | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M16SCE144A7G | 10M16SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M16SCU169A7G | 10M16SC | 169-pin UBGA | -40°C to 125°C | -7 |
| 10M16DCF256A7G | 10M16DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M16DAF256A7G ⁽³⁾ | 10M16DA | 256-pin FBGA | -40°C to 125°C | -7 |

continued...

⁽³⁾ This automotive-grade ordering code might be available upon request. Faster speed grade devices might be available depending on the application and device feature needed. Consult your Intel sales representative to submit your request.



| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|-------------------------------|---------|--------------|----------------------------|-------------|
| 10M16DCU324A7G | 10M16DC | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M16DAU324A7G ⁽³⁾ | 10M16DA | 324-pin UBGA | -40°C to 125°C | -7 |
| 10M16DCF484A7G | 10M16DC | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M16DAF484A7G ⁽³⁾ | 10M16DA | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M25SCE144A7G | 10M25SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M25DCF256A7G | 10M25DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M25DAF256A7G ⁽³⁾ | 10M25DA | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M25DCF484A7G ⁽³⁾ | 10M25DC | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M25DAF484A7G ⁽³⁾ | 10M25DA | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M25DCF672A7G ⁽³⁾ | 10M25DC | 672-pin FBGA | -40°C to 125°C | -7 |
| 10M25DAF672A7G ⁽³⁾ | 10M25DA | 672-pin FBGA | -40°C to 125°C | -7 |
| 10M40SCE144A7G | 10M40SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M40DCF256A7G | 10M40DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M40DAF256A7G ⁽³⁾ | 10M40DA | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M40DCF484A7G ⁽³⁾ | 10M40DC | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M40DAF484A7G ⁽³⁾ | 10M40DA | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M40DCF672A7G ⁽³⁾ | 10M40DC | 672-pin FBGA | -40°C to 125°C | -7 |
| 10M40DAF672A7G ⁽³⁾ | 10M40DA | 672-pin FBGA | -40°C to 125°C | -7 |
| 10M50SCE144A7G | 10M50SC | 144-pin EQFP | -40°C to 125°C | -7 |
| 10M50DCF256A7G | 10M50DC | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M50DAF256A7G ⁽³⁾ | 10M50DF | 256-pin FBGA | -40°C to 125°C | -7 |
| 10M50DCF484A7G ⁽³⁾ | 10M50DC | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M50DAF484A7G ⁽³⁾ | 10M50DA | 484-pin FBGA | -40°C to 125°C | -7 |
| 10M50DCF672A7G ⁽³⁾ | 10M50DC | 672-pin FBGA | -40°C to 125°C | -7 |
| 10M50DAF672A7G ⁽³⁾ | 10M50DA | 672-pin FBGA | -40°C to 125°C | -7 |

2.4.2 Package Options and Maximum User I/Os

Table 8. Package Options and Maximum User I/Os in Intel MAX 10 Single Power Supply Devices

| Device | Package | | | |
|---------------------|------------|----------------------|----------------------|----------------------|
| | Type | M153 153-pin MBGA | U169 169-pin UBGA | E144 144-pin EQFP |
| | Size | 8 mm × 8 mm | 11 mm × 11 mm | 22 mm × 22 mm |
| | Ball Pitch | 0.5 mm | 0.8 mm | 0.5 mm |
| 10M02S | | 112 | 130 | 101 |
| 10M04S | | 112 | 130 | 101 |
| <i>continued...</i> | | | | |



| Device | Package | | | |
|--------|------------|----------------------|----------------------|----------------------|
| | Type | M153 153-pin MBGA | U169 169-pin UBGA | E144 144-pin EQFP |
| | Size | 8 mm × 8 mm | 11 mm × 11 mm | 22 mm × 22 mm |
| | Ball Pitch | 0.5 mm | 0.8 mm | 0.5 mm |
| 10M08S | | 112 | 130 | 101 |
| 10M16S | | — | 130 | 101 |
| 10M25S | | — | — | 101 |
| 10M40S | | — | — | 101 |
| 10M50S | | — | — | 101 |


Table 9. Package Options and Maximum User I/Os in Intel MAX 10 Dual Power Supply Devices

| Device | Package | | | | | | |
|--------|------------|------------------------|------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| | Type | V36 36-pin WLCSP | V81 81-pin WLCSP | U324 324-pin UBGA | F256 256-pin FBGA | F484 484-pin FBGA | F672 672-pin FBGA |
| | Size | 3 mm × 3 mm | 4 mm × 4 mm | 15 mm × 15 mm | 17 mm × 17 mm | 23 mm × 23 mm | 27 mm × 27 mm |
| | Ball Pitch | 0.4 mm | 0.4 mm | 0.8 mm | 1.0 mm | 1.0 mm | 1.0 mm |
| 10M02D | | 27 | — | 160 | — | — | — |
| 10M04D | | — | — | 246 | 178 | — | — |
| 10M08D | | — | 56 | 246 | 178 | 250 | — |
| 10M16D | | — | — | 246 | 178 | 320 | — |
| 10M25D | | — | — | — | 178 | 360 | — |
| 10M40D | | — | — | — | 178 | 360 | 500 |
| 10M50D | | — | — | — | 178 | 360 | 500 |



2.4.3 Device Ordering Codes

Figure 3. Automotive-Grade Ordering Information for Intel MAX 10 Devices



2.5 Cyclone V SoC Devices

2.5.1 Supported Automotive-Grade Devices

Table 10. Automotive-Grade in Cyclone V SoC Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| 5CSEBA2U19A7N | 5CSEBA2 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CSEBA2U23A7N | 5CSEBA2 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA2U23A7N | 5CSEMA2 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEBA4U19A7N | 5CSEBA4 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CSEBA4U23A7N | 5CSEBA4 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA4U23A7N | 5CSEMA4 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEBA5U19A7N | 5CSEBA5 | 484-pin UBGA | -40°C to 125°C | -7 |

continued...



| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| 5CSEBA5U23A7N | 5CSEBA5 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA5U23A7N | 5CSEMA5 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA5F31A7N | 5CSEMA5 | 896-pin FBGA | -40°C to 125°C | -7 |
| 5CSEBA6U19A7N | 5CSEBA6 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CSEBA6U23A7N | 5CSEBA6 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA6U23A7N | 5CSEMA6 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSEMA6F31A7N | 5CSEMA6 | 896-pin FBGA | -40°C to 125°C | -7 |
| 5CSXFC2C6U23A7N | 5CSXFC2 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSXFC4C6U23A7N | 5CSXFC4 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSXFC5C6U23A7N | 5CSXFC5 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSXFC6C6U23A7N | 5CSXFC6 | 672-pin UBGA | -40°C to 125°C | -7 |
| 5CSXFC6D6F31A7N | 5CSXFC6 | 896-pin FBGA | -40°C to 125°C | -7 |

2.5.2 Package Options and Maximum User I/Os

Table 11. Package Options and Maximum User I/Os in Cyclone V SE Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | |
|----------------------------|----------------------|--------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| | | | 5CSEA2 | 5CSEA4 | 5CSEA5 | 5CSEA6 |
| | | | (25K LEs) | (40K LEs) | (85K LEs) | (110K LEs) |
| | | | FPGA I/Os / HPS I/Os | | | |
| UBGA-484 | 0.8 | 19 x 19 | 66 / 151 ⁽⁴⁾ |
| UBGA-672 | 0.8 | 23 x 23 | 145 / 181 ⁽⁴⁾ |
| FBGA-896 | 1 | 31 x 31 | — | — | 288 / 181 ⁽⁴⁾ | 288 / 181 ⁽⁴⁾ |

Table 12. Package Options and Maximum User I/Os in Cyclone V SX Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | |
|----------------------------|----------------------|--------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| | | | 5CSXC2 | 5CSXC4 | 5CSXC5 | 5CSXC6 |
| | | | (25K LEs) | (40K LEs) | (85K LEs) | (110K LEs) |
| | | | FPGA I/Os / HPS I/Os / XCVRs | | | |
| UBGA-672 | 0.8 | 23 x 23 | 145 / 181 / 6 ⁽⁴⁾ |
| FBGA-896 | 1 | 31 x 31 | — | — | 288 / 181 / 9 ⁽⁵⁾ | 288 / 181 / 9 ⁽⁴⁾ |


⁽⁴⁾ Package options available with automotive-grade variants.

⁽⁵⁾ This automotive-grade ordering code might be available upon request. Faster speed grade devices might be available depending on the application and device feature needed. Consult your Intel sales representative to submit your request.



2.5.3 Device Ordering Codes


Figure 4. Automotive-Grade Ordering Information for Cyclone V SE Devices



Note:

* All Cyclone V SoC devices include one hard memory controller dedicated to the processor and which can be shared by the FPGA.

Figure 5. Automotive-Grade Ordering Information for Cyclone V SX Devices



Note:

* All Cyclone V SoC devices include one hard memory controller dedicated to the processor and which can be shared by the FPGA.



2.6 Cyclone V Devices

2.6.1 Supported Automotive-Grade Devices

Table 13. Automotive-Grade in Cyclone V Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| 5CEBA2F17A7N | 5CEBA2 | 256-pin FBGA | -40°C to 125°C | -7 |
| 5CEFA2U19A7N | 5CEFA2 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CEBA4F17A7N | 5CEBA4 | 256-pin FBGA | -40°C to 125°C | -7 |
| 5CEFA4U19A7N | 5CEFA4 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CEFA5U19A7N | 5CEFA5 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CEFA7U19A7N | 5CEFA7 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CEFA9U19A7N | 5CEFA9 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC3B6U15A7N | 5CGXFC3 | 324-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC3B6U19A7N | 5CGXFC3 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC4C6U19A7N | 5CGXFC4 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC5C6U19A7N | 5CGXFC5 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC5C6F23A7N | 5CGXFC5 | 484-pin FBGA | -40°C to 125°C | -7 |
| 5CGXFC7C6U19A7N | 5CGXFC7 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGXFC9A6U19A7N | 5CGXFC9 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGTFD5C5U19A7N | 5CGTFD5 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGTFD7C5U19A7N | 5CGTFD7 | 484-pin UBGA | -40°C to 125°C | -7 |
| 5CGTFD9A5U19A7N | 5CGTFD9 | 484-pin UBGA | -40°C to 125°C | -7 |

2.6.2 Package Options and Maximum User I/Os

Table 14. Package Options and Maximum User I/Os in Cyclone V E Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | |
|-------------------------|-------------------|-----------------|--------------------|--------------------|-----------|--------------|------------|
| | | | 5CEA2 | 5CEA4 | 5CEA5 | 5CEA7 | 5CEA9 |
| | | | (25K LEs) | (49K LEs) | (77K LEs) | (149.5K LEs) | (301K LEs) |
| I/Os | | | | | | | |
| FBGA-256 | 1 | 17 x 17 | 128 ⁽⁶⁾ | 128 ⁽⁶⁾ | — | — | — |
| UBGA-324 | 0.8 | 15 x 15 | 176 ⁽⁷⁾ | 176 ⁽⁷⁾ | — | — | — |
| <i>continued...</i> | | | | | | | |

⁽⁶⁾ Package options available with automotive-grade variants.



| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | |
|----------------------------|----------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| | | | 5CEA2 | 5CEA4 | 5CEA5 | 5CEA7 | 5CEA9 |
| | | | (25K LEs) | (49K LEs) | (77K LEs) | (149.5K LEs) | (301K LEs) |
| I/Os | | | | | | | |
| UBGA-484 | 0.8 | 19 x 19 | 224 ⁽⁶⁾ | 224 ⁽⁶⁾ | 224 ⁽⁶⁾ | 240 ⁽⁶⁾ | — |
| FBGA-484 | 1 | 23 x 23 | 224 ⁽⁷⁾ | 224 ⁽⁷⁾ | 240 ⁽⁷⁾ | 240 ⁽⁷⁾ | 224 ⁽⁷⁾ |
| FBGA-672 | 1 | 27 x 27 | — | — | — | 336 ⁽⁷⁾ | 336 ⁽⁷⁾ |
| FBGA-896 | 1 | 31 x 31 | — | — | — | 480 ⁽⁷⁾ | 480 ⁽⁷⁾ |

Table 15. Package Options and Maximum User I/Os in Cyclone V GX Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | |
|----------------------------|----------------------|--------------------|------------------------|------------------------|------------------------|------------------------|-------------------------|
| | | | 5CGXC3 | 5CGXC4 | 5CGXC5 | 5CGXC7 | 5CGXC9 |
| | | | (36K LEs) | (50K LEs) | (77K LEs) | (149.5K LEs) | (301K LEs) |
| I/Os / XCVRs | | | | | | | |
| UBGA-324 | 0.8 | 15 x 15 | 144 / 3 ⁽⁶⁾ | — | — | — | — |
| UBGA-484 | 0.8 | 19 x 19 | 208 / 3 ⁽⁶⁾ | 224 / 6 ⁽⁶⁾ | 224 / 6 ⁽⁶⁾ | 240 / 6 ⁽⁶⁾ | 240 / 5 ⁽⁶⁾ |
| FBGA-484 | 1 | 23 x 23 | 208 / 3 ⁽⁷⁾ | 240 / 6 ⁽⁷⁾ | 240 / 6 ⁽⁶⁾ | 240 / 6 ⁽⁷⁾ | 224 / 6 ⁽⁷⁾ |
| FBGA-672 | 1 | 27 x 27 | — | 336 / 6 ⁽⁷⁾ | 336 / 6 ⁽⁷⁾ | 336 / 9 ⁽⁷⁾ | 336 / 9 ⁽⁷⁾ |
| FBGA-896 | 1 | 31 x 31 | — | — | — | 480 / 9 ⁽⁷⁾ | 480 / 12 ⁽⁷⁾ |
| FBGA-1152 | 1 | 35 x 35 | — | — | — | — | 560 / 12 ⁽⁷⁾ |

Table 16. Package Options and Maximum User I/Os in Cyclone V GT Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | |
|----------------------------|----------------------|--------------------|------------------------|------------------------|-------------------------|
| | | | 5CGTD5 | 5CGTD7 | 5CGTD9 |
| | | | (77K LEs) | (149.5K LEs) | (301K LEs) |
| I/Os / XCVRs | | | | | |
| UBGA-484 | 0.8 | 19 x 19 | 224 / 6 ⁽⁶⁾ | 240 / 6 ⁽⁶⁾ | 240 / 5 ⁽⁶⁾ |
| FBGA-484 | 1 | 23 x 23 | 240 / 6 ⁽⁷⁾ | 240 / 6 ⁽⁷⁾ | 224 / 6 ⁽⁷⁾ |
| FBGA-672 | 1 | 27 x 27 | 336 / 6 ⁽⁷⁾ | 336 / 9 ⁽⁷⁾ | 336 / 9 ⁽⁷⁾ |
| FBGA-896 | 1 | 31 x 31 | — | 480 / 9 ⁽⁷⁾ | 480 / 12 ⁽⁷⁾ |
| FBGA-1152 | 1 | 35 x 35 | — | — | 560 / 12 ⁽⁷⁾ |

⁽⁷⁾ These package options are not currently available in automotive-grade but might become available upon request. Consult your Intel sales representative to submit your request.



2.6.3 Device Ordering Codes

Figure 6. Automotive-Grade Ordering Information for Cyclone V E Devices




Figure 7. Automotive-Grade Ordering Information for Cyclone V GX Devices







Figure 8. Automotive-Grade Ordering Information for Cyclone V GT Devices



2.7 Cyclone IV Devices

2.7.1 Supported Automotive-Grade Devices

Table 17. Automotive-Grade in Cyclone IV Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| EP4CE6F17A7N | EP4CE6 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP4CE6E22A7N | EP4CE6 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP4CE10F17A7N | EP4CE10 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP4CE10E22A7N | EP4CE10 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP4CE15F17A7N | EP4CE15 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP4CE15F23A7N | EP4CE15 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP4CE15U14A7N | EP4CE15 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP4CE22F17A7N | EP4CE22 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP4CE22E22A7N | EP4CE22 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP4CE22U14A7N | EP4CE22 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP4CE30F19A7N | EP4CE30 | 324-pin FBGA | -40°C to 125°C | -7 |
| EP4CE30F23A7N | EP4CE30 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP4CE40F19A7N | EP4CE40 | 324-pin FBGA | -40°C to 125°C | -7 |
| EP4CE40F23A7N | EP4CE40 | 484-pin FBGA | -40°C to 125°C | -7 |

continued...



| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|----------|--------------|----------------------------|-------------|
| EP4CE40U19A7N | EP4CE40 | 484-pin UBGA | -40°C to 125°C | -7 |
| EP4CE55F23A7N | EP4CE55 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP4CGX15BF14A7N | EP4CGX15 | 169-pin FBGA | -40°C to 125°C | -7 |

2.7.2 Package Options and Maximum User I/Os

Table 18. Package Options and Maximum User I/Os in Cyclone IV E Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | | | |
|----------------------------|----------------------|--------------------|-------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|---------------------------------|
| | | | EP4CE6 (6.3K LEs) | EP4CE1 0 (10.3K LEs) | EP4CE1 5 (15.4K LEs) | EP4CE2 2 (22.3K LEs) | EP4CE3 0 (28.8K LEs) | EP4CE4 0 (39.6K LEs) | EP4CE5 5 (55.9K LEs) | EP4CE7 5 (75.4K LEs) | EP4CE1 15 (114.5K LEs) |
| | | | I/Os | | | | | | | | |
| EQFP-144 | 0.5 | 22 x 22 | 91 ⁽⁸⁾ | 91 ⁽⁸⁾ | 81 ⁽⁹⁾ | 79 ⁽⁸⁾ | — | — | — | — | — |
| MBGA-164 | 0.5 | 8 x 8 | — | — | 89 ⁽⁹⁾ | — | — | — | — | — | — |
| UBGA-256 | 0.8 | 14 x 14 | 179 ⁽⁹⁾ | 179 ⁽⁹⁾ | 165 ⁽⁹⁾ | 153 ⁽⁹⁾ | — | — | — | — | — |
| FBGA-256 | 1 | 17 x 17 | 179 ⁽⁸⁾ | 179 ⁽⁸⁾ | 165 ⁽⁸⁾ | 153 ⁽⁸⁾ | — | — | — | — | — |
| UBGA-484 | 0.8 | 19 x 19 | — | — | — | — | — | 328 ⁽⁹⁾ | 324 ⁽⁹⁾ | 292 ⁽⁹⁾ | — |
| FBGA-324 | 1 | 19 x 19 | — | — | — | — | 193 ⁽⁸⁾ | 193 ⁽⁸⁾ | — | — | — |
| FBGA-484 | 1 | 23 x 23 | — | — | 343 ⁽⁸⁾ | — | 328 ⁽⁸⁾ | 328 ⁽⁸⁾ | 324 ⁽⁹⁾ | 292 ⁽⁹⁾ | 280 ⁽⁹⁾ |
| FBGA-780 | 1 | 29 x 29 | — | — | — | — | 532 ⁽⁹⁾ | 532 ⁽⁹⁾ | 374 ⁽⁹⁾ | 426 ⁽⁹⁾ | 528 ⁽⁹⁾ |

Table 19. Package Options and Maximum User I/Os in Cyclone IV GX Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | |
|----------------------------|----------------------|--------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|----------------------------------|----------------------------------|
| | | | EP4CGX1 5 (14.4K LEs) | EP4CGX2 2 (21.3K LEs) | EP4CGX3 0 (29.4K LEs) | EP4CGX5 0 (49.9K LEs) | EP4CGX7 5 (73.9K LEs) | EP4CGX1 10 (109.4K LEs) | EP4CGX1 50 (149.8K LEs) |
| | | | I/Os | | | | | | |
| QFN-148 | 0.5 | 11 x 11 | 72 / 2 ⁽⁹⁾ | — | — | — | — | — | — |
| FBGA-169 | 1 | 14 x 14 | 72 / 2 ⁽⁸⁾ | 72 / 2 ⁽⁹⁾ | 72 / 2 ⁽⁹⁾ | — | — | — | — |

continued...

⁽⁸⁾ Package options available with automotive-grade variants.

⁽⁹⁾ These package options are not currently available in automotive-grade but might become available upon request. Consult your Intel sales representative to submit your request.



| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | |
|-------------------------|-------------------|-----------------|----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| | | | EP4CGX15 (14.4K LEs) | EP4CGX22 (21.3K LEs) | EP4CGX30 (29.4K LEs) | EP4CGX50 (49.9K LEs) | EP4CGX75 (73.9K LEs) | EP4CGX10 (109.4K LEs) | EP4CGX150 (149.8K LEs) |
| | | | I/Os | | | | | | |
| FBGA-324 | 1 | 19 x 19 | — | 150 / 4 ⁽⁹⁾ | 150 / 4 ⁽⁹⁾ | — | — | — | — |
| FBGA-484 | 1 | 23 x 23 | — | — | 290 / 4 ⁽⁹⁾ | 290 / 4 ⁽⁹⁾ | 290 / 4 ⁽⁹⁾ | 270 / 4 ⁽⁹⁾ | 270 / 4 ⁽⁹⁾ |
| FBGA-672 | 1 | 27 x 27 | — | — | — | 310 / 8 ⁽⁹⁾ | 310 / 8 ⁽⁹⁾ | 393 / 8 ⁽⁹⁾ | 393 / 8 ⁽⁹⁾ |
| FBGA-896 | 1 | 31 x 31 | — | — | — | — | — | 475 / 8 ⁽⁹⁾ | 475 / 8 ⁽⁹⁾ |

2.7.3 Device Ordering Codes

Figure 9. Automotive-Grade Ordering Information for Cyclone IV E Devices





Figure 10. Automotive-Grade Ordering Information for Cyclone IV GX Devices





2.8 MAX V Devices

2.8.1 Supported Automotive-Grade Devices

Table 20. Automotive-Grade in MAX V Devices

Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| 5M40ZE64A5N | 5M40Z | 64-pin EQFP | -40°C to 125°C | -5 |
| 5M80ZE64A5N | 5M80Z | 64-pin EQFP | -40°C to 125°C | -5 |
| 5M80ZT100A5N | 5M80Z | 100-pin TQFP | -40°C to 125°C | -5 |
| 5M160ZE64A5N | 5M160Z | 64-pin EQFP | -40°C to 125°C | -5 |
| 5M160ZT100A5N | 5M160Z | 100-pin TQFP | -40°C to 125°C | -5 |
| 5M240ZT100A5N | 5M240Z | 100-pin TQFP | -40°C to 125°C | -5 |
| 5M570ZT100A5N | 5M570Z | 100-pin TQFP | -40°C to 125°C | -5 |
| 5M1270ZF256A5N | 5M1270Z | 256-pin FBGA | -40°C to 125°C | -5 |
| 5M1270ZT144A5N | 5M1270Z | 144-pin TQFP | -40°C to 125°C | -5 |

2.8.2 Package Options and Maximum User I/Os

Table 21. Package Options and Maximum User I/Os in MAX V Devices

| Package Type/ Pin Count | Ball Spacing (mm) | Dimensions (mm) | Product Line | | | | | | |
|-------------------------|-------------------|-----------------|--------------------|--------------------|--------------------|---------------------|---------------------|---------------------|---------------------|
| | | | 5M40Z (40K LEs) | 5M80Z (80K LEs) | 5M160Z (160K LEs) | 5M240Z (240K LEs) | 5M570Z (570K LEs) | 5M1270Z (1270K LEs) | 5M2210Z (2210K LEs) |
| | | | I/Os | | | | | | |
| MBGA-64 | 0.5 | 4.5 x 4.5 | 30 ⁽¹⁰⁾ | 30 ⁽¹⁰⁾ | — | — | — | — | — |
| EQFP-64 | 0.5 | 7 x 7 | 54 ⁽¹¹⁾ | 54 ⁽¹¹⁾ | 54 ⁽¹¹⁾ | — | — | — | — |
| MBGA-68 | 0.5 | 5 x 5 | — | 52 ⁽¹⁰⁾ | 52 ⁽¹⁰⁾ | 52 ⁽¹⁰⁾ | — | — | — |
| QFP-100 | 0.5 | 14 x 14 | — | 79 ⁽¹¹⁾ | 79 ⁽¹¹⁾ | 79 ⁽¹¹⁾ | 74 ⁽¹¹⁾ | — | — |
| MBGA-100 | 0.5 | 6 x 6 | — | — | 79 ⁽¹⁰⁾ | 79 ⁽¹⁰⁾ | 74 ⁽¹⁰⁾ | — | — |
| DFP-144 | 0.5 | 20 x 20 | — | — | — | 114 ⁽¹⁰⁾ | 114 ⁽¹⁰⁾ | 114 ⁽¹¹⁾ | — |
| FBGA-256 | 1 | 17 x 17 | — | — | — | — | 159 ⁽¹⁰⁾ | 211 ⁽¹¹⁾ | 203 ⁽¹⁰⁾ |
| FBGA-324 | 1 | 19 x 19 | — | — | — | — | — | 271 ⁽¹⁰⁾ | 271 ⁽¹⁰⁾ |


⁽¹⁰⁾ These package options are not currently available in automotive-grade but might become available upon request. Consult your Intel sales representative to submit your request.

⁽¹¹⁾ Package options available with automotive-grade variants.



2.8.3 Device Ordering Codes

Figure 11. Automotive-Grade Ordering Information for MAX V Devices



2.9 MAX II Devices

2.9.1 Supported Automotive-Grade Devices

Table 22. Automotive-Grade in MAX II Devices


Other automotive-grade product line/package combinations or ordering codes might be available upon request. Consult your Intel sales representative to submit your request.

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|---------|--------------|----------------------------|-------------|
| EPM240T100A5N | EPM240 | 100-pin TQFP | -40°C to 125°C | -5 |
| EPM570F100A5N | EPM570 | 100-pin FBGA | -40°C to 125°C | -5 |
| EPM570T100A5N | EPM570 | 100-pin TQFP | -40°C to 125°C | -5 |
| EPM570T144A5N | EPM570 | 144-pin TQFP | -40°C to 125°C | -5 |
| EPM1270T144A5N | EPM1270 | 144-pin TQFP | -40°C to 125°C | -5 |
| EPM1270F256A5N | EPM1270 | 256-pin FBGA | -40°C to 125°C | -5 |
| EPM2210F256A5N | EPM2210 | 256-pin FBGA | -40°C to 125°C | -5 |
| EPM2210F324A5N | EPM2210 | 324-pin FBGA | -40°C to 125°C | -5 |



2.9.2 Device Ordering Codes

Figure 12. Automotive-Grade Ordering Information for MAX II Devices



2.10 Cyclone III Devices (Legacy Support)

2.10.1 Supported Automotive-Grade Devices

Table 23. Automotive-Grade in Cyclone III Devices

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|--------|--------------|----------------------------|-------------|
| EP3C5E144A7N | EP3C5 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP3C5F256A7N | EP3C5 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP3C5U256A7N | EP3C5 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP3C10E144A7N | EP3C10 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP3C10F256A7N | EP3C10 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP3C10U256A7N | EP3C10 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP3C16E144A7N | EP3C16 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP3C16F256A7N | EP3C16 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP3C16U256A7N | EP3C16 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP3C16F484A7N | EP3C16 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP3C16U484A7N | EP3C16 | 484-pin UBGA | -40°C to 125°C | -7 |
| EP3C25E144A7N | EP3C25 | 144-pin EQFP | -40°C to 125°C | -7 |
| EP3C25F256A7N | EP3C25 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP3C25U256A7N | EP3C25 | 256-pin UBGA | -40°C to 125°C | -7 |
| EP3C25F324A7N | EP3C25 | 324-pin FBGA | -40°C to 125°C | -7 |


continued...



| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|--------|--------------|----------------------------|-------------|
| EP3C40F324A7N | EP3C40 | 324-pin FBGA | -40°C to 125°C | -7 |
| EP3C40F484A7N | EP3C40 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP3C40U484A7N | EP3C40 | 484-pin UBGA | -40°C to 125°C | -7 |

2.10.2 Device Ordering Codes

Figure 13. Automotive-Grade Ordering Information for Cyclone III Devices



2.11 Cyclone II Devices (Legacy Support)


2.11.1 Supported Automotive-Grade Devices

Table 24. Automotive-Grade in Cyclone II Devices

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|--------|--------------|----------------------------|-------------|
| EP2C5AT144A7N | EP2C5 | 144-pin TQFP | -40°C to 125°C | -7 |
| EP2C5AF256A7N | EP2C5 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP2C8AF256A7N | EP2C8 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP2C15AF256A7N | EP2C15 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP2C15AF484A7N | EP2C15 | 484-pin FBGA | -40°C to 125°C | -7 |
| EP2C20AF256A7N | EP2C20 | 256-pin FBGA | -40°C to 125°C | -7 |
| EP2C20AF484A7N | EP2C20 | 484-pin FBGA | -40°C to 125°C | -7 |

2.11.2 Device Ordering Codes

Figure 14. Automotive-Grade Ordering Information for Cyclone II Devices



2.12 Cyclone Devices (Legacy Support)


2.12.1 Supported Automotive-Grade Devices

Table 25. Automotive-Grade in Cyclone Devices

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|--------|--------------|--|-------------|
| EP1C3T100A8N | EP1C3 | 100-pin TQFP | -40°C to 125°C | -8 |
| EP1C3T144A8N | EP1C3 | 144-pin TQFP | -40°C to 125°C | -8 |

2.12.2 Device Ordering Codes

Figure 15. Automotive-Grade Ordering Information for Cyclone Devices





2.13 MAX 7000A Devices (Legacy Support)


2.13.1 Supported Automotive-Grade Devices

Table 26. Automotive-Grade in MAX 7000A Devices

| Device Ordering Code | Device | Package | Junction Temperature Range | Speed Grade |
|----------------------|-----------|--------------|----------------------------|-------------|
| EPM7032AETA44-10N | EPM7032AE | 44-pin TQFP | -40°C to 130°C | -10 |
| EPM7064AETA44-10N | EPM7064AE | 44-pin TQFP | -40°C to 130°C | -10 |
| EPM7064AETA100-10N | EPM7064AE | 100-pin TQFP | -40°C to 130°C | -10 |
| EPM7128AETA100-10N | EPM7128AE | 100-pin TQFP | -40°C to 130°C | -10 |
| EPM7128AETA144-10N | EPM7128AE | 144-pin TQFP | -40°C to 130°C | -10 |

2.13.2 Device Ordering Codes

Figure 16. Automotive-Grade Ordering Information for MAX 7000A Devices





3 Intel Quartus Prime Software Support

The Intel Quartus Prime design software supports the automotive-grade devices in the automotive temperature range. The Intel Quartus Prime software provides a comprehensive environment for SoC design. It also includes HDL and schematic design entry, compilation and logic synthesis, full simulation and advanced timing analysis, Signal Tap II logic analyzer, and device configuration.

To target an automotive-grade device in your design in the Intel Quartus Prime software, follow these steps:

1. Click **Assignments** ► **Device**. The **Settings** dialog box appears.
2. In the **Family** drop-down list, select your device.
3. Under **Target device**, select **Specific device selected in 'Available devices' list**.
4. In the **Available devices** list, select the appropriate ordering code.

Note: The Intel Quartus Prime software does not show the "N" suffix, which indicates a lead-free device. For example, the 5CGXFC3B6U15A7N device is shown only as 5CGXFC3B6U15A7.

5. Click **OK**.

Legacy support for the following automotive-grade devices in Intel Quartus Prime software requires special approval. Contact the nearest Intel sales representative to submit your request.

- Cyclone III
- Cyclone II
- Cyclone
- MAX 7000AE



4 Power Analysis and Estimation

4.1 Early Power Estimator

The Early Power Estimator (EPE) is a power estimation tool that helps you estimate the power consumption of your design during the system planning phase for proper power supply planning and consideration.

The EPE allows you to enter design information based on architectural features and calculates the power consumed by each architectural feature. Inputs to the EPE are environmental conditions and device resources (such as clock frequency, RAM blocks, and digital signal processing [DSP] blocks) that you expect to use in your design. The EPE then calculates the static and dynamic power, current estimates, and thermal analysis for the design.

You can either enter the design information manually into the spreadsheet or import a power estimator file of a fully or partially completed design from the Intel Quartus Prime software. After importing a file, you can edit some of the input parameters including V_{CCINT} , ambient temperature, airflow, clock frequency, and toggle percentage to suit your system requirements.

The value obtained from the EPE is only an estimation and should not be used as a specification. The accuracy of the EPE results depends on how close your input of the design information into the EPE resembles that of the final design.

For more information about the EPE, and how to generate and import the power estimator file, refer to the respective user guides.

Related Links

- [Early Power Estimator for Intel Arria 10 FPGAs User Guide](#)
Applicable to Intel Arria 10.
- [Early Power Estimator User Guide](#)
Applicable to Cyclone III, Cyclone IV, Cyclone V, Cyclone V SoC devices, Intel Cyclone 10, and Intel Arria 10.
- [Early Power Estimator for Intel CPLDs User Guide](#)
Applicable to MAX II and MAX V devices.
- [Early Power Estimator User Guide For Stratix®, Stratix GX & Cyclone FPGAs](#)
Applicable to Cyclone devices.

4.2 Power Analyzer

The Power Analyzer tool in the Intel Quartus Prime software is a power analysis tool that helps you calculate your design power consumption accurately to ensure thermal and power supply budgets are not violated after your design is complete. The Power Analyzer tool requires your design to be synthesized and fitted to the target device.



Availability of information such as design resources, how the design is placed and routed on the target device, and the I/O standards assigned to each I/O cell allow the Power Analyzer tool to provide accurate power estimation.

The process of using the Power Analyzer tool consists of the following three parts:

- Specifying sources of input data
- Specifying operating conditions
- Running the Power Analyzer tool

The input data consists of the signal activities data (toggle rates and static probabilities) of the compiled design. Signal activity data can be derived from simulation results, user assignment in the Assignment Editor, user-defined default toggle rate, and vectorless estimation.

The operating conditions include device power characteristic, ambient and junction temperature, cooling solution, and board thermal model, all of which can be set in the Intel Quartus Prime software.

The Power Analyzer tool calculates the dynamic, static and I/O thermal power consumption, current consumed from voltage source, a summary of the signal activities used for analysis, and a confidence metric that reflects the overall quality of the data sources for the signal activities.

Related Links

- [Power Analysis chapter, Intel Quartus Prime Standard Edition Handbook Volume 3: Verification](#)
- [Power Analysis chapter, Intel Quartus Prime Pro Edition Handbook Volume 3: Verification](#)



5 DC and Timing Specifications

The automotive-grade devices have the same values for the following specifications as published in the respective device datasheets :

- Absolute maximum ratings
- Recommended operating conditions
- DC electrical characteristics
- Timing specifications over the automotive temperature range

For the maximum power-up current (I_{CCINT}) required to power up an automotive-grade Cyclone device, use the value specified for the corresponding industrial-grade device.

The on-chip series termination (R_S OCT) specifications for the following automotive-grade devices are as follows:

- Automotive-grade Cyclone III, Cyclone IV, Cyclone V, and Cyclone V SoC devices—same as the corresponding industrial-grade devices
- Automotive-grade Cyclone II devices—same as the corresponding extended-temperature devices

The switching characteristics of the automotive-grade Cyclone III, Cyclone IV, Cyclone V, and Cyclone V SoC devices are the same as the devices with -8 speed grade as published in the respective device datasheets.

Related Links

- [Intel Cyclone 10 LP Device Datasheet](#)
- [Intel Arria 10 Device Datasheet](#)
- [Intel MAX 10 FPGA Device Datasheet](#)
- [Cyclone V Device Datasheet](#)
- [Cyclone IV Device Datasheet](#)
- [DC and Switching Characteristics for MAX V Devices](#)
- [DC and Switching Characteristics chapter, MAX II Device Handbook](#)
- [Cyclone III Device Datasheet](#)
- [DC Characteristics and Timing Specifications chapter, Cyclone II Device Handbook](#)
- [DC and Switching Characteristics chapter, Cyclone Device Handbook](#)
- [MAX 7000A Programmable Logic Device Data Sheet](#)



6 Pin-Out Information

For more information about the device pin-outs, refer to the respective device pin-out files.

Related Links

[Pin-Out Files for Intel Devices page](#)



7 Package and Board Layout Information

Intel provides information on package and PCB design guidelines.

Related Links

- [Package and Thermal Resistance page, Intel website](#)
Provides more information about the package-related information and Package Information Datasheet for Intel Devices.
- [AN114: Designing With High-Density BGA Packages for Intel Devices](#)
Provides more information about the PCB design guidelines
- [Cadence Capture CIS and Allegro PCB Symbols and Footprints page](#)
Provides more information about designing PCBs with the Cadence OrCAD capture component information system and symbols libraries.



A Document Revision History for the Automotive-Grade Device Handbook

| Date | Version | Changes |
|---------------------|------------|--|
| December 2017 | 2017.12.15 | <ul style="list-style-type: none"> • Removed Intel Cyclone 10 GX devices. <ul style="list-style-type: none"> — Removed Intel Cyclone 10 GX devices from <i>Automotive-Grade in Intel Cyclone 10 GX Devices</i> table. — Removed <i>Package Options and Maximum User I/Os in Intel Cyclone 10 GX Devices</i> table. — Removed <i>Automotive-Grade Ordering Information for Intel Cyclone 10 GX Devices</i> diagram. • Intel rebranding. |
| July 2017 | 2017.07.13 | Corrected the automotive temperature range in the figure showing the available options for the Intel Arria 10 GX devices from "-40°C to 100°C" to "-40°C to 125°C". |
| May 2017 | 2017.05.08 | <ul style="list-style-type: none"> • Updated links. • Rebranded as Intel. |
| February 2017 | 2017.02.13 | <ul style="list-style-type: none"> • Added Intel Arria 10, Cyclone 10, and Enpirion devices. • Removed PowerPlay text from tool name. |
| continued... | | |

Intel Corporation. All rights reserved. Intel, the Intel logo, Altera, Arria, Cyclone, Enpirion, MAX, Nios, Quartus and Stratix words and logos are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Intel warrants performance of its FPGA and semiconductor products to current specifications in accordance with Intel's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Intel assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Intel. Intel customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services.

*Other names and brands may be claimed as the property of others.

**ISO
9001:2008
Registered**



| Date | Version | Changes |
|----------|------------|--|
| May 2016 | 2016.05.03 | <ul style="list-style-type: none"> • Updated the Overview topic to remove ASIC devices. • Updated footnote in Automotive-Grade in MAX 10 Devices table. • Added new automotive-grade devices for the following device families: <ul style="list-style-type: none"> – MAX 10—10M08SAU169A7G – Cyclone V SoC—5CSXFC6D6F31A7N – Cyclone IV—EP4CE15U14A7N, EP4CE22U14A7N, and EP4CE55F23A7N • Removed the following devices from Automotive-Grade in MAX 10 Devices table. <ul style="list-style-type: none"> – 10M04SFE144A7G – 10M04SFU169A7G – 10M04DFF256A7G – 10M04DFU324A7G – 10M08SFE144A7G – 10M08SFU169A7G – 10M08DFF256A7G – 10M08DFU324A7G – 10M08DFF484A7G – 10M16SFE144A7G – 10M16SFU169A7G – 10M16DFF256A7G – 10M16DFU324A7G – 10M16DFF484A7G – 10M25SFE144A7G – 10M25DFF256A7G – 10M25DFF484A7G – 10M25DFF672A7G – 10M40SFE144A7G – 10M40DFF256A7G – 10M40DFF484A7G – 10M40DFF672A7G – 10M50SFE144A7G – 10M50DFF256A7G – 10M50DFF484A7G – 10M50DFF672A7G • Updated the Package Options and Maximum User I/Os in Cyclone V GX Devices table. <ul style="list-style-type: none"> – Updated the LE count for 5CGXC3 from 31.5K LEs to 36K LEs. – Added I/Os / XCVRs count for UBGA-484 package in 5CGXC9 device. • Updated the Package Options and Maximum User I/Os in Cyclone V GT Devices table. <ul style="list-style-type: none"> – Added I/Os / XCVRs count for UBGA-484 package in 5CGTD9 device. • Updated the following device ordering codes diagrams: <ul style="list-style-type: none"> – Automotive-Grade Ordering Information for MAX 10 Devices – Automotive-Grade Ordering Information for Cyclone IV E Devices – Automotive-Grade Ordering Information for Cyclone V SE Devices – Automotive-Grade Ordering Information for Cyclone V SX Devices • Changed instances of <i>Quartus II</i> to <i>Quartus Prime</i>. |
| | | continued... |



| Date | Version | Changes |
|----------------|------------|---|
| September 2014 | 2014.09.22 | <ul style="list-style-type: none"> • Added MAX 10 devices. • Removed HardCopy® II devices. • Updated the Quartus II software support versions for the legacy device families. <ul style="list-style-type: none"> – Cyclone III—Version 8.0 to 13.1 – Cyclone II—Version 7.2 SP1 to 13.0 – Cyclone—Version 7.2 SP1 to 13.0 – MAX 7000AE—Version 7.2 SP1 to 13.0 • Added new automotive-grade devices for the following device families: <ul style="list-style-type: none"> – Cyclone V—5CGXFC5C6F23A7N – Cyclone IV—EP4CE40U19A7N and EP4CGX15BF14A7N – MAX V—5M40ZE64A5N, 5M80ZT100A5N, and 5M160ZT100A5N • Added Cyclone IV GX ordering information diagram. • Updated HPS I/O count for Cyclone V SE and SX devices. |
| September 2013 | 3.4 | <ul style="list-style-type: none"> • Updated Table 3-2, Table 3-3, and Table 3-4. • Updated Figure 3-1, Figure 3-2, and Figure 3-3. |
| June 2013 | 3.3 | Updated Table 3-1 and Table 3-5. |
| May 2013 | 3.2 | <ul style="list-style-type: none"> • Updated Figure 3-2, Figure 3-3, Figure 4-1, and Figure 5-1. • Updated Table 3-1, Table 3-5, Table 4-2, Table 5-1, and Table 5-3. |
| February 2013 | 3.1 | Updated Table 2-2, Table 2-3, Table 3-2, Table 3-3, Table 3-4, Table 4-2, Table 4-3, and Table 5-2. |
| January 2013 | 3.0 | <ul style="list-style-type: none"> • Added Cyclone V and Cyclone V SoC devices. • Added Table 4-2, Table 4-3, and Table 5-2. • Updated Table 4-1, Table 4-4, Table 6-1, and Table 6-2. • Updated Figure 4-1. • Listed the following devices under legacy support: <ul style="list-style-type: none"> – Cyclone III – Cyclone II – Cyclone – MAX 7000A |
| May 2011 | 2.0 | <ul style="list-style-type: none"> • Added MAX V devices. • Updated part number for Cyclone III, Cyclone IV, and HardCopy II devices. • Template conversion. • Minor text edits. |
| March 2010 | 1.2 | <ul style="list-style-type: none"> • Added Cyclone IV devices. • Removed Referenced Documents section. |
| October 2008 | 1.1 | <ul style="list-style-type: none"> • Updated DC and Timing Specifications section. • Converted to new template. |
| February 2008 | 1.0 | Initial release. |