

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_MMCX-50-2-3/111\_O

Rev.: B



### Description

Straight cable plug for flexible cable

Interface standards  
SUHNER-MMCX

### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0008 kg

#### Environmental Data

Operating Temperature -55 °C to 155 °C  
2002/95/EC (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating
Body	Brass	Gold Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating

#### Related Documents

Outline drawing DOU-00006967  
Catalogue drawing DOU-00006969  
Assembly instruction DOC-0000180916

#### Ordering Information

Single package 11\_MMCX-50-2-3/111\_OE  
Bulk 100 pcs package 11\_MMCX-50-2-3/111\_OH

#### Additional Information

Suitable cables ENVIROFLEX\_316, RG\_316\_U, RG\_188\_A/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**