




PHYSICAL

Conductors: 24 AWG 7/32 Tinned Copper
 Insulation: .010" Nom. PVC
 Color Code: Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White, Black and Repeat
 Temp. Rating: 105°C

ELECTRICAL

Voltage Rating: 300 V
 Current Rating: 2.2 A @ 10°C Rise Above Ambient
 Insulation Res.: 10^{10} ohms - 10 ft Min.
 Cable Style: UL AWM Style 2693 (105°C, 300V)

Part Number	Count	Width, Nominal	
111-2413-010	10	.44	(11,18mm)
111-2413-015	15	.66	(16,76mm)
111-2413-020	20	.88	(22,35mm)
111-2413-030	30	1.32	(33,53mm)

DRAWN	PROD ENG	QA	MKT	P/ECN#		DRAWING NO.	111-2413-0XX	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872	Rev A
FITS 7/31/03						TITLE:	Spectra-Bond® Parallel		SHEET
							Conductor Cable		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[111-2413-010](#) [111-2413-020](#) [111-2413-015](#) [111-2413-030](#)