



PANCON CONNECTORS

Part Number: 120-096-435

Agency Cert	UL
Product Family	Pancon Connectors
Product Name	HI-CON® DIN 41612 Connectors
Brand Name	IDC Conn. Sys. - Type C & C/2 Female Socket
Rohs Status	COMPLIANT
Comp Type	Socket
Term Method	IDC
Wire Awg	28 awg ribbon cable
Contact Material	Copper Alloy
Contact Plating	selective gold over nickel performance level 2
Housing Material	Glass filled Polyester
Dielectric Voltage	1,000 VRMS
Durability	Performance Level 2 - 400 Mating Cycles
Flammability	UL 94 V-0
Insulation Resistance	10 ¹¹ Ohms
Mating Force	3.35 oz/contact
Packaging Type	Box
Standard Pack Size	25
Product Specification	PS 1203
Sales Drawing	KA-10389.pdf
Stackable	NO
Polarized To Mating Part	YES
Lock To Mating Part	NO
Polarization	YES
Breakaway	NO
Current Max Per Contact	1.5 amps
Voltage Max	300 volts
Wire Size Awg	28
Num Rows	3
Pitch Mating	.100"
Spacing	.050"
Gender	Female


[Request Quote](#)
[Request Sample](#)
[View PDF](#)
[Compliance Specifications](#)

Pancon Corporation
 350 Revolutionary Drive
 East Taunton, MA 02718
 800-342-6472 (toll-free)
 781-297-6000
info@panconcorp.com

Ark-Les Connectors
 Flag
 Quick Connects
 Rings and Spades
 Splices
 Stationary

Pancon Connectors
 Cross Reference
 HI-CON Products
 I/O Connectors
 Jumper Switches
 LAT-CON Products
 PAN-Flex Products

Paktron Capacitors
 Metallized PET
 Metallized PET-SMD
 Multilayer Polymer
 RC Snubber

Pancon MIE
 Insert Molded Connectors
 Insert Molded Housings
 Over Molded Leadframes

Pancon S3
 Stamped Terminals
 Compliant Pins
 Bandolier Pins



[Site Map](#) | All content copyright 2013 Pancon Corporation