

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

6P MOD II BREAK AWAY HDR , SMD, BLISTER

AMPMODU | AMPMODU Headers

1241150-6

TE Internal Number: 1241150-6

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **6**

Header Type **Breakaway**

✓ Active

 **PRODUCT DRAWING**

English

 **3D PDF**

Product Drawings

[AMPMODU II PIN HEADER, SINGLE ROW, SMD, PACKED IN BLISTER](#)

PDF

English

CAD Files

[3D PDF](#)

PDF

3D

[Customer View Model](#)

2D_DXF.ZIP

English

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Board Standoff

Without

Product Type	Connector
Gasket	Without
<hr/>	
Configuration Features	Number of Positions 6
	Number of Rows 1
	Keyed No
	Selectively Loaded No
<hr/>	
Body Features	Header Type Breakaway
	Post Size .64 mm [.025 in]
<hr/>	
Contact Features	Contact Protection Without
	Contact Shape Square
	Contact Type Pin
	Contact Base Material CuZn, Phosphor Bronze
	Solder Tail Contact Plating Material Tin over Nickel
	Contact Mating Area Plating Thickness (µm) .8
	Contact Mating Area Plating Material Gold
<hr/>	
Termination Features	Termination End Plating Material Tin
	Termination End Plating Thickness (µm) 3 – 5
	Termination Method to PC Board Surface Mount
<hr/>	
Mechanical Attachment	PCB Mounting Style Surface Mount
	PCB Mount Retention Without
	Panel Mount Retention Without
	Mating Alignment Without
	Mating Connector Lock Without
<hr/>	
Housing Features	Centerline 2.54 mm [.1 in]
	Housing Color Black
	Housing Material PCT GF
<hr/>	
Dimensions	Mating Post Length 5.8 mm [.228 in]
<hr/>	
Usage Conditions	High Temperature Housing No
<hr/>	

Operation/Application

High Speed Serial Data Connector

No

Packaging Features	Packaging Quantity	500
	Packaging Method	Reel

Product Compliance	Statement of Compliance PDF
VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	BARRIER STRIPS	SURFACE MOUNT RESISTORS	RJ25 CONNECTORS
 40 MODII HDR SRST B/A .100CL 9-146276-0	 4P .374" DR BARRIER STRIP 1546306-4	 CPF 0603 2K15 0.1% 25PPM 1K RL CPF0603B2K15E1	 MJ, RJ11, SMT, 6/6, GRAY, 13"REEL 5406514-2
 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products