

Datasheet

Product Name: UL1371 26AWG
Product Discription: UL1371 26AWG
Specification No.:
Customer's Name:

						Outcomer 5 realist			
Description					Construction				
Rated Vo	oltage:	Voltage	not specified	k	Conductor	Stranded Sliver plated co	pper		
		deg C,60 or 80 o	leg C Oil, Gasoli	ne Resistant	Size(AWG)	26			
Reference	erence Standard: UL758			Construction(±0.008mm)	7/0.16				
Cross Section					Stranded Dia.(mm)Ref.	0.48			
					Insulation Material PTFE				
					Insulation Color	sulation Color ANY COLOR			
					Ave Thickness(mm)	0.15			
					Insulation Dia.(±0.05mm)	0.84			
Marking					Remark:				
No marking on the cable jacket					9033995 Red	9033999 Blue	e 9034011 Grey	9034015 Violet	
					9033983 Black	9034002 White 9034009 Yellow			
					9033992 Brown	9034005 Gree	en 9034018 Orange	018 Orange	
					Characteristics		S	Customer Approve	
Applications					Test Item		Standard Value		
Internal Wiring, where not subjected to movement or					Test Material		PTFE(ROHS)		
mechanical damage					Insulation resistance(20℃ MΩ*m		1000		
					Vol. Tesr(AC.V.60S) (V)		2000	Cool 9 Ctomp	
					Flammability Test		Horizontal flame	Seal & Stamp	
Revisions					Max.DC Resistance(20℃ Ω/km)		127.0(MAX)		
Version	Description	Drawn by	Approved by	Date					
1 0	New document issue	Danniel	Jason	05/10/2015					
								Signature:	
								Date:	
			ı		u				

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.