



RIBBON CABLE CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

V23535A2200A 60=BKMOD421 HEADE

[AMP-LATCH](#) | [EMG Latch](#)

1393586-3

TE Internal Number: 1393586-3

Alias ID: V23535A2200A 60, V23535A2200A60

[Always EU RoHS/ELV Compliant](#)

Centerline **2.54 mm [.1 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole - Solder**

Shrouded **Yes**

Product Drawings

[Steckverbinder, ML, Kompakt Header \(Ma Bild\) Plug Connector, ML, Compact Header](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1393586-3_01082016922_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

PCB Mounting Orientation	Vertical
Shrouded	Yes
Row-to-Row Spacing	2.54 mm [.1 in]
Connector Style	Receptacle
Profile	Low
Applies To	Printed Circuit Board
Product Type	Connector
Board Standoff	Without
Connector Type	Header
Connector System	Wire-to-Board
Ejection Latches	Without

Configuration Features	Number of Positions	6
	Number of Rows	2
Body Features	Post Size	.64 mm [.025 in]
	Header Type	Pin Header
	Daisy Chain	Without
Contact Features	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
	Contact Design	Solder Dip
	Contact Shape	Square
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	CuZn
	Contact Type	Pin
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Post Length	2.9 mm [.114 in]
Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center
	Mating Connector Lock	Without
	Mating Alignment	With
	Polarization	With
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Gray
	Housing Style	4-Sided
	Housing Material	PBT GF
Dimensions	Height	8.9 mm [.35 in]
Usage Conditions	Temperature Rating	Standard
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tray
	Packaging Quantity	80

