

## V23026D1023B201 Product Details

**V23026D1023B201**

(1393776-6)

TE Internal Number: 1393776-6

[Active](#)**Communications/Signal PC Board Relays**[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)**Product Highlights:**

- V23026 / P1 Relay Series
- DC Actuating System
- Input Voltage = 15 VDC
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 1 Amps.

[View all Features](#)**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[!\[\]\(5a351309c3b87e4420622c1f0e57efc0\_img.jpg\) Add to My Part List](#) [!\[\]\(109f62b74df51103529c262619933f25\_img.jpg\) Request Sample](#) [!\[\]\(4d14b1b787ec9dd7ebdfa2a60f58688e\_img.jpg\) Find Similar Products](#) [!\[\]\(6db7b173d29de84b9bc04eedb0173d7b\_img.jpg\) Buy Product](#)**Documentation & Additional Information****Product Drawings:**

- None Available

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

**Additional Information:**

- [Product Line Information](#)

**Additional Product Images:**

- [Product Photo](#)
- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

**Related Products:**

- [Tooling](#)

**Product Features (Please use the Product Drawing for all design activity)****Product Type Features:**

- Termination Type = SMT, J-Legs
- Comment = Delivered in sticks

**Electrical Characteristics:**

- Actuating System = DC
- Input Voltage (VDC) = 15
- Contact Current Rating (Amps.) = 1
- [Coil Resistance \(?\)](#) = 2813
- Coil Power, Nominal (mW) = 80
- Dielectric Between Coil and Contacts (V rms) = 1500

**Body Related Features:**

- [Series](#) = V23026 / P1 Relay
- Polarized = Yes

**Contact Related Features:**

- Mounting Options = PC Board
- Enclosure = Immersion Cleanable
- [FCC Part 68 Isolation](#) = Yes
- Approved Standards = CSA Certified, UL Recognized
- Contact Base Material = Palladium-Nickel, Gold Overlay, Rhodium Flash
- Approx. Dimensions (L x W x H) (mm [in]) = 13.00 x 7.85 x 8.00 [.512 x .309 x .315]
- Contact Type = Bifurcated
- Pin Configuration = DIP

**Configuration Related Features:**

- [Contact Arrangement](#) = 1 Form C, SPDT, 1 C/O
- [Coil Magnetic System](#) = Polarized, Monostable
- Coil Suppression Diode = Without

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

**Other:**

- Brand = Axicom

**Corporate Information**[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat with Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)