



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

GET MALE TERM, B, SN

AMP | Get .64 Connector System

1438299-4

TE Internal Number: 1438299-4

Converted to EU RoHS/ELV Compliant

Terminal Style **Pin/Tab**

Mating Tab Width **1 mm [.025 in]**

Mating Tab Thickness **.64 mm [.025 in]**

Terminal Transmits **0 – 24 A (Low Power)**

Wire Size Search (mm²) **.5, .6, .75**

Wire Size Search (AWG) **18, 19, 20**

Product Drawings

[0.64mm GET MALE IN-LINE TERMINAL](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Application Specification

[Global Electronic Technology \(GET\) 0.64-Mm Pin And Socket Terminals For GET Connectors](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Primary Locking Feature

Clean Body

Wire Type

Copper

Contact Features

Terminal Style

Pin/Tab

Mating Tab Width	1 mm [.025 in]
Mating Tab Thickness	.64 mm [.025 in]
Interface Plating	Tin (Sn)
Typical Current Rating (A)	11
Contact Termination Area Plating Material	Gold (Au)

Termination Features	Termination Method	Double Crimp
	Crimp Type	F-Crimp

Dimensions	Wire Size Search (mm ²)	.5, .6, .75
	Wire Size Search (AWG)	18, 19, 20
	Wire Size	.5 – .75 mm² [20 – 18 AWG]
	Wire Insulation Diameter	1.4 – 2.06 mm [.055 – .081 in]

Usage Conditions	Operating Temperature (Max) (°C)	80, 85, 90, 100, 105, 110, 120, 125
	Operating Temperature (Max) (°F)	176, 185, 194, 212, 221, 230, 248, 257
	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]

Industry Standards	Agency/Standard	SAE/USCAR-2, USCAR-21
--------------------	-----------------	------------------------------

Other	Terminal Transmits	0 – 24 A (Low Power)
-------	--------------------	-----------------------------

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>OTHER AUTOMOTIVE CONNECTOR ACCESSORIES</p>  <p>BODY CLIP HOUSING DUAL 345485-1</p> <p>Save to List Find Similar Products</p>	<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS</p>  <p>3P FML ASSY, SEAL, STD, A KEY, W/CPA, ALLOPEN 1488991-5</p> <p>Save to List Find Similar Products</p>	<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS</p>  <p>3 POS AMP MCP1.5k REC. HSG COD 2-1418448-1</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p>  <p>MALE CONTACT ASSY. (STRIP) 1-66255-1</p> <p>Save to List Find Similar Products</p>
---	--	---	--

Relation Type ▼


RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS



Connectors - Automotive, Truck, Bus, & Off-Road Terminals

AMP I Get .64 Connector System

V23540X7000Y 21=GET-FEM TERM S - 1393366-1

TE INTERNAL NUMBER: 1393366-1

ALIAS ID: V23540X7000Y 21, V23540X7000Y21

Active

Always EU RoHS/ELV Compliant

Terminal Style Receptacle/Socket

Mating Tab Width 1 mm

Mating Tab Thickness .64 mm

Terminal Transmits 0 - 24 A (Low Power)

Wire Size Search .5 mm², .6 mm², .75 mm²



RELATIONSHIP

Toolings

Tooling

See All Toolings

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators AMP

OC-AT-S-FA-070F068SP-001-0069 - 2151539-2

TE INTERNAL NUMBER: 2151539-2

Active

Not in Scope for EU RoHS/ELV Compliance

Region Worldwide

Tool Type Applicator

Spare Parts Tooling No

Applicator Style OCEAN - Atlantic

Applicator Feed Style Side Feed



RELATIONSHIP

Toolings

Tooling

See All Toolings

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators AMP

OC-PA-S-FA-070F068SP-001-0069 - 2-2151539-2

TE INTERNAL NUMBER: 2-2151539-2

Active

Not in Scope for EU RoHS/ELV Compliance

Region Worldwide

Tool Type Applicator

Spare Parts Tooling No

Applicator Style OCEAN - Pacific

Applicator Feed Style Side Feed



