


031-0050-0001 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



031-0050-0001
(1466288-1)

TE Part Number: 1466288-1

Active

Add to Part List

SMB RF Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Jack
- Miniature
- Terminate To Coaxial Cable
- Coupler Style = Threaded

[View all Features](#) | [Find Similar Products](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [BULKHEAD RECEPTACLE S-50 OHM TURRET 'D' MOUNT](#) (TIF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Gender](#) = Jack
- Connector Series = Miniature
- [Body Style](#) = Straight
- [Grade](#) = Commercial
- Safety Wire Holes = Without
- Thread Size = 4.83 [.190]-32
- Panel Thickness (mm [in]) = 4.06 [0.160]
- Body Material = Brass
- Dielectric Material = TEFLON

Mechanical Attachment:

- [Panel Attachment](#) = With
- [Panel Attachment Style](#) = Front Mount
- Panel Attachment Method = Jam Nut

Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 50
- Environmental Seal = Without
- Solderless = No

Termination Related Features:

- [Coaxial Cable Termination Type](#) = Solder

Body Related Features:

- Coupler Style = Threaded
- [Pin Protection](#) = Without
- Solder Lug = With
- [Body Plating](#) = Gold per MIL-G-45204, Type II, Grade C, Class 1
- Terminal Style = Turret Pin

Contact Related Features:

- [Center Contact Plating](#) = Gold per MIL-G-45204, Type II, Grade C, Class 1
- Contacts = With

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Terminate To](#) = Coaxial Cable

Other:

- Brand = Microdot