

# Self Adhesive / Screw Fixing Cable Tie Mounts TY3G1S

TY-Series Rectangle Design, self adhesive, screwable,  
Article number: 151-11319



## Features

- Screwable or self-adhesive versions
- Concave design to support larger diameter cables and bundles
- 2-way mounting base for safe guiding of cables and conduits
- Suitable for applications with minimal space
- Mounted before cable installation
- Usable with standard cable ties for reduced inventory

## TY-Series Rectangle Design, self adhesive, screwable application

Where speed, simplicity, and a firm fixing base are required these self adhesive clips are ideal. Particularly suitable for use in control cabinets, telecoms equipment or domestic appliances where the use of holes, screws, or nuts and bolts is impractical or undesirable.

## TY-Series Rectangle Design, self adhesive, screwable is suitable for following markets and industries



Solar Energy Sector



Wind Energy Sector



Rail Transportation Sector



Electrical Wholesale



Shipbuilding



Defence Industry

## Base Data

---

<b>Colour</b>	Natural (NA)
<b>Description Short (BMEcat) (max. 150 characters)</b>	Screw Fixing Cable Tie Mount self adhesive 20x14 natural
<b>Fixation Method (FF)</b>	Screw Mounting and Adhesive
<b>Manufacturer Type</b>	TY3G1S PA66 NA 100
<b>Product Family</b>	TY-Series Rectangle Design, self adhesive, screwable
<b>Product Group</b>	Self Adhesive / Screw Fixing Cable Tie Mounts
<b>Type</b>	TY3G1S.NN3P

## Product Dimensions

---

<b>Fixing Hole Centres (F)</b>	15.0 mm
<b>Height (H)</b>	3.7 mm
<b>Hole <math>\varnothing</math></b>	2.2 mm
<b>Hole <math>\varnothing</math> (FH)</b>	2.2 mm
<b>Hole <math>\varnothing</math> (FH) min.</b>	2.2 mm
<b>Length (L)</b>	20.0 mm
<b>Strap Width max. (G)</b>	4.0 mm
<b>Thickness of Adhesive (TA) nom.</b>	0.8
<b>Width (W)</b>	14.0 mm

## Logistics and Packaging

---

<b>Carton Quantity</b>	5000 pcs.
<b>EAN / GTIN</b>	4031026122168
<b>Pack Cont.</b>	100 pcs.
<b>Quantity of Europallet</b>	240000 pcs.
<b>Quantity per</b>	pieces
<b>Weight</b>	0.8 kg

## Material and Specifications

---

<b>Adhesive</b>	Acrylate with base of polyurethane foam
<b>Adhesive Operating Temperature</b>	to +105 °C
<b>Adhesive Shortcut</b>	Acrylate
<b>ELV compliant Dir. Art. 4 (2)</b>	YES
<b>Flammability</b>	UL94 V2 (excluding adhesive)
<b>Halogenfree</b>	Yes
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material</b>	PA66
<b>Operating Temperature</b>	-40 °C to +85 °C, (+105 °C, 500 h)
<b>REACH compliant Regu. Art. 33</b>	YES

## More Information

---

<b>ETIM 5.0</b>	EC000449
<b>ETIM 6.0</b>	EC000449

## Competences

---



### Cable Ties

Cable ties for your applications: inside and outside serrated cable ties, releasable cable ties, cable tie mounts, clips ...