

1520136 -2 Product Details



1520136 -2

[Active](#)

Power Toggle Switches

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? Double Pole - Single Throw Configuration (Pole - Throw)
- ? Toggle Length = 12.70 mm
- ? Toggle Style = Baton with Ball
- ? Bushing Length = 11.50 mm
- ? Termination Type = Screw - In Terminal

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

? None Available

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Related Products:

? [Tooling](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Configuration (Pole - Throw) = Double Pole - Single Throw
- ? Termination Type = Screw - In Terminal

Electrical Characteristics:

- ? UL/CSA 125V Current Rating (Amps.) = 20
- ? UL/CSA 250V Current Rating (Amps.) = 10
- ? UL/CSA 125V Horse Power Rating (hp) = 1.50
- ? UL/CSA 250V Horse Power Rating (hp) = 1.50

Housing Related Features:

- ? Toggle Length (mm [in]) = 12.70 [0.500]
- ? Toggle Style = Baton with Ball

Configuration Related Features:

- ? Bushing Length (mm [in]) = 11.50 [0.453]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Not reviewed for lead free solder process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- ? Brand = Alcoswitch