

PHYSICAL PROPERTIES:	SEE FIGURE.
HOUSING MATERIAL: THERMOPLASTIC, PC	
FLAMMABILITY: UL94V-0 COLOR: BLACK	
MAX BOW/WARP: .0056 IN/IN.	
TERMINAL:	
TERMINALS: BRASS, TIN PLATED	
SCREWS: 6-32, STEEL, NICKEL PLATED	
MECHANICAL:	
PITCH (TERMINAL SPACING): 9.50mm(.374")	
WIRE RANGE: 12-22 AWG	
RECOMMENDED TIGHTENING TORQUE: 12IN-LBS MAX.	
ELECTRICAL PROPERTIES:	
MAXIMUM CURRENT: 20A	
OPERATING VOLTAGE: 300V	
ENVIRONMENTAL PROPERTIES:	
OPERATING TEMP. RANGE: -40°C TO +120°C	

-- SELECT LOAD CHART --

[illegible]

	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	294.7	302.2	30	3-1546306-0
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	285.2	292.7	29	2-1546306-9
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	275.7	283.2	28	2-1546306-8
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	266.2	273.7	27	2-1546306-7
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	256.7	264.2	26	2-1546306-6
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	247.2	254.7	25	2-1546306-5
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	237.7	245.2	24	2-1546306-4
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	228.2	235.7	23	2-1546306-3
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	218.7	226.2	22	2-1546306-2
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	209.2	216.7	21	2-1546306-1
 SPL MARKING	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	199.7	207.2	20	3-1546306-2
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	199.7	207.2	20	2-1546306-0
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	190.2	197.7	19	1-1546306-9
NOTES	(1)  SPL MARKING	(2)  SPL MARKING	(11)  SPL MARKING	(10) JUMPER	(9)  SPL MARKING	(8)  SPL MARKING	(7)  SPL MARKING	(6)  SPL MARKING	(5)  SPL MARKING	(4)  SPL MARKING	(3)  SPL MARKING	(2)  SPL MARKING	(1)  SPL MARKING	DIM B		DIM A		NO. OF		PART NO.	

[illegible]

Downloaded from Elcodis.com electronic components distributor