







TOP VIEW




**SECTION B-B
SIDE VIEW**





INSIDE LID



SECTION A-A



INSIDE BOX



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmg.com for quotes
Solid models of this enclosure available in STEP or IGES.
(Part number and text placement/orientation on our products are subject to change,
we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes box, lid and 4 cover screws.
Box and lid are made from Diecast Aluminum Alloy.
Silicone Gasket supplied with liquid resistant enclosure.

Recommended Torque: 50-55 cN.m [71-78 ozf.in]

Recommended Torque with Gasket : 25-30 cN.m [36-43 ozf.in]

PART NUMBERS

1590TRPC Enclosure	
Natural Finish Enclosure	1590TRPC
Black Textured Enclosure	1590TRPCBK
1590TRPC Liquid Resistant Enclosure (Silicone Gasket)	
Natural Finish Enclosure	1590WTRPC
Black Textured Enclosure	1590WTRPCBK

ACCESSORIES

Liquid Resistant Cover Screws

Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100
Black Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100BK

Standard Cover Screws

Plated Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100
Black Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100BK



**HAMMOND
MANUFACTURING®**

1590TRPC

www.hammondmg.com

Dimensions:
mm
[inches]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hammond:](#)

[1590TRPCPR](#) [1590TRPCYL](#) [1590TRPC](#) [1590TRPCBK](#) [1590TRPCCB](#) [1590TRPCGR](#) [1590TRPCLG](#)
[1590TRPCOR](#) [1590TRPCRD](#)