

HelaGuard**LTS-LTS Compression Coupler, IP68**

Nickel plated brass.

Fulfils IP66, IP67 and IP68.

Features and Benefits

- Multipart compression coupler including polyamide seals
- Joins two conduits



HelaGuard LTS-LTS Compression Coupler.

Technical Table

Article-No.	Type	Conduit Ø	Pack Cont.
166-32600	LTS20-LTS20	20	10
166-32601	LTS25-LTS25	25	10

All dimensions in mm. Subject to technical changes.

Material Data

Material	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Colour	Metal (ML)
Operating Temperature	-40 °C to +135 °C

**HelaGuard****LTS-EI End Insert**

Nickel plated brass.

Features and Benefits

- Single part
- Caps end of conduit



HelaGuard LTS-EI End Insert.

Technical Table

Article-No.	Type	Conduit Ø	Pack Cont.
166-32700	LTS10-EI	10	10
166-32701	LTS12-EI	12	10
166-32702	LTS16-EI	16	10
166-32703	LTS20-EI	20	10
166-32704	LTS25-EI	25	10
166-32705	LTS32-EI	32	2
166-32706	LTS40-EI	40	1
166-32707	LTS50-EI	50	1
166-32708	LTS63-EI	63	1

All dimensions in mm. Subject to technical changes.

Material Data

Material	Nickel Plated Brass (NPB)
Colour	Metal (ML)
Operating Temperature	-100 °C to +300 °C

