

166-90222



Article Number: 166-90222

HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 0.75" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel



 Download spec sheet

 Download tech sheet

Base Data

Local Order Number	166-90222
Type	PSR0750
Color	Black (BK)
Features and Benefits	• Spiral reinforced construction provides protection from crushing yet remains extremely flexible. • Lightweight, easy-to-use material reduces installation time and labor costs. • Material stands up to vibration and limited torsional movement without creation of stress points or cracks. • Smooth inside bore protects wires and eases insertion of wire bundles. • UV resistant; suitable for use in outdoor applications.
Product Description	A lightweight tubing with a smooth inside bore, made of a spiral reinforced PVC material that provides high flexibility. This tubing is well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Non-Metallic Compression Fittings to create an enclosed system.
Short Description	HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 0.75" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.5 m
Inner Diameter D (Imperial)	0.87 "
Inner Diameter D (metric)	22 mm
Outside Diameter D (imperial)	1.09 "
Outside Diameter D (metric)	27.5 mm
Nominal Diameter (imperial)	3/4 "
Nominal Diameter (metric)	25 mm
Inside Bend Radius (Imperial)	1.78 "
Inside Bend Radius (Metric)	45 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	30.5 m
Trade Size	3/4

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Flammability	self-extinguishing according to EN IEC 61386
Halogenfree	No
Operating Temperature	-4°F to +158°F (-20°C to +70°C)
ROHS Conformity	Yes
UL Listed (US)	No
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes
UL Recognized (US)	Yes