

166-90223



Article Number: 166-90223

HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.00" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel



 Download spec sheet

 Download tech sheet

Base Data

Local Order Number	166-90223
Type	PSR1000
Color	Black (BK)
Features and Benefits	• Spiral reinforced construction provides protection from crushing yet remains extremely flexible. • Lightweight, easy-to-use material reduces installation time and labor costs. • Material stands up to vibration and limited torsional movement without creation of stress points or cracks. • Smooth inside bore protects wires and eases insertion of wire bundles. • UV resistant; suitable for use in outdoor applications.
Product Description	A lightweight tubing with a smooth inside bore, made of a spiral reinforced PVC material that provides high flexibility. This tubing is well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Non-Metallic Compression Fittings to create an enclosed system.
Short Description	HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.00" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.5 m
Inner Diameter D (Imperial)	1.11 "
Inner Diameter D (metric)	28 mm
Outside Diameter D (imperial)	1.32 "
Outside Diameter D (metric)	33.5 mm
Nominal Diameter (imperial)	1 "
Nominal Diameter (metric)	32 mm
Inside Bend Radius (Imperial)	2.36 "
Inside Bend Radius (Metric)	60 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	30.5 m
Trade Size	1

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Flammability self-extinguishing according to EN IEC 61386

Halogenfree No

Operating Temperature -4°F to +158°F (-20°C to +70°C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US and Canada) Yes

UL Recognized (US) Yes