

- Panel Gasket: NBR, Color: Black			PRODU TO A TH	로				UP	LC ± 0.30	7			
- M3 Mounting Hardware: Stainless Steel				-	ame	Title	Approval Date	2 P 3 P	PLC ±0.30 PLC ±0.20 PLC ±0.10 PLC ±0.05	Autodesk Inventor	Material. See Notes		
Includes 4 x (Screw + Nut + Flat Washer + Spring Lock Washer)		SED OI SION.	DRAWING				ANGLES ±1° 2012 Date		Name	┨			
3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm. 4. IP67 rated when covered or fully mated with the appropriate mating connector 5. Hardware shipped unassembled			E PAS E PAS ERMIS	8 -				Draw.	Oct.16	Vincent Ke	IP67 Cat. 6A RJ45 Inline Coupl		
			NOT BE					Appd. Oct.16	Oct.16	J. Chaudry		-	Α
			AY NO MAY WRIT	¥				Norm	Nickel Plated Z		Nickel Plated Zinc Die-Cast	re-Cast Version	4
ⓑ 6. Recommended mounting torque is 8 to 10 lb-inch			AND SAN	┰				D-old			Drawing No.: 17K1A366		
			WAY. WITH	DOI 1	1 x b	Mar/11/201	3 Vincent Ke			B	, Diawing No.: 1/K1A300		┙
			THIS DE IN ANY PARTY OWNER		original						Part No.: 17-160004		ıt.
				Rev.	Changes	Date	Name)	T all		1 art No.: 17-160004		
4	1.								2		1		_

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CONEC: 17-160004