

170-03113



**Article Number:** 170-03113

**Plenum Rated Expandable Braided Sleeving (Halar), 1.75" Dia., White, 30.0 ft/Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03113

**Type** BSHLR13410

**Color** White (WH)

**Features and Benefits**

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

**Product Description** Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.

**Short Description** Plenum Rated Expandable Braided Sleeving (Halar), 1.75" Dia., White, 30.0 ft/Reel

## Product Dimensions

**Length L (Imperial)** 30.0 "

**Length L (Metric)** 9.1 mm

**Reel Length (imperial)** 30.0 ft

**Width W (Imperial)** 0.02 "

**Width W (Metric)** .60 mm

**Bundle Diameter Min. (Imperial)** 1.25 "

**Bundle Diameter Min. (Metric)** 31.8 mm

**Bundle Diameter Max. (Imperial)** 2.75 "

**Bundle Diameter Max. (Metric)** 69.9 mm

**Nominal Diameter (Imperial)** 1-3/4 "

**Nominal Diameter (Metric)** 44.4 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 30 ft

**Weight (imperial)** 1.32 lbs

## Material and Specifications

**Material** Polyamide 6.6 (E/CTFE)

**Material Shortcut** E/TFE

**Flammability** FAR 25  
UL VW-1

**Operating Temperature** -103°F to +302°F (-75°C to +150°C)

**ROHS Compliant** Yes

**Certification/Specification** UL2024

**UL Recognized (US and Canada)** Yes