

## Printed-circuit board connector - DFK-PC 5/11-GF-7,62 - 1727786

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 41 A, Rated voltage (III/2): 630 V, Number of positions: 11, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Mounting: Soldering



### Why buy this product

- ✓ Panel thickness of 1 mm to 3 mm
- ✓ For soldering onto the PCB
- ✓ Mounted on the housing panel by means of tool-free snap-lock mechanism or conventional screw connection
- ✓ Feed-through headers for use in combination with all PC 5 plugs



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 pc                                                                                                   |
| Minimum order quantity               | 10 pc                                                                                                   |
| GTIN                                 | <br>4 046356 136037 |
| Weight per Piece (excluding packing) | 27.76 g                                                                                                 |
| Custom tariff number                 | 85366990                                                                                                |
| Country of origin                    | Poland                                                                                                  |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Dimensions

|                |           |
|----------------|-----------|
| Length         | 29.25 mm  |
| Pitch          | 7.62 mm   |
| Dimension a    | 76.2 mm   |
| Pin dimensions | 0,8 x 1,0 |
| Pin spacing    | 7.62 mm   |
| Hole diameter  | 1.3 mm    |

#### General

|                           |                 |
|---------------------------|-----------------|
| Range of articles         | DFK-PC 5/...-GF |
| Insulating material group | I               |

## Printed-circuit board connector - DFK-PC 5/11-GF-7,62 - 1727786

### Technical data

#### General

|                                         |        |
|-----------------------------------------|--------|
| Rated surge voltage (III/3)             | 6 kV   |
| Rated surge voltage (III/2)             | 6 kV   |
| Rated surge voltage (II/2)              | 6 kV   |
| Rated voltage (III/3)                   | 500 V  |
| Rated voltage (III/2)                   | 630 V  |
| Rated voltage (II/2)                    | 800 V  |
| Connection in acc. with standard        | EN-VDE |
| Nominal current $I_N$                   | 41 A   |
| Maximum load current                    | 41 A   |
| Insulating material                     | PA     |
| Inflammability class according to UL 94 | V0     |
| Color                                   | green  |
| Number of positions                     | 11     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

#### Approvals

## Printed-circuit board connector - DFK-PC 5/11-GF-7,62 - 1727786

### Approvals

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

#### Approvals submitted

#### Approval details

|                                                                                                 |       |       |       |
|-------------------------------------------------------------------------------------------------|-------|-------|-------|
| UL Recognized  |       |       |       |
|                                                                                                 | B     | C     | D     |
| Nominal current I <sub>N</sub>                                                                  | 41 A  | 41 A  | 10 A  |
| Nominal voltage U <sub>N</sub>                                                                  | 300 V | 150 V | 300 V |

|                                                                                                    |       |       |       |
|----------------------------------------------------------------------------------------------------|-------|-------|-------|
| cUL Recognized  |       |       |       |
|                                                                                                    | B     | C     | D     |
| Nominal current I <sub>N</sub>                                                                     | 41 A  | 41 A  | 10 A  |
| Nominal voltage U <sub>N</sub>                                                                     | 300 V | 150 V | 300 V |


|     |
|-----|
| EAC |
|-----|

|                                                                                                      |
|------------------------------------------------------------------------------------------------------|
| cULus Recognized  |
|------------------------------------------------------------------------------------------------------|


### Drawings

## Printed-circuit board connector - DFK-PC 5/11-GF-7,62 - 1727786

Drilling diagram




Dimensioned drawing




Sheet metal cutout for snap-on.

Dimensioned drawing



Dimensioned drawing



Sheet metal cutout for screw connection.