

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION








© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DW

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
E		REVISED (ECR-12-012115) OBSOLETE PMS: -3, -8, -13, -14, -16 & -17	26OCT'12	E.L.	W.K.

MATING WITH RJ-45 PLUG
(REFERENCE)RECOMMENDED PCB LAYOUT (THICKNESS: 1.6MM)
(DIMENSION TOLERANCE: 1 PLC: ±0.1, 2 PLC: ±0.05)

NOTE:

1. MATERIAL:

1.1 HOUSING: PA9T WITH 30% GF, UL94 V-0, BLACK COLOR.

1.2 CONTACTS: PHOSPHOR BRONZE.

1.3 SHELL: BRASS.

2. FINISH:

2.1 CONTACTS:

(SEE TABLE) GOLD PLATED ON CONTACT AREA.

GOLD FLASH ON SOLDER TAIL.

1.27μm [50u"] MIN. NICKEL UNDERPLATED OVERALL.

2.2 SHELL: 0.51μm [20u"] MIN. NICKEL PLATED.

3. WAVE SOLDER CAPABLE TO 265°C PER TYCO TEST SPEC. 109-202, CONDITION B.

⚠ OBSOLETE PART : OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm



MATERIAL

SEE NOTE

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	± .
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	± .
ANGLES	± 3°

FINISH

SEE NOTE

DWN O. HU 14SEP2007

CHK S. HOU 14SEP2007

APVD W.J. KE 14SEP2007

PRODUCT SPEC

108-57535

APPLICATION SPEC

WEIGHT 3.5 GRAMS

CUSTOMER DRAWING

SCALE

SHEET 1 OF 5

REV E

	TAPE & REEL	W/O	W/O	TYPE A	2.2	6u"	3-1734795-2
					1.5	6u"	3-1734795-1
TE	TRAY	W/ W/O			2.4	50u"	1734795-8
						30u"	1734795-7
						15u"	1734795-6
				6u"		1734795-5	
				50u"		1734795-4	
TE	W/O	TYPE B		30u"	1734795-3		
TE		TYPE A		15u"	1734795-2		
				6u"	1734795-1		
	PACKAGE TYPE	PANEL GROUND	LED	SHELL TYPE	DIM L	MIN. GOLD THICKNESS	PART NUMBER

STE

TE Connectivity

NAME

MODULAR JACK CONNECTOR
RJ45, 8P8C, SHIELDED
TAB UP, DIP TYPE, H=11.3mm

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 C=1734795

SCALE

SHEET 1 OF 5

REV E

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION



© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DW




DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			

0.8~2.0
6 PLC

AMP LOGO

MATING WITH RJ-45 PLUG
(REFERENCE)SHIELD'S
LEGS
2 PLC

LED 2

LED 1

0.46X0.35
8 PLC

0.25 A B

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

8 PLC

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC
DW

DIST



REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			

TRAY
325mm(L)X216mm(W)X17.5mm(H)






INNER CARTON
345mm(L)X240mm(W)X175mm(H)



CARTON
500mm(L)X365mm(W)X195mm(H)

PACKAGE BEIT

TRAY (10 LAYERS)


20 DESICCATING AGENTS
AT LEAST

80	800	1600	8.5	6.5	1734795-4
					1734795-3
					1734795-2
					1734795-1
PCS/ TRAY	TRAYS/ CARTON	QUANTITY (PCS)	G/W (Kg)	N/W (Kg)	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm



MATERIAL

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	± .
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	± .
ANGLES	± 3°

FINISH

DWN	—
CHK	—
APVD	—
PRODUCT SPEC	—
APPLICATION SPEC	—
WEIGHT	—
CUSTOMER DRAWING	—

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=

1734795



TE Connectivity

MODULAR JACK CONNECTOR
RJ45, 8P8C, SHIELDED
TAB UP, DIP TYPE, H=11.3mm

SCALE

SHEET 3 of 5

REV E

D

C

B


A

D

C

B

A



90	33	2970	12.5	10.5	1-1734795-4
					1-1734795-3
					1-1734795-2
					1-1734795-1
					2-1734795-2
					1-1734795-8
					1-1734795-7
					1-1734795-6
					1-1734795-5
					1734795-8
					1734795-7
					1734795-6
					1734795-5
PCS/ TRAY	TRAYS/ CARTON	QUANTITY (PCS)	G/W (Kg)	N/W (Kg)	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± 0.3

2 PLC ± 0.2

3 PLC ± 0.15

4 PLC ± -

ANGLES ± 3°

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

TE Connectivity

NAME

MODULAR JACK CONNECTOR
RJ45, 8P8C, SHIELDED
TAB UP, DIP TYPE, H=11.3mm

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C=1734795

CUSTOMER DRAWING

SCALE

SHEET

4 of 5

REV

E

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION.

LOC
DW

DIST

REVISIONS

P

LTR





DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1.



8.7 KG	5.05 KG	180	8	1440	3-1734795-2
GROSS WEIGHT	NET WEIGHT	PCS/REEL	REEL/BOX	PCS/BOX	PART NUMBER
					3-1734795-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC $\pm .$
 1 PLC ± 0.3
 2 PLC ± 0.2
 3 PLC ± 0.15
 4 PLC $\pm .$
 ANGLES $\pm 3^{\circ}$

MATERIAL

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME

MODULAR JACK CONNECTOR
 RJ45, 8P8C, SHIELDED
 TAB UP, DIP TYPE, H=11.3mm

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1734795

SCALE

SHEET

5 of 5

REV

E