

# **RAFIX 22 FS<sup>+</sup> - Signal indicator, round collar, suitable for legending**

**1.74.508.001/2200**


## General information

|                |                   |
|----------------|-------------------|
| Form of lens   | flat lens         |
| Color of lens  | translucent white |
| Form of collar | round             |

## Dimensions

|                  |                          |
|------------------|--------------------------|
| Length of collar | acc. to potentiometer mm |
| Overall height   | 9.7 mm                   |
| Mounting depth   | PCB 9.2 mm, QC 27 mm     |
| Mounting hole    | 22.3 mm                  |
| Key grid         | 30 x 30 mm               |

## Mechanical design

|                     |          |
|---------------------|----------|
| Mounting            | ring nut |
| Illuminability      | yes      |
| Torque for nut ring | 1.2 Nm   |

## Other specifications

|                                      |                                          |
|--------------------------------------|------------------------------------------|
| Degree of protection from front side | IP65 (DIN EN 60529)                      |
| Ambient temp. operating min.         | -25 °C                                   |
| Ambient temp. operating max.         | +70 °C                                   |
| Storage temperature min.             | -40 °C                                   |
| Storage temperature max.             | +80 °C                                   |
| Environmental resistance             | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Salt spray                           | IEC 600 68-2-11                          |
| ROHS compliant                       | yes                                      |
| REACH compliant                      | yes                                      |

Panel cut-out to IEC 60947-5-1



