



## BOX MOUNT D-SUB CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### AMPLIMITE, ASY, RCPT, STD, 90, ZN, 2

[AMPLIMITE](#) | [AMPLIMITE](#)

1757824-2

TE Internal Number: 1757824-2

Mil-Spec: M24308/2-287Z

[Always EU RoHS/ELV Compliant](#)

Connector Style **Receptacle**

Number of Positions **26**

Power/Signal/Coax Combination **No**

Shell Size **2**

Contact Style **Crimp Snap-In**

#### Product Drawings

#### [AMPLIMITE RECEPTACLE ASSY, SIZE 1 THRU 6 SERIES 90 WITH ZINC PLATED SHELLS](#)

PDF  
**English**

#### CAD Files

#### [3D PDF](#)

PDF  
**3D**

#### [Customer View Model](#)

2D\_DXF.ZIP  
**English**

#### [Customer View Model](#)

3D\_IGS.ZIP  
**English**

#### [Customer View Model](#)

3D\_STP.ZIP  
**English**

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Connector Style

**Receptacle**

Shell Size

**2**

Blindmate

**No**

Applies To

**Wire/Cable**

Product Type

**Connector**

#### Configuration Features

Number of Positions

**26**

	Power/Signal/Coax Combination	<b>No</b>
Body Features	Non-Magnetic	<b>No</b>
	Retention Clip Material	<b>Stainless Steel</b>
	Shell Material	<b>Steel</b>
	Insert Arrangement	<b>MS18274-2</b>
	Shell Plating Material	<b>Zinc</b>
Contact Features	Contact Style	<b>Crimp Snap-In</b>
	Contact Size	<b>22</b>
	Contact Type	<b>Socket</b>
Mechanical Attachment	Mounting Style	<b>Mounting Holes</b>
	Mounting Hole Diameter	<b>3.05 mm [ .12 in ]</b>
Operation/Application	ULTRA-LITE Connector	<b>No</b>
Industry Standards	NASA Qualification	<b>No</b>
Packaging Features	Packaging Method	<b>Carton</b>
Other	Comment	<b>"Z" is stamped on connectors following M24308 part number as required. "Z" designates zinc shell plating., Size 22 sockets supplied with receptacles are loose piece.</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)