

Printed-circuit board connector - MC 1,5/ 2-G-3,5 P14 THR - 1788945

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: SMD/THT/THR



Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 046356 610889
Weight per Piece (excluding packing)	0.7 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Length	9.2 mm
Pitch	3.5 mm
Dimension a	3.5 mm
Pin dimensions	0,8 x 0,8 mm
Hole diameter	1.4 mm

General

Range of articles	MC 1,5/...-G-THR
Insulating material group	IIIa
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	160 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	250 V
Connection in acc. with standard	EN-VDE

Printed-circuit board connector - MC 1,5/ 2-G-3,5 P14 THR - 1788945

Technical data

General

Nominal current I_N	8 A
Maximum load current	8 A
Insulating material	LCP
Inflammability class according to UL 94	V0
Color	black
Number of positions	2

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Printed-circuit board connector - MC 1,5/ 2-G-3,5 P14 THR - 1788945

Approvals

Approval details

UL Recognized 		
	B	D
Nominal current I_N	8 A	8 A
Nominal voltage U_N	300 V	300 V

cUL Recognized 		
	B	D
Nominal current I_N	8 A	8 A
Nominal voltage U_N	300 V	300 V


VDE Gutachten mit Fertigungsüberwachung 	
Nominal current I_N	8 A
Nominal voltage U_N	160 V

EAC


cULus Recognized 
--

Drawings

Drilling diagram




Dimensioned drawing



Printed-circuit board connector - MC 1,5/ 2-G-3,5 P14 THR - 1788945

Diagram



Type: MC 1,5/...-ST(F)-3,5 with MC 1,5/...-G(F)-3,5 P.. THR