

Printed-circuit board connector - GMSTBV 2,5/10-GF-7,62 EX - 1796746

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 12 A, Nominal current (Ex): 12 A, Nominal voltage (Ex): 352 V, Number of positions: 2, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Mounting: Soldering



Why buy this product

- Ex approval for voltages up to 275 V



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 50 pc |
| GTIN |  4 046356 636872 |
| Weight per Piece (excluding packing) | 24.6 g |
| Custom tariff number | 85366990 |
| Country of origin | Germany |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|-----------------------|----------|
| Pitch | 7.62 mm |
| Dimension a | 68.58 mm |
| Constructional height | 12 mm |
| Pin dimensions | 1 x 1 mm |
| Hole diameter | 1.4 mm |

General

| | |
|--|---------------------|
| Range of articles | GMSTBV 2,5/..-GF-EX |
| Insulating material group | I |
| Rated voltage (III/3) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 12 A |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |

Printed-circuit board connector - GMSTBV 2,5/10-GF-7,62 EX - 1796746

Technical data

General

| | |
|---------------------|-------|
| Color | green |
| Number of positions | 2 |

Ex-specific data

| | |
|---------------------------------|--------------------------|
| Identification | 0344# II 2GD Ex e IIC Gb |
| EU type-examination certificate | KEMA 10ATEX0196 U |
| IECEX certificate | IECEX KEM 10.0093U |
| Rated voltage | 352 V |
| Rated current | 12 A |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |


UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Drawings

Printed-circuit board connector - GMSTBV 2,5/10-GF-7,62 EX - 1796746

Drilling diagram



Dimensional drawing

