



## SLIDE SWITCHES



✓ Active

[PRODUCT DRAWING](#)  
English

[3D PDF](#)

### TE CONNECTIVITY (TE) SE1EGR04=SEALED SLIDE SWITCH

Alcoswitch | SE

1825031-2

TE Internal Number: 1825031-2

Alias ID: SE1EGR04

Always EU RoHS/ELV Compliant

Configuration (Pole-Throw) **Single Pole - Double Throw**

Mounting Angle **Right Angle**

Contact Base Material **Phosphor Bronze**

Number of Actuators **Single**

Number of Positions **3**

### Product Drawings

[SWITCH, SLIDE, RIGHT ANGLE, SE\(\\*\\*\)GRA](#)

PDF  
English

### CAD Files

[3D PDF](#)  
PDF  
3D

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[SWITCHES\\_CORE\\_PROGRAM\\_CATALOG](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Actuator Style

**Side**

Threaded Case

**Without**

Switch Style

**Process Sealed**

Terminal Configuration

**Standard**

Product Type

**Switch**

Grade

**Instrumentation**

Grade	Instrumentation	
Switch Type	<b>Slide</b>	
Configuration Features	Configuration (Pole-Throw)	<b>Single Pole - Double Throw</b>
Number of Actuators	<b>Single</b>	
Number of Positions	<b>3</b>	
Operating Function	<b>On Off On</b>	
Process Seal Material	<b>Silicone Rubber</b>	
Body Features	Actuator Material	<b>PA 46</b>
Actuator Color	<b>Yellow</b>	
Actuator Travel	<b>2.2 mm [ .087 in ]</b>	
Contact Features	Contact Base Material	<b>Phosphor Bronze</b>
Contact Plating	<b>Gold</b>	
Termination Features	Termination Type	<b>PC</b>
Mechanical Attachment	Mounting Angle	<b>Right Angle</b>
Mounting Type	<b>Through Hole</b>	
PCB Mount Retention Type	<b>Extended</b>	
PCB Mount Retention	<b>With</b>	
Dimensions	PCB Tail Length	<b>3.3 mm [ .13 in ]</b>
Length	<b>9.5 mm [ .374 in ]</b>	
Actuator Length	<b>2.8 mm [ .1102 in ]</b>	
Width	<b>5 mm [ .19685 in ]</b>	
Identification Marking	Stamped Marking	<b>With</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Tray</b>
Product Compliance	<a href="#">Statement of Compliance</a>	PDF
<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>		

