



1825097-6 Product Details

[Share](#) | [Print](#) | [Email](#)


1825097-6

TE Internal Number: 1825097-6

Active

Pushbutton Switches

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Switch
- Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 0.4VA
- Operating Function = Off [On]

[View all Features](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

- Product Drawings:**
- [PUSHBUTTON SWITCH, TPB SERIES \(PDF, English\)](#)
- Catalog Pages/Data Sheets:**
- [SWITCHES_CORE_PROGRAM_CATALOG \(PDF, English\)](#)
- Product Specifications:**
- None Available
- Application Specifications:**
- None Available
- Instruction Sheets:**
- None Available
- CAD Files:**
- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

- | | |
|--|--|
| <p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Switch • Tactile = Yes • Series = TPB • Mount Angle = Right Angle • Termination Type = Printed Circuit • Actuator Style = Round <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Contact Rating = 0.4VA <p>Dimensions:</p> <ul style="list-style-type: none"> • Actuator Length (mm [in]) = 3.40 [0.134] <p>Body Features:</p> <ul style="list-style-type: none"> • Mount Style = Through-Hole • Actuator Profile = Extended • Actuator Color = Black • Case Material = Thermoplastic (LCP) • Actuator Material = Nylon <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Plating = Gold • Contact Base Material = Copper Alloy <p>Housing Features:</p> <ul style="list-style-type: none"> • Process Sealed = No • Low Profile = No | <p>Configuration Features:</p> <ul style="list-style-type: none"> • Configuration (Pole-Throw) = Single Pole - Single Throw • Operating Function = Off [On] • Ganged = No • ESD Grounding Terminal = Without • Number of Actuators = Single • Illuminated = No • Dust Proof = No • Support Bracket = Without • Snap Action = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Rating = Standard <p>Operation/Application:</p> <ul style="list-style-type: none"> • Actuator Force (g [oz]) = 50.00 - 400.00 [1.770 - 14.120] <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Loose Piece <p>Other:</p> <ul style="list-style-type: none"> • Brand = Alcoswitch |
|--|--|

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference Products](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

[▶](#)

