



## SLIDE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### MSS225004=DPDT SL SW VERT AG

[Alcoswitch](#) | [MSS](#)

1825263-1

TE Internal Number: 1825263-1

Alias ID: MSS225004

[Always EU RoHS/ELV Compliant](#)

Configuration (Pole-Throw) **Double Pole - Double Throw**

Mounting Angle **Vertical**

Contact Base Material **Copper Alloy**

Number of Actuators **Single**

Number of Positions **2**

#### Product Drawings

##### [SLIDE SWITCH, MSS 2250 SERIES, DP-DT, VERTICAL](#)

PDF  
**English**

#### CAD Files

##### [Customer View Model](#)

2D\_DXF.ZIP  
**English**

##### [3D PDF](#)

PDF  
**3D**

##### [Customer View Model](#)

3D\_IGS.ZIP  
**English**

##### [Customer View Model](#)

3D\_STP.ZIP  
**English**

#### Product Environmental Compliance

TE Material Declaration

##### [MD\\_1825263-1\\_04162014034\\_dmtec](#)

PDF  
**English**

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Actuator Style

**Extended, Top**

Threaded Case

**Without**

Terminal Configuration

**Standard**

Product Type

**Switch**


Grade

**Instrumentation**

	Switch Type	Slide
Configuration Features	Configuration (Pole-Throw)	<b>Double Pole - Double Throw</b>
	Number of Actuators	<b>Single</b>
	Number of Positions	<b>2</b>
	Terminals Connected	<b>2-1, 5-4</b>
Body Features	Actuator Material	<b>POM</b>
	Actuator Color	<b>Black</b>
	Actuator Travel	<b>2 mm [ .0787 in ]</b>
Contact Features	Contact Base Material	<b>Copper Alloy</b>
	Contact Current Rating (A)	<b>.3</b>
	Contact Plating	<b>Silver</b>
Termination Features	Termination Type	<b>PC</b>
Mechanical Attachment	Mounting Angle	<b>Vertical</b>
	Mounting Type	<b>Through Hole</b>
	PCB Mount Retention Type	<b>Guide Posts</b>
	PCB Mount Retention	<b>With</b>
Dimensions	PCB Tail Length	<b>3.5 mm [ .137 in ]</b>
	Length	<b>14 mm [ .5472 in ]</b>
	Actuator Length	<b>11 mm [ .433 in ]</b>
	Width	<b>5.8 mm [ .227 in ]</b>
Identification Marking	Stamped Marking	<b>With</b>
Industry Standards	UL Flammability Rating	<b>UL 94-HB</b>
Packaging Features	Packaging Method	<b>Tray</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF  <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

CUSTOMERS ALSO BOUGHT

MOTOR TERMINAL HOUSINGS




FASTON 187 REC HSG 3  
CIR NYLON NAT  
520212-1

Save to List

Find Similar Products

BARRIER STRIPS




JC6-P108-02=JC6  
ASSEMBLY  
JC6-P108-02

Save to List

Find Similar Products

WIRE-TO-BOARD HEADERS & RECEPTACLES




04P MTA100 HDR ASSY  
SQ R/A  
640453-4

Save to List

Find Similar Products

RJ14 CONNECTORS



M/J, LPF, R/A, 6P/4C, TIN,  
BULK PKG  
5555165-2

Save to List

Find Similar Products