

RELAYS, CONTACTORS & SWITCHES

## **TACTILE SWITCHES**





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

## FSM2JLH=6MM TACT SWITCH, HIGH TEMP

Alcoswitch | FSM

1825910-1

TE Internal Number: 1825910-1

Alias ID: FSM2JLH

Always EU RoHS/ELV Compliant

Actuator Style Round

Operating Function No

Contact Base Material Copper Alloy

Contact Plating Silver

Dust Proof No

**Product Drawings** 

6MM TACT SWITCH, THRU-HOLE HIGH TEMP

PDF **English** 

CAD Files

Customer View Model

2D\_DXF.ZIP

3D PDF

PDF **3D** 

Customer View Model

3D\_IGS.ZIP English

Customer View Model

3D\_STP.ZIP **English** 

Catalog Pages/Data Sheets

SWITCHES\_CORE\_PROGRAM\_CATALOG

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Actuator Style

Round

Dust Proof

No

Illuminated

With

Leg Style

Product Type

Kinked Switch

Configuration Features	Operating Function	No
•	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	Ganged	With
	ESD Grounding Terminal	Without
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With
Body Features	Actuator Color	Brown
	Bushing Style	Unthreaded
	Actuator Material	РВТ
	Actuator Force	100 g [ 3.53 oz ]
	Cover Material	PET Film
	Actuator Profile	Extended
	Case Material	Nylon
	Case Color	Black
Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50
Termination Features	Termination Type	Printed Circuit Board
Mechanical Attachment		
Mechanical Attachment	Mounting Type	Through Hole
Mechanical Attachment	Mounting Type  Mounting Angle	Through Hole Vertical
Mechanical Attachment  Housing Features		
	Mounting Angle	Vertical
Housing Features	Mounting Angle  Low Profile	Vertical
Housing Features	Mounting Angle  Low Profile  Process Sealed	Vertical  With  No
	Mounting Angle  Low Profile  Process Sealed  Actuator Length	Vertical  With  No  .7 mm [.028 in]

Usage Conditions	Temperature Rating (°C)	High
Packaging Features	Packaging Method	Loose Piece
Other	Comment	(On) indicates momentary position.
Product Compliance	Statement of Compliance PDF  VIEW ALL PRODUCT COMPLIANCE	