

Article Number: 184-22000



High Density Slotted Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, Gray, 30 ft/BoxDescription:

Base Data		
	Local Order Number	184-22000
	Туре	SLHD2X2
	Color	Gray (GY)
	Features and Benefits	<ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li> <li>Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li> <li>Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.</li> </ul>
	Quantity Per	box
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	High Density Slotted Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, Gray, 30ft/Box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	2.0"
	Width W (Metric)	50.8mm
	Width W2 (Imperial)	2.0"
	Width W2 (Metric)	50.8mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	1.6"
	Width W5 (metric)	40.6mm

2/1/2017 generated on:

## 184-22000



Product Dimensions         Width W6 (imperial)         0.5"           Width W6 (metric)         12.7mm           Height H (Imperial)         2.07"           Height H (Metric)         52.6mm           Mounting Hole Centers (Imperial)         2.0"           Material and Specifications         Polyvinylchloride (PVC)           Material Shortcut         PVC           Flammability         self-extinguishing           Operating Temperature         +122°F (+50°C)           ROHS Compliant         Yes           Certification/Specification         UL           UL Recognized (US)         Yes           Logistic and Packaging         Package Quantity (Imperial)         30.0ft           Package Quantity (Imperial)         9.1m			
Height H (Imperial)   2.07"     Height H (Metric)   52.6mm     Mounting Hole Centers (Imperial)   2.0"     Material and Specifications     Material Shortcut   PVC     Flammability   self-extinguishing     Operating Temperature   +122°F (+50°C)     ROHS Compliant   Yes     Certification/Specification   UL     UL Recognized (US)   Yes     Package Quantity (Imperial)   30.0ft		Width W6 (imperial)	0.5"
Height H (Metric) 52.6mm  Mounting Hole Centers (Imperial) 2.0"  Material and Specifications  Material Polyvinylchloride (PVC)  Material Shortcut PVC  Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification UL  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 30.0ft		Width W6 (metric)	12.7mm
Material and Specifications  Material Polyvinylchloride (PVC)  Material Shortcut PVC  Flammability self-extinguishing Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification UL  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 30.0ft		Height H (Imperial)	2.07"
Material and Specifications  Material Polyvinylchloride (PVC)  Material Shortcut PVC  Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification UL  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 30.0ft		Height H (Metric)	52.6mm
Specifications  Material  Material  Polyvinylchloride (PVC)  Material Shortcut  PVC  Flammability  Self-extinguishing  Operating Temperature  +122°F (+50°C)  ROHS Compliant  Yes  Certification/Specification  UL  UL Recognized (US)  Ves  Logistic and Packaging  Package Quantity (Imperial)  30.0ft		Mounting Hole Centers (Imperial)	2.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 30.0ft			
Flammability Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification UL UL Recognized (US)  Logistic and Packaging  Package Quantity (Imperial)  30.0ft		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification UL  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 30.0ft		Material Shortcut	PVC
ROHS Compliant  Certification/Specification  UL  UL Recognized (US)  Yes  Logistic and Packaging  Package Quantity (Imperial)  30.0ft		Flammability	self-extinguishing
Certification/Specification  UL  UL Recognized (US)  Logistic and Packaging  Package Quantity (Imperial)  30.0ft		Operating Temperature	+122°F (+50°C)
Logistic and Packaging  Package Quantity (Imperial)  Yes  30.0ft		ROHS Compliant	Yes
Logistic and Packaging  Package Quantity (Imperial) 30.0ft		Certification/Specification	UL
Packaging  Package Quantity (Imperial) 30.0ft		UL Recognized (US)	Yes
Package Quantity (Metric) 9.1m		Package Quantity (Imperial)	30.0ft
Tablego Quarkity (month)		Package Quantity (Metric)	9.1m
Customs Number(Schedule B) 3925900000		Customs Number(Schedule B)	3925900000

generated on: 2/1/2017