


DETAIL A
OPTIONAL CONSTRUCTION



3-DIMENSIONAL MODEL
NOT TO SCALE

27.43	1.080
26.67	1.050
20.32	.800
11.68	.460
0.38	.015
0.13	.005
MM	IN

CONVERSION TABLE

- MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK™ CAP OR HEADER.
 - SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS [1.0] LBS. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS [0.5] LBS.
- ⚠ DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.
 - ⚠ FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, NO RIBS OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.
 - 5 NOT MANUFACTURED IN U.S.
 - ⚠ UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE ON EACH SIDE OF HOUSING.
 - ⚠ MATERIAL CORRESPONDING TO THE REQUIREMENTS OF IEC 60335 (INCL. GLOW WIRE TEST 750° C. WITHOUT FLAME)



NATURAL		1863005-1	
COLOR		PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT

DESIGNED BY	DATE	REVISED BY	DATE
DRW. NO.	REV. NO.	REV. DATE	REV. BY
APPROVED BY	DATE	APPROVED BY	DATE
CHECKED BY	DATE	CHECKED BY	DATE
ISSUED BY	DATE	ISSUED BY	DATE

PLUG, 12 CIRCUIT, UNIVERSAL MATE-N-LOK

CUSTOMER DRAWING

1863005