

USED ON

Restricted to: General Release

| Part # | L (meters) | L (feet) | LC-Duplex, Beige | | LC-Duplex, Beige | |
|-------------|-------------------|-----------------|------------------|---------|------------------|---------|
| | | | IL (dB) | RL (dB) | IL (dB) | RL (dB) |
| 4-1906866-3 | 45.540 - 46.460 | 149.40 - 152.42 | 0.57 | - | 0.57 | - |
| 4-1906866-4 | 47.520 - 48.480 | 155.90 - 159.05 | 0.57 | - | 0.57 | - |
| 4-1906866-5 | 128.700 - 131.300 | 422.24 - 430.77 | 0.7 | - | 0.7 | - |
| 4-1906866-6 | 118.800 - 121.200 | 389.76 - 397.63 | 0.68 | - | 0.68 | - |
| 5-1906866-0 | 49.500 - 50.500 | 162.40 - 165.68 | 0.58 | - | 0.58 | - |

THIS DRAWING IS A CONTROLLED DOCUMENT. BFC/ND

Label 1

Per specification 107-1645-1



Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1



Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin

This label is used on all lengths on this drawing.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS TO BE KEPT CONFIDENTIAL AND NOT DISCLOSED TO ANYONE OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
 CE
 DIST
 16

| REV | DATE | BY | CHKD | APPD |
|-----|-----------|----|------|------|
| B | 8/11/2006 | MK | | |
| P | | | | |

| DIMENSIONS: | TOLERANCES UNLESS OTHERWISE SPECIFIED: |
|-------------|--|
| meters | 0 PLC ± . |
| | 1 PLC ± . |
| | 2 PLC ± . |
| | 3 PLC ± . |
| | 4 PLC ± . |

Customer Print

| | | | |
|-------|---|--|------------|
| DIN | Cable Assy Configurator | MATERIAL | HEAT TREAT |
| CHK | Michael Kepko | | |
| APVD | Michael Kepko | AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608 | |
| NAME | FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex to LC-Duplex | | |
| SCALE | SIZE | DRAWING NO | SHEET |
| NTS | A2 | C- 1906866 | 3 of 3 |
| | | | REV B |

D
C
B
A