

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [19276-0003](#)
Status: **Active**
Description: Quixon Quick Disconnect, InsulKrimp™ Style, Female, Fully Insulated Red, 18-22 AWG, Mylar Tap



Series

image - Reference only

Documents:

[Drawing \(PDF\)](#) [Product Specification PS-19902-015 \(PDF\)](#)
[Product Specification PS-19902-011 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR18689
UL E79133

General

Product Family Quick Disconnects
Series [19276](#)
Comments Low Insertion Force
Crimp Quality Equipment Yes
Insulated Fully
Product Name InsulKrimp™, Quixon
Type Quick Disconnect
UPC 884982565098

Physical

Barrel Type Closed
Color - Resin Red
Flammability 94V-2
Gender Female
Glow-Wire Compliant No
Insulation Nylon (PA)
Lock to Mating Part None
Material - Metal Brass
Material - Plating Mating Tin
Net Weight 0.917/g
Orientation Straight
Packaging Type Embossed Tape on Reel
Tab Thickness 0.41mm
Tab Width 7.87mm
Temperature Range - Operating -55°C to +105°C
Wire Insulation Diameter 3.43mm
Wire Size AWG 18, 20, 22

Electrical

Voltage - Maximum 600V

Material Info

Old Part Number AA-2201T-LIF

Reference - Drawing Numbers

Product Specification PS-19902-011, PS-19902-015
Sales Drawing SD-19276-001

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series

[19276Series](#)

Application Tooling | FAQ

*Tooling specifications and manuals are
found by selecting the products below.
Crimp Height Specifications are then
contained in the Application Tooling
Specification document.*

Global

Description	Product #
Mini-Mac™	0638857000
Applicator	
ATP Perishable	0192880049
Tool Kit used in ATP	
Presses that Process	
Product on Tape	